

# BKT

**GROWING TOGETHER**

## AW-702 RIB IMPLEMENT & TRAILER

**Agricultural Tires**



- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.				Max. Load	PSI	Max. Load	PSI	
6.00-16/6 TT		4.0	6.5	28	10	18	1820	54	1655	54	\$	
7.00-12/6 TL		4.3	7.3	27	11	21	1815	49	1655	49		
9.00-13			Under Development									
10.0/80-12/6 TL		9.0	10.4	28	13	38	2755	46	2535	46		
10.0/80-12/6 TL		9.0	10.4	28	13	24	2835	46	2335	46		
10.0/80-12/8 TL		9.0	10.4	28	13	32	3305	61	2755	61		
10.0/80-12/10 TL		9.0	10.4	28	13	33	3750	78	3195	78		
10.0/80-12/8 TL		9.0	10.4	28	13	27	3305	61	2755	61		
10.0/80-12/10 TL		9.0	10.4	28	13	27	3750	78	3195	78		
10.0/75-15.3/8 TT		9.0	10.8	30	13	32	3525	61	3000	61		
10.0/75-15.3/10 TL	43253	9.0	10.8	30	13	35	3970	75	3415	75		
10.0/75-15.3/12 TL		9.0	10.8	30	13	36	4410	93	3750	93		
10.0/75-15.3/14 TT		9.0	10.8	30	13	36	4940	109	4190	109		
10.0/75-15.3/14 TL	63809	9.0	10.8	30	13	36	4940	109	4190	109		
10.0/75-15.3/18 TL		9.0	10.8	30	13	42	5840	103	5205	103		
10.5/65-16/10 TL		9.0	10.8	30	10	36	4880	75	3415	75		
10.5/65-16/14 TL		9.0	10.8	30	10	37	5070	103	4190	103		
10.5/80-18/10 TL		9.0	10.8	35	14	52	5205	73	4300	73		
10.5/80-18/12 TL		9.0	10.8	35	14	52	5675	87	4805	87		
10.5/80-18/14 TL		9.0	10.8	35	14	55	6175	102	5203	102		
11.5/80-15.3/10 TL		9.0	11.7	34	13	47	5070	67	4300	67		
11.5/80-15.3/12 TL	43254	9.0	11.7	34	13	48	5675	81	4805	81		
11.5/80-15.3/14 TL	54966	9.0	11.7	34	13	49	6395	94	5355	94		
11.5/80-15.3/14 TT	43255											
11.5/80-15.3/16 TT		9.0	11.7	34	13	49	6780	107	5675	107		
11.5/80-15.3/18 TL #		9.0	11.7	34	13	54	7165	109	6395	109		
12.5/80-15.3/14 TL		9.0	12.3	35	14	60	6780	84	5840	84		
12.5/80-15.3/16 TT		9.0	12.3	35	14	58	7385	94	6175	94		
12.5/80-18/12 TL	56378	9.0	12.1	38	15	66	6945	73	5840	73		
12.5/80-18/10 TL		9.0	12.1	38	15	65	6395	59	5360	59		
12.5/80-18/12 TL		9.0	12.1	38	15	66	6945	73	5840	73		
12.5/80-18/14 TL		9.0	12.1	38	15	67	7825	86	6615	86		
12.5/80-18/16 TL		9.0	12.1	38	15	68	8265	97	7385	97		
13.0-55-16/12 TL		11.0	13.3	30	13	47	4940	71	4540	71		
13.0-55-16/14 TL		11.0	13.3	30	13	47	5355	84	4940	84		
13.0-55-16/18 TL		11.0	13.3	30	13	49	7165	103	6615	103		
13.0/65-18/12 TL		11.0	13.2	35	14	66	6175	71	5200	71		
13.0/65-18/14 TL		11.0	13.2	35	14	66	6780	84	5675	84		
13.0/65-18/16 TL		11.0	13.2	35	14	73	7385	97	6175	97		

# = Made for special requirements only

## AW-708 FRONT FARM

**Agricultural Tires**



- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.				Max. Load	PSI	Max. Load	PSI	
400/60-15.5/10 TL											\$	
400/60-15.5/10 TL		13	15.9	34	15	70	6005	51	4940	51		
400/60-15.5/14 TL	44994	13	15.9	34	15	71	7165	71	6005	71		
19.0/45-17/10 TL		16	19.3	34	15	86	6175	44	5205	44		
19.0/45-17/14 TL		16	19.3	34	15	92	7385	57	6175	57		
19.0/45-17/18 TL		16	19.3	34	15	94	9920	65	8820	65		
500/50-17/10 TL		16	19.7	37	15	109	7165	39	6395	39		
500/50-17/14 TL		16	19.7	37	15	111	8540	52	7825	52		
500/50-17/16 TL		16	19.7	37	15	119	9370	58	8545	58		
500/50-17/18 TL	71844	16	19.7	37	15	113	9920	64	9095	64		

# AW-909

# Agricultural Tires



- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
10.0/80-12/6 TL		.9	10.4	.28	.9	.38	2755	.46	2535	.46	\$
10.0/80-12/6 TL		.9	10.4	.28	.9	.24	2835	.46	2335	.46	
10.0/80-12/8 TL		.9	10.4	.28	.9	.32	3305	.61	2755	.61	
10.0/80-12/10 TL		.9	10.4	.28	.9	.33	3750	.78	3195	.78	
10.0/80-12/8 TL		.9	10.4	.28	.9	.27	3305	.61	2755	.61	
10.0/80-12/10 TL		.9	10.4	.28	.9	.27	3750	.78	3195	.78	
10.0/75.15.3/10 TL		.9	10.8	.30	.11	.31	3970	.75	3415	.75	
10.0/75.15.3/12 TL		.9	10.8	.30	.11	.32	4410	.93	3750	.93	
10.0/75.15.3/14 TL		.9	10.8	.30	.11	.32	4940	.109	4190	.109	
10.0/75.15.3/16 TL		.9	10.8	.30	.11	.32	5360	.103	4540	.103	
10.0/75.15.3/18 TL		.9	10.8	.30	.11	.38	5840	.103	5205	.103	
11.5/80-15.3/10 TL		.9	11.7	.34	.11	.41	5070	.67	4300	.67	
11.5/80-15.3/12 TL		.9	11.7	.34	.11	.42	5675	.81	4805	.81	
11.5/80-15.3/14 TL		.9	11.7	.34	.11	.42	6395	.94	5355	.94	
11.5/80-15.3/16 TL		.9	11.7	.34	.11	.47	6780	.107	5675	.107	
11.5/80-15.3/18 TL		.9	11.7	.34	.11	.48	7165	.109	6395	.109	
12.5/80-15.3/14 TL		.9	12.3	.35	.11	.53	6780	.84	5840	.84	
15.0/55-17/10 TL		.13	15.4	.33	.12	.55	5675	.52	4675	.52	
15.0/55-17/12 TL		.13	15.4	.33	.12	.55	6175	.61	5205	.61	
15.0/55-17/14 TL		.13	15.4	.33	.12	.56	6780	.71	5675	.71	

# RIB IMPLEMENT

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
10.0/80-12/6 TL		.9	9.6	.29	.23	.38	2755	.46	2535	.46	\$
10.0/80-12/6 TL		.9	9.6	.29	.23	.24	2835	.46	2335	.46	
10.0/80-12/8 TL		.9	9.6	.29	.23	.32	3305	.61	2755	.61	
10.0/80-12/10 TL		.9	9.6	.29	.23	.33	3750	.78	3195	.78	
10.0/80-12/8 TL		.9	9.6	.29	.23	.27	3305	.61	2755	.61	
10.0/80-12/10 TL		.9	9.6	.29	.23	.27	3750	.78	3195	.78	

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# RIB 900

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
400/60-15.5/10 TL		.13	15.9	.34	.14	.66	6005	.51	4940	.51	\$
400/60-15.5/14 TL		.13	15.9	.34	.14	.67	7165	.71	6005	.71	
400/60-15.5/16 TL		.13	15.9	.34	.14	.74	8045	.75	7165	.75	

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# RIB MASTER

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
4215/75-17.5/16 TL		.675	8.7	.30	.13	.43	6005	.131	5510	.131	\$

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# SL 441

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
200/60-14.5/10 TT		.675	8.3	.24	.7	.18	2535	.100	2270	.100	\$
200/60-14.5/14 TT		.675	8.3	.24	.7	.23	2680	.109	2425	.109	

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# SMOOTH

# Agricultural Tires

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
200/60-14.5/10 TT		6.75	8.3	.24	.28	.2535	.100	.2270	.100	.....\$	

# RIB 774-A

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
15.0/55-17/10 TL		.13	15.4	.33	.13	.63	.5675	.52	.4675	.52	.....\$

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# RIB 774-B

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
200/60-14.5/10 TT		6.75	8.3	.24	.12	.25	.2535	.100	.2270	.100	.....\$
200/60-14.5/14 TL		6.75	8.3	.24	.12	.30	.2680	.109	.2425	.109	.....\$

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# RIB 774-C

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
225/75-17.5/12 TL		6.75	8.7	.30	.11	.38	.5840	.94	.5355	.94	.....\$
225/75-17.5/16 TL		6.75	8.7	.30	.11	.38	.6945	.131	.6395	.131	.....\$
12.0-18/16 TL (340/70-18)		.11	13.5	.35	.11	.78	.8820	.103	.8045	.103	.....\$

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# RIB 775

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
300/65-12/8 TL		.9	.12	.27	.12	.46	.3305	.52	.3000	.52	.....\$

- Low section implement tyres, offering high load capacity with minimum soil compaction.
- Ideal tyres for modern farming, suitable for both on and off-the-road applications.

# FLOTATION 558

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
400/55-22.5/14 TL		11.75	15.9	.40	.23	.109	.5205	.51	.4675	.51	.....\$
400/55-22.5/16 TL		11.75	15.9	.40	.23	.111	.5510	.58	.4940	.58	.....\$
500/45-22.5/12 TL		.16	19.7	.40	.23	.123	.4940	.39	.4410	.39	.....\$
500/45-22.5/16 TL		.16	19.7	.40	.23	.130	.5840	.52	.5205	.52	.....\$

- BKT Flotation Implement tyres are specially designed for high load capacities at low inflation pressures, minimising soil compaction and preventing damage to crops.
- Ideal suited for agricultural implement & trailer uses, both on and off-the-road applications.

# FLOTATION 648

## Agricultural Tires



- BKT Flotation Implement tyres are specially designed for high load capacities at low inflation pressures, minimising soil compaction and preventing damage to crops.
- Ideal suited for agricultural implement & trailer uses, both on and off-the-road applications.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
400/60-22.5/16 TL (385/65-22.5)		11.75	15.7	42	27	113	6175	51	4940	51	\$
400/60-22.5/18 TL (385/65-22.5)		11.75	15.7	42	27	124	6945	62	5510	62	
500/50-22.5/12 TL		16	19.7	42	27	131	5510	32	4940	32	
500/50-22.5/16 TL		16	19.7	42	27	136	6615	44	5840	44	
500/60-22.5/12 TL		16	19.7	46	33	171	6395	35	5840	35	
500/60-22.5/16 TL		16	19.7	46	33	174	7605	46	6945	46	
500/60-22.5/18 TL		16	19.7	46	33	174	8050	52	7385	52	
550/45-22.5/12 TL		16	21.7	42	27	142	5675	30	4540	30	
550/45-22.5/16 TL		16	21.7	42	27	150	6780	41	5355	41	
550/60-22.5/12 TL		16	21.7	48	33	204	6945	30	6175	30	
550/60-22.5/16 TL		16	21.7	48	33	217	8265	41	7385	41	
600/50-22.5/12 TL		20	23.6	46	33	205	6780	29	6175	29	
600/50-22.5/16 TL	63801	20	23.6	46	33	208	8045	38	7165	38	
600/55-22.5/12 TL		20	23.6	48	33	226	7605	29	6945	29	
600/55-22.5/16 TL		20	23.6	48	33	241	8820	38	8045	38	
700/40-22.5/12 TL		24	27.6	46	33	238	6945	25	6175	25	
700/40-22.5/16 TL		24	27.6	46	33	242	8265	32	7385	32	
700/50-22.5/12 TL		24	27.6	50	33	261	8820	26	8045	26	
700/50-22.5/16 TL	63808	24	27.6	50	33	276	10470	35	9370	35	
700/50x22.5/16 TL (166E)	61879	24	27.6	50	33	276	10470	35	9370	35	
600/55-26.5/12 TL		20	23.6	53	33	265	8045	29	7165	29	
600/55-26.5/16 TL		20	23.6	53	33	269	9645	38	8820	38	
700/50-26.5/12 TL		24	27.6	53	33	297	9095	26	8265	26	
700/50-26.5/16 TL		24	27.6	53	33	299	10470	35	9370	35	
800/45-26.5/12 TL		28	31.5	53	33	324	9370	25	8540	25	
800/45-26.5/16 TL		28	31.5	53	33	326	11025	32	9920	32	
650/65-30.5/12 TL		20	25.6	65	33	424	10470	25	9370	25	
650/65-30.5/16 TL		20	25.6	65	33	432	12015	32	10745	32	
750/60-30.5/12 TL		24	29.5	65	33	477	11025	25	9920	25	
750/60-30.5/16 TL		24	29.5	65	33	485	13230	32	12015	32	
850/50-30.5/12 TL		28	33.5	65	33	533	12345	22	11025	22	
850/50-30.5/16 TL		28	33.5	65	33	514	14770	32	13225	32	

# V LINE

## Agricultural Tires

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
500/60-22.5/12 TL		16	19.7	46	33	167	6395	35	5840	35	\$
500/60-22.5/16 TL		16	19.7	46	33	167	7605	46	6945	46	
550/60-22.5/12 TL		16	21.7	48	33	188	6945	30	6175	30	
550/60-22.5/16 TL		16	21.7	48	33	189	8265	41	7385	41	

# RIB 774

## Agricultural Tires



- BKT Flotation Implement tyres are specially designed for high load capacities at low inflation pressures, minimising soil compaction and preventing damage to crops.
- Ideal suited for agricultural implement & trailer uses, both on and off-the-road applications.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
550/60-22.5/12 TL		16	21.7	48	18	194	6945	30	6175	30	\$
550/60-22.5/16 TL		16	21.7	48	18	197	8265	41	7385	41	
600/55-22.5/12 TL		20	23.6	48	18	211	7605	29	6945	29	
600/55-22.5/16 TL		20	23.6	48	18	215	8820	38	8045	38	
10.5/65-16/14 TT		9	10.4	29	7	37	5070	103	4190	103	
215/75-17.5/12TL		6.75	8.7	30	11	38	5205	100	4675	100	
215/75-17.5/16 TL		6.75	8.7	30	11	43	6395	131	5840	131	

# FL 630

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	40 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
500/60 R 22.5 TL		16(15,17)	19.8	46.1	.36	236	8545	.58	11685	.58	\$
560/45 R 22.5 TL		16	21.4	42	.36	200	7830	.58	10750	.58	
560/60 R 22.5 TL		16(17,20)	21.4	49	.36	240	10200	.58	13890	.58	
580/65 R 22.5 TL		16	21.9	52	.36	238	10475	.52	14300	.52	
600/50 R 22.5 TL		20	24	46.1	.37	250	9645	.58	13230	.58	
600/55 R 26.5 TL		20	24	52.2	.38		11355	.58	15655	.58	
700/40 R 22.5			UNDER DEVELOPMENT								
710/45 R 22.5			UNDER DEVELOPMENT								
650/55 R 26.5			UNDER DEVELOPMENT								
680/55 R 26.5			UNDER DEVELOPMENT								
710/50 R 26.5			UNDER DEVELOPMENT								
750/45 R 26.5			UNDER DEVELOPMENT								
800/45 R 26.5			UNDER DEVELOPMENT								
710/50 R 30.5			UNDER DEVELOPMENT								
750/60 R 30.5			UNDER DEVELOPMENT								

- Excellent self-cleaning property.
- Non-directional Tread design enabling higher traction forces in both drive directions.
- Higher non-ski depth to give extra life.
- Wide footprint area suitable for soft soil conditions.
- Aggressive shoulder area.
- Suitable for applications such as Free rolling & Drive Wheel with LLV or HLV.

# TR-117

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
11.2-24/6 TT	68120	10			.315	59	2335	.26	\$
11.2-38/4 TT	68121				.315				
14.9-24/4 TT		13	14.9	49	.35	95	2470	.12	
14.9-24/6 TT	68122	13	14.9	49	.35	94	3420	.20	

- Round shaped tyre reduces crop & soil damage.
- Special tyre for irrigation application.
- Tread pattern designed for sufficient traction and self cleaning property.

# AS-504 TRACTION IMPLEMENT

# Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
6.5/80-12/4 TT		5.0	6.4	23	.19	19	1325	.45	1200	.45	\$
6.5/80-12/6 TT		5.0	6.4	23	.19	16	1710	.67	1565	.67	
7.00-12/4 TL		5.5	7.9	27	.23	26	1475	.35	1235	.33	
7.00-12/6 TL	44996	5.5	7.9	27	.23	26	1820	.49	1520	.46	
5.00-15/4 TT		4	5.7	26	.20	13	1170	.42	1045	.42	
5.00-15/6 TT		4	5.7	26	.20	13	1475	.70	1325	.70	
7.5L-15/6 TT		6	8.3	30	.31	33	2755	.62	2470	.62	
7.5L-15/8 TT		6	8.3	30	.31	33	3000	.73	2680	.73	
10.0/75-15.3/8 TL		9	10.4	31	.29	45	3525	.58	3000	.61	
10.0/75-15.3/10 TL	63810	9	10.4	31	.29	45	3970	.75	3415	.75	
11.5/80-15.3/8 TL		9	11.4	34	.29	61	4545	.55	3750	.51	
11.5/80-15.3/12 TL		9	11.4	34	.29	62	5675	.81	4805	.76	
11.5/80-15.3/14 TT		9	11.4	34	.29	59	6395	.87	5840	.94	
6.00-16/6 TT	43277	4.5	6.7	29	.22	20	1820	.51	1655	.51	
7.50-16/6 TL		6	8.4	32	.27	28	2335	.42	2095	.42	
7.50-16/8 TT	43278	6	8.4	32	.27	30	3000	.60	2680	.60	
15/55-17/10 TL	43256	13	15	35	.29	71	5675	.52	4675	.51	
15/55-17/14 TL	58029	13	15	35	.29	72	6780	.71	5675	.67	
19/45-17/14 TL		16	18.3	34	.31	89	7385	.55	6615	.55	
7.50-18/8 TT		6	8.4	33	.27	31	3085	.62	2835	.62	
10.5/80-18/10 TL		9	10.8	36	.27	64	5205	.74	4300	.68	
12.5/80-18/12 TL		9	12.1	39	.35	87	6945	.73	5840	.68	
7.50-20/6 TT		6	8.4	36	.27	34	2600	.42	2335	.42	
7.50-20/8 TT	43281	6	8.4	36	.27	34	3305	.60	3000	.60	
16.0/70-20/10 TL		14	16.5	43	.38	136	8045	.49	6780	.46	
16.0/70-20/12 TL		14	16.5	43	.38	138	9095	.59	7605	.59	
16.0/70-20/14 TL	43257	14	16.5	43	.38	139	9920	.70	8265	.65	
15.5/80-24/10# TL		13	15.5	50	.50	143	9920	.49	8265	.46	
15.5/80-24/12 TL	43258	13	15.5	50	.50	143	10745	.58	9095	.57	
15.5/80-24/14 TL		13	15.5	50	.50	144	1685	.67	9920	.65	
15.5/80-24/16# TL		13	15.5	50	.50	155	12785	.75	10745	.75	
16.5/85-24/10 TL		13	16.3	52	.50	171	11355	.49	10195	.44	
16.5/85-24/12 TL		13	16.3	52	.50	172	12785	.58	11355	.54	
16.5/85-24/16# TL		13	16.3	52	.50	182	14770	.73	13225	.73	
16.5/85-28			UNDER DEVELOPMENT								

TT = Tube Type TL = Tubless # = Made for special requirements only

## AS-505 TRACTION IMPLEMENT

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
6.5/80-15/6 TL		.5	.64	.26	.24	.21	.1985	.67	.1820	.68	\$	
6.5/80-15/8 TL		.5	.64	.26	.24	.22	.2335	.91	.2095	.91		

- Traction patterns, suitably designed for on and off-the-road use, in all weather conditions.
- Patterns are engineered to provide excellent traction to drive wheels and are suited for both implement and industrial/construction applications.

## TR-882 TRACTION IMPLEMENT

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
400/60-15.5/8 TL		.13	.15.7	.34	.25	.75	.5205	.39	.4410	.38	\$	
400/60-15.5/14 TL	.44997	.13	.15.7	.34	.25	.76	.7165	.68	.6005	.65		

- Traction patterns, suitably designed for on and off-the-road use, in all weather conditions.
- Patterns are engineered to provide excellent traction to drive wheels and are suited for both implement and industrial/construction applications.

## AT-603 TRACTION IMPLEMENT

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
10.5/80-18/10 TL		.9	.10.8	.36	.27	.64	.5205	.74	.4300	.68	\$	
12.5/80-18/12 TL		.9	.12.1	.39	.35	.87	.6945	.73	.5840	.68		
12.5/80-18/12 TL		.9	.12.1	.39	.35	.87	.6945	.74	.6175	.68		
12.5/80-18/16 TL		.9	.12.1	.39	.35	.88	.8265	.97	.7385	.97		

- Traction patterns, suitably designed for on and off-the-road use, in all weather conditions.
- Patterns are engineered to provide excellent traction to drive wheels and are suited for both implement and industrial/construction applications.

## TR-675 TRACTION IMPLEMENT

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
500/60-22.5/12 TL		.16	.19.7	.47	.47	.201	.12235	.48	.11025	.48	\$	
500/60-22.5/16 TL		.16	.19.7	.47	.47	.203	.14330	.64	.12785	.64		
550/60-22.5/12 TL		.16	.21.7	.50	.47	.234	.13225	.42	.12015	.42		
550/60-22.5/16 TL		.16	.21.7	.50	.47	.247	.16095	.55	.14330	.55		

- Traction patterns, suitably designed for on and off-the-road use, in all weather conditions.
- Patterns are engineered to provide excellent traction to drive wheels and are suited for both implement and industrial/construction applications.

# I-1 FARM IMPLEMENT

## Agricultural Tires



- Multirib, Low section I-1 tires are designed to provide high flotation and high load capacity and low inflation pressures.
- Suitable for both on and off-the-road service.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	40 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
6.70-15/6 TT	56372	4.5	.68	.28	.7	.17	.1610	.44	..\$
9.5L-14/6 TT		7.0	.94	.29	.9	.23	.1930	.32	
9.5L-14/8 TT	43263	7.0	.94	.29	.9	.24	.2405	.44	
6.70-15/6 TT		4.5	.68	.28	.7	.17	.1610	.44	
6.70-15/8 TT		4.5	.68	.28	.7	.20	.1875	.57	
9.5L-15/6 TT		7.0	.95	.30	.9	.25	.2040	.32	
9.5L-15/8 TT	43264	7.0	.95	.30	.9	.26	.2470	.44	
9.5L-15/8 TL	44992	7.0	.95	.30	.9	.28	.2470	.44	
9.5L-15/12 TL		7.0	.95	.30	.9	.32	.2865	.56	
11L-15/8 TT	43265	8.0	1.06	.30	1.0	.30	.2535	.36	
11L-15/8 TL	56373	8.0	1.06	.30	1.0	.32	.2532	.36	
11L-15/10 TT		8.0	1.06	.30	1.0	.32	.2910	.44	
12.5L-15/8 TT		10.0	1.22	.32	1.1	.41	.3000	.36	
12.5L-15/8 TL	56374	10.0	1.22	.32	1.1	.44	.3000	.36	
12.5L-15/10 TT	44993	10.0	1.22	.32	1.1	.41	.3415	.44	
12.5L-15/10 TL		10.0	1.22	.32	1.1	.44	.3415	.44	
12.5L-15/12 TT		10.0	1.22	.32	1.1	.42	.3860	.52	
12.5L-15/12 TL	74105	10.0	1.22	.32	1.1	.45	.3860	.52	
7.50-16/8 TT	56375	5.5	.81	.31	.7	.26	.2335	.48	
9.00-16/10 TT	56376	6.0	.92	.33	.9	.37	.3305	.52	
11L-16/8 TT	56377	8.0	1.06	.31	1.0	.31	.2680	.36	
11L-16/10 TT		8.0	1.06	.31	1.0	.34	.3000	.44	
12.5L-16/8 TT		10.0	1.22	.33	1.1	.42	.3085	.36	
12.5L-16/10 TT		10.0	1.22	.33	1.1	.43	.3525	.44	
12.5L-16/12 TT		10.0	1.22	.33	1.1	.44	.3970	.52	

# INDUSTRIAL RIB F-3

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
11L-15/10 TL	43235	.8	.11	.32	.16	.50	.2612	.52	.2337	.52	..\$
11L-15/12 TL		.8	.11	.32	.16	.50	.2844	.61	.2557	.61	
11L-16/10 TL	43270	.8	.11	.33	.16	.52	.2723	.52	.2469	.52	
11L-16/12 TL #	56346	.8	.11	.33	.16	.53	.3053	.64	.2756	.64	

# = Made for special requirements only.

- Low section height design, with highway tread pattern, suitable for agricultural implement & trailers, as also industrial applications such as backhoe loader.

# MULTI RIB F-3

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
11.00-16/12 TL		10	.12	.37	.15	.66	.59		.59	..\$	

- Low section height design, with highway tread pattern, suitable for agricultural implement & trailers, as also industrial applications such as backhoe loader.

# PRO RIB F2M FRONT FARM

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
9.5L-15/8 TL	63542	7.0	.95	.31	.22	.39	.1870	.48	..\$
11L-15/8 TL	63543	8.0	.11	.31	.26	.44	.2090	.44	
10.00-16/8 TT	63544	8.0	.11	.35	.26	.46	.2330	.44	
11.00-16/8 TT	63545	10.0	1.32	.37	.30	.61	.2595	.41	
14L-16.1/12 TL	63546	11.0	1.42	.39	.33	1.00	.3850	.52	

- Specially made for front fitment for tractors working on hard surfaces.
- Best at handling heavy loads on hard surfaces.
- Steers easily and offers excellent load distribution and flotation.
- Strong nylon carcass.

# TF-8181 F-2 TRACTOR FRONT

## Agricultural Tires



- Ideal for use on tractor front for field operations and regular transport.
- Sturdy shoulder bars offer excellent sidewall protection.
- Wider tread area guarantees longer life.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
5.00-15/6 TT		4	5.6	26	15	13	990		785	55	\$	
4.50-16/4 TT		3	4.8	26	13	12	805		640	45		
5.00-16/4 TT		4	5.5	27	15	14	880		715	41		
5.00-16/6 TT	56334	4	5.5	27	15	14	1100		880	61		
5.50-16/6 TT	56335	4	6.2	28	17	16	1170		935	54		
6.00-16/6 TT	56336	4.5	6.7	29	18	20	1235		990	48		
6.00-16/8 TT		4.5	6.7	29	18	23	1475		1200	62		
6.50-16/6 TT	56337	4.5	7.1	30	22	24	1355		1075	45		
7.50-16/6 TT		5.5	8.1	32	26	34	1655		1325	41		
7.50-16/8 TT		5.5	8.1	32	26	35	1930		1520	54		
7.50-18/6 TT		5.5	8.2	34	26	34	1820		1475	41		
7.50-18/8 TT		5.5	8.2	34	26	38	2095		1655	54		
6.00-19/4 TT		4.5	6.5	32	18	22	1135		1000	33		
6.00-19/6 TT		4.5	6.5	32	18	22	1435		1135	48		
6.50-20/6 TT		4.5	6.9	34	22	30	1610		1280	45		
7.50-20/6 TT		5.5	8.1	36	26	38	1930		1565	41		
7.50-20/8 TT		5.5	8.1	36	26	42	2205		1820	49		

# TF-9090 TRI RIB F-2 FRONT FARM

## Agricultural Tires



- 3 Rib front wheel tyres, designed for easy steering. Strong nylon carcass ensures good performance on tractors fitted with implements such as a front loader or front mover.
- Also suitable for use on certain agricultural machines.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
5.00-15/4 TT	57926	4	5.5	26	14	13	805		640	41	\$	
5.50-16/6 TT	72950	4	5.9	28	17	18	1170		935	54		
6.00-16/6 TT	44987	4.5	6.7	29	23	20	1235		990	48		
6.00-16/8 TT	61748	4.5	6.7	29	23	22	1475		1200	62		
6.50-16/6 TT	44988	4.5	7.1	30	23	24	1355		1075	45		
6.50-16/8 TT		4.5	7.1	30	23	27	1565		1235	57		
7.50-16/6 TT	56341	5.5	8.1	32	26	31	1655		1325	41		
7.50-16/8 TT	44989	5.5	8.1	32	26	34	1930		1565	54		
9.00-16/8 TT		8	9.3	34	31	49	2405		1930	45		
9.00-16/10 TT	43234	8	9.3	34	31	49	2755		2205	57		
10.00-16/8 TT	44990	8	10.8	35	35	51	2680		2150	41		
10.00-16/10 TT		8	10.8	35	35	52	3000		2405	49		
11.00-16/8 TT	44991	10	12.6	38	37	67	2910		2335	36		
7.50-18/6 TT	56342	5.5	8.1	34	26	33	1820		1475	41		
7.50-18/8 TT	56397	5.5	8.1	34	26	37	2095		1655	54		
4.00-19/4 TT	56343	3.00	4.5	28	14	12	785		615	49		
6.00-19/6 TT	56398	4.50	6.6	32	20	22	1435		1135	48		
7.50-20/6 TT	56399	5.50	8.1	36	26	36	1930		1565	41		
7.50-20/8 TT	56400	5.50	8.1	36	26	40	2205		1820	49		

# POWER RIB-F2 TRACTOR FRONT

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI	Max. Load	PSI		
11L-15 SL TL		8	11	32	29	58	2335		2095	44	\$	

- Four Rib tyre offers easy steering and excellent load distribution.
- Best for handling heavy loads.

# TR-270 R-2

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	25 MPH		PRICE
			S. Width	O.D.	Max. Load			PSI		
23.1-26/8 TL		20	23.2	65	110	392	5675	16	\$	
18.4-30/8 TL		16	18.3	62	104	270	4805	20		
23.1-30/8 TL		20	23.2	69	110	422	6005	16		
18.4-34/8 TL		16	18.3	66	101	291	5070	20		
23.1-34/8 TL		20	23.2	73	110	456	6395	16		
18.4-38/8 TL		16	18.3	70	101	317	5355	20		
20.8-38/10 TL		18	20.9	72	106		6945	22		

- Extra deep Tread specially designed to get excellent traction on wet and sticky soil with excellent self cleaning properties, preventing mud clogging between the lug.
- Sidewall rubber preventing weather cracking.
- Tough tread compound to resist fast wear.



# TR-171 R-1 BIAS REAR TRACTOR

## Agricultural Tires



- Specially design for excellent traction & self cleaning property for wet soil & paddy fields.
- Extra deep lugs provide improved performance with increased tyre life.
- Natural rubber tread compound for better wear & tear resistance.
- Tough nylon casing for longer tyre life.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
8-18/4 TT		.6	.75	.33	.48	.41	.1145	.23	..\$
8.3-20/6 TT	.54685	.7	.79	.35	.56	.46	.1565	.34	..
9.5-20/6 TT	.54686	.8	.93	.37	.56	.62	.1875	.32	..
11.2-20/8 TT	.54687	.10	.11.2	.40	.60	.77	.2535	.38	..
8.3-24/6 TT		.7	.79	.39	.56	.55	.1785	.35	..
9.5-24/6 TT		.8	.93	.41	.56	.75	.2070	.30	..
11.2-24/6 TT		.10	.11.2	.43	.60	.90	.2340	.26	..
12.4-24/8 TT		.11.0	.12.4	.46	.64	.98	.3120	.33	..
13.6-24/6 TT		.12	.14	.48	.67	1.28	.2955	.23	..
14.9-24/6 TT	.70734	.13	.15.4	.50	.70	1.46	.3415	.20	..
13.6-26/6 TT	.64742	.11	.13.4	.50	.67	1.35	.3050	.23	..
12.4-28/6 TT		.11	.12.4	.50	.64	1.19	.2833	.25	..
13.6-28/6 TT		.12	.13.8	.51	.67	1.46	.3195	.23	..
14.9-28/8 TT		.13	.15.3	.54	.70	1.63	.4189	.26	..

# FLOTATION 351

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
242X25-20/12 TL		.20.5	.23.8	.44	.47	.238	.4805	.45	..\$
48X25-20/10 TL		.20.5	.24.8	.50	.59	.311	.6175	.35	..
48X31-20/12 TL		.26	.30.5	.50	.59	.385	.6945	.40	..
66X43-25			UNDER DEVELOPMENT						..

- Extra deep tread lugs offers extra traction & longer life.
- Wide Tyre for high load application at low inflation pressure.

# MP-567 MULTI-PURPOSE TRUCK

## Agricultural Tires



- Good traction in all weather conditions.
- Good on-the-road driveability.
- Good self cleaning properties.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	56 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
10.0/75-15.3/10 TT		.9	.10.2	.30	.27	.43			.3305	.57	..\$
10.0/75-15.3/10 TL	.44998	.9	.10.2	.30	.27	.45			.3305	.57	..
10.0/75-15.3/12 TL		.9	.10.2	.30	.27	.45			.3750	.68	..
10.0/75-15.3/14 TL		.9	.10.2	.30	.27	.45			.4190	.80	..
11.5/80-15.3/10 TT		.9	.11.5	.34	.27	.68			.4190	.49	..
11.5/80-15.3/10 TL		.9	.11.5	.34	.27	.62			.4190	.49	..
11.5/80-15.3/14 TT		.9	.11.5	.34	.27	.60			.5355	.69	..
11.5/80-15.3/14 TL	.44999	.9	.11.5	.34	.27	.62			.5355	.69	..
11.5/80-15.3/18 TL		.9	.11.5	.34	.27	.68			.6175	.87	..
10.5-18/10 TT		.9	.10.6	.39	.27	.64	.3750	.54	.4310	.54	..
10.5-18/10 TL		.9	.10.6	.39	.27	.68	.3750	.54	.4310	.54	..
12.5-18/10 TT		.11	.12.8	.39	.27	.88	.3970	.44	.4565	.44	..
12.5-18/10 TL		.11	.12.8	.39	.27	.91	.3970	.44	.4565	.44	..
12.5-18/12 TT		.11	.12.8	.39	.27	.90	.4300	.51	.4950	.51	..
12.5-18/12 TL		.11	.12.8	.39	.27	.93	.4300	.51	.4950	.51	..
18-19.5/16 TL	.45000	.14	.18.1	.43	.31	1.55	.8815	.73	.9345	.73	..
18-19.5/18 TL		.14	.18.1	.43	.31	1.65	1.1350	1.05	1.2035	1.05	..
10.5-20/10 TT		.9	.10.6	.38	.27	.75	.3970	.54	.4565	.54	..
10.5-20/10 TL	.43251	.9	.10.6	.38	.27	.78	.3970	.54	.4565	.54	..
12.5-20/10 TT		.11	.12.8	.41	.27	.93	.4080	.44	.4695	.44	..
12.5-20/10 TL		.11	.12.8	.41	.27	.96	.4080	.44	.4695	.44	..
12.5-20/12 TT		.11	.12.8	.41	.27	.98	.4410	.51	.5070	.51	..
12.5-20/12 TL	.43252	.11	.12.8	.41	.27	1.01	.4410	.51	.5070	.51	..
14.5-20/10 TL		.11	.14.2	.44	.31	1.18	.4410	.36	.5070	.36	..
14.5-20/12 TL	.43266	.11	.14.2	.44	.31	1.26	.4940	.44	.5690	.44	..
14.5-20/14 TL		.11	.14.2	.44	.31	1.28	.5355	.51	.6150	.51	..
14.5-20/16 TL		.11	.14.2	.44	.31	1.28	.5675	.58	.6525	.58	..
14.5-20/18 TL		.11	.14.2	.44	.31	1.29	.6005	.65	.6910	.65	..
16.0/70-20/14 TL	.43267	.13	.15.9	.44	.31	1.44	.6395	.51	.7365	.51	..

\* These loads are only for 35mph (it's highest operating speed)

# MP-570 MULTI-PURPOSE TRUCK

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	56 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
12.5-18/10 TT		.11	.12.1	.39	.30	.94	.4255	.44	.4410	.44	..\$
12.5-20/12 TL		.11	.13.2	.41	.30	1.10	.4540	.51	.5070	.51	..
14.5-20/12 TL	.44643	.11	.14.2	.44	.31	1.27	.5355	.44	.5510	.44	..

- Good traction in all weather conditions.
- Good on-the-road driveability.
- Good self cleaning properties.

## MP-585 MULTI-PURPOSE TRUCK

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	56 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
10.5-20/10		.9	10.7	.38	.19	.69	.3970	.54	.4410	.54	\$
12.5-20/12		.11	13.2	.41	.23	.104	.4410	.51	.4940	.51	\$

Tires for multi purpose trucks, designed for use on highways, off-the-road and agricultural applications. Specially engineered tread patterns offers maximum flexibility.

- Good traction in all weather conditions.
- Good on-the-road driveability.
- Good self cleaning properties.

## MP-590 MULTI-PURPOSE TRUCK

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	56 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
18-22.5/16		.14	18.3	.47	.39	.194	.9670	.80	10745	.80	\$

- Good traction in all weather conditions.
- Good on-the-road driveability.
- Good self cleaning properties.

## MP-600 MULTI-PURPOSE TRUCK

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	56 MPH		25 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
10.5-18/10		.9	10.7	.36	.27	.63			4190	.54	\$
12.5-18/10		.11	12.1	.39	.30	.94			4410	.44	\$
12.5-18/12		.11	12.1	.39	.30	.97			4940	.51	\$
16.0/70-24/14		.13	15.9	.47	.42	.166			7825	.51	\$

- Good traction in all weather conditions.
- Good on-the-road driveability.
- Good self cleaning properties.

## TR-126 R-1 BIAS REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
6-14/4 TT	.56338	.5	6.2	.26	.33	.19	.660	.29	\$
7-14/4 TT	.56339	.5	6.7	.28	.33	.19	.825	.26	\$

- Heavy duty drive wheel tyre with dual angled tread lugs, which provide high traction and long life in both, field and on-the-road operations.
- Strong casing for excellent stability and safety to the operator.
- Also ideally suited for industrial/construction application.

## TR-144 R-1 BIAS REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
7-16/4 TT	.44984	.6	7.2	.29	.31	.25	.855	.23	\$
8-16/6 TT	.44985	.6	7.8	.31	.33	.30	1355	.27	\$
8-18/6 TT		.6	7.8	.33	.33	.35	2140	.27	\$
8.3-20/6 TT		.7	8.3	.35	.35	.39	1565	.35	\$
9.5-22/6 TT		.8	9.6	.39	.35	.50	1958	.32	\$

- Heavy duty drive wheel tyre with dual angled tread lugs, which provide high traction and long life in both, field and on-the-road operations.
- Strong casing for excellent stability and safety to the operator.
- Also ideally suited for industrial/construction application.

# TR-136 R-1 BIAS REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
16.9-30/8 D TT (21 LUGS)	45552	15	16.9	.59	.47	169	5070	.25	\$
18.4-26/12 TL		16	18.9	.57	.52	202	6615	.33	
18.4-30/14 TT		16	18.3	.61	.52	248	7605	.38	

- Heavy duty drive wheel tyre with dual angled tread lugs, which provide high traction and long life in both, field and on-the-road operations.
- Strong casing for excellent stability and safety to the operator.
- Also ideally suited for industrial/construction application.

# TR-135 R-1 BIAS REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
8.00-20/6 TT	44972	.6	.92	.38	.34	.56	2040	.30	\$
8.00-20/8 TT		.6	.92	.38	.34	.56	2400	.40	
8.00-20/8		.6	.92	.38	.34	.56	2400	.40	
9.5-20/6	44973	.8	9.4	.38	.35	.50	1875	.32	
8.3-24/6	44974	.7	8.3	.39	.34	.42	1765	.35	
8.3-24/8	44975	.7	8.3	.39	.34	.44	2040	.45	
9.5-24/6		.8	9.1	.42	.38	.53	2095	.30	
9.5-24/8	44976	.8	9.1	.42	.38	.56	2470	.40	
11.2-24/6		.10	11.2	.43	.41	.68	2336	.26	
11.2-24/8	43213	.10	11.2	.43	.41	.68	2755	.35	
12.4-24/4		.11	12.4	.46	.42	.68	2095	.15	
12.4-24/6		.11	12.4	.46	.42	.86	2680	.25	
12.4-24/8	43214	.11	12.4	.46	.42	.86	3195	.22	
NEW 12.4-24/8	72077	.11	12.4	45.6	.42	.92	3195	.33	
13.6-24/8	43215	.12	13.5	.48	.45	101	3305	.28	
14.9-24/6		.13	14.9	.50	.45	116	3415	.20	
14.9-24/8	43216	.13	14.9	.50	.45	116	3970	.26	
16.9-24/6		.15	16.9	.52	.47	143	3860	.19	
16.9-24/8	43217	.15	16.9	.52	.47	143	4540	.25	
NEW 14.9-26/8 TT	72947	.13	14.7	51.77	.45	126	4080	.26	
NEW 16.9-26/10 TT	72948	.15	16.93	54.3	.47	166	5070	.29	
23.1-26/8		.20	23.1	.62	.53	308.9	6395	.16	
23.1-26/12	43220	.20	23.1	.62	.53	310	8045	.25	
23.1-26/16 TT		.20	23.1	.62	.53	319	9645	.33	
23.1-26/16 TL		.20	23.1	.62	.53	334	9645	.33	
8.3-28/6	44977	.7	8.4	.46	.35	.49	1930	.35	
11.2-28/6		.10	11.2	.47	.41	.80	2470	.26	
11.2-28/8	43221	.10	11.2	.47	.41	.80	2910	.35	
12.4-28		.11	12.4	.50	.42	.98	2790	.25	
12.4-28/8	43222	.11	12.4	.50	.42	.98	3415	.33	
12.4-28/12		.11	12.4	.50	.42	107	3635	.36	
13.6-28/8	43223	.12	13.6	.52	.45	115	3635	.29	
14.9-28/6		.13	14.9	.54	.45	132	3635	.20	
14.9-28/8	43224	.13	14.9	.54	.45	132	4190	.26	
7.2-30/4		.6	7.3	.43	.35	.51	1355	.26	
7.2-30/6	44978	.6	7.3	.43	.35	.49	1520	.33	
9.5-30		.8	9.5	.47	.39	.67	2675	.40	
NEW 14.9-30/8 TT	72949	.13	14.8	55.7	.45	148	4300	.26	
16.9-30/6		.15	16.9	.59	.47	164	4190	.19	
16.9-30/8	43225	.15	16.9	.59	.47	164	5070	.25	
16.9-30/10	44980	.15	16.9	.59	.47	171	5675	.29	
18.4-30/8	43226	.15	18	.61	.48	186	5355	.20	
18.4-30/10		.15	18	.61	.48	197	6395	.26	
18.4-30/12	54674	.15	18	.61	.48	200	7165	.33	
18.4-30/14	54675	.15	18	.61	.48	232	7605	.37	
23.1-30/8	54676	.20	24	.67	.53	329	6615	.16	
23.1-30/12	54677	.20	24	.67	.53	332	8540	.25	
8.3-32/6	54678	.7	8.3	.47	.35	.53	2040	.35	
8.3-32/8		.7	8.3	.47	.35	.56	2400	.46	
9.5-32			under development						
12.4-32/6		.11	12.4	.53	.42	106	3000	.23	
12.4-32/8	54679	.11	12.4	.53	.42	106	3635	.32	
16.9-34/6		.15	16.9	.62	.47	185	4540	.19	
16.9-34/8	43227	.15	16.9	.62	.47	185	5355	.25	
16.9-34/10		.15	16.9	.62	.47	193	5840	.29	
18.4-34/8	43228	.16	18.4	.65	.48	210	5840	.20	
18.4-34/10	54680	.16.0	18.4	.65	.48	210	6615	.26	
18.4-34/12	54681	.16.0	18.4	.65	.48	215	7385	.33	
8.3-36		.7.0	8.3	.51	.31	.58	2150	.35	
9.5-36			under development						
12.4-36/6		.11.0	12.4	.58	.42	116	3195	.25	
12.4-36/8	45551	.11.0	12.4	.58	.42	116	3855	.33	
12.4-36/10		.11.0	12.4	.58	.42	125	4300	.42	
13.6-36/6		.12.0	13.6	.60	.45	138	3635	.23	
13.6-36/8	43229	.12.0	13.6	.60	.45	138	4300	.30	
13.6-38/6		.12.0	13.6	.62	.45	144	3745	.23	
13.6-38/8	43230	.12.0	13.6	.62	.45	144	4300	.29	
13.6-38/12		.12.0	13.6	.62	.45	151	5355	.42	
15.5-38/8	44981	.14.0	15.5	.62	.42	164	4540	.26	
16.9-38/8	43231	.15.0	16.9	.66	.47	209	5675	.25	
16.9-38/10		.15.0	16.9	.66	.47	213	6005	.29	
16.9-38/12		.15.0	16.9	.66	.47	216	6615	.33	
18.4-38/8	43232	.16.0	18.4	.69	.48	239	6005	.20	
18.4-38/12	44982	.16.0	18.4	.69	.48	242	8045	.33	
20.8-38/8	54682	.18.0	20.9	.72	.51	319	6945	.19	
20.8-38/12		.18.0	20.9	.72	.51	332	8820	.29	

## TR-137 R-1 BIAS REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
24.5-32/12 TL	54683	.21	.24.5	.71	.57	.460	.9645	.25	\$
30.5L-32/12 TL	54684	.27	.30.3	.72	.60	.603	10470	.20	
30.5L-32/18 TL	44983	.27	.30.3	.72	.60	.639	13225	.30	

- Heavy duty drive wheel tyre with dual angled tread lugs, which provide high traction and long life in both, field and on-the-road operations.
- Strong casing for excellent stability and safety to the operator.
- Also ideally suited for industrial/construction application.

## TR-387 R-3 REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
18.4-26/10	54688								\$
18.4-26/12	54689	.16	.18.7	.56	.30	.202	.6615	.22	
23.1-26/8	54690	.20	.23.1	.51	.34	.283	.6395	.16	
23.1-26/12	43233	.20	.23.1	.51	.34	.302	.8045	.25	
23.1-26/12 HD		.20	.23.1	.61	.34	.321	10470	.25	
23.1-26/16	54691	.20	.23.1	.51	.34	.307	.9645	.33	
12.4-28/8	54692	.11	.12.8	.47	.22	.89	.3415	.33	
16.9-28/8	54693	.15	.17.3	.55	.26	.142	.4805	.25	
16.9-28/12		.15	.17.3	.55	.26	.180	.6005	.35	
16.9-30/8	54694	.15	.17.3	.57	.26	.149	.5070	.25	
18.4-30/8	54695	.16	.18.7	.59	.28	.179	.5355	.20	

- Specially engineered tread design, provides high flotation. Ideal for use on soft soil, orchards and similar applications.
- Increased tread depth and strong carcass ensure long service life.
- Also suitable for various industrial/construction applications.

## TR-390 R-3 REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
23.1-26/8		.20	.23.1	.51	.34	.283	.6395	.16	\$
23.1-26/12		.20	.23.1	.51	.34	.302	.8045	.25	
23.1-26/16		.20	.23.1	.51	.34	.307	.9645	.33	
28.0L-26/12 TL		.25	.28.1	.61	.34	.372	.8265	.20	
28.0L-26/16 TL		.25	.28.1	.61	.34	.396	.9920	.27	

- Specially engineered tread design, provides high flotation. Ideal for use on soft soil, orchards and similar applications.
- Increased tread depth and strong carcass ensure long service life.
- Also suitable for various industrial/construction applications.

## TR-391 R-3 REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
14.9-24/6 TT		.13	.15.9	.49	.24	.124	.3415	.20	\$
14.9-24/8 TL	54696								

- Specially engineered tread design, provides high flotation. Ideal for use on soft soil, orchards and similar applications.
- Increased tread depth and strong carcass ensure long service life.
- Also suitable for various industrial/construction applications.

## AS 2001 R-1 BIAS REAR TRACTOR

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	20 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	
18.4-26/10 TT	43218	.16	.18.4	.58	.47	.190	.5840	.26	\$
18.4-26/12 TT	43219	.16	.18.4	.58	.47	.190	.6615	.33	
16.9-28/8 TT	44986	.15	.16.9	.56	.50	.173	.4805	.25	
16.9-28/10 TT		.15	.16.9	.56	.50	.173	.5355	.29	

- Heavy duty drive wheel tyre with dual angled tread lugs, which provide high traction and long life in both, field and on-the-road operations.
- Strong casing for excellent stability and safety to the operator.
- Also ideally suited for industrial/construction application.

# AGRIMAX RT 855

## Agricultural Tires



- Deeper tread imparting longer tyre life.
- Advanced Lug Geometry with wider lug angles, maximizing power transmission.
- Broader Tread with optimum number of lugs and open center design, giving excellent traction with minimum soil compaction.
- Strong Nylon casing and rigged polyester belts, providing higher durability by minimizing fatigue.
- Prominent Rim Guard, protecting rim flange from damage.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
380/85R30 TL	.63553	.12	.15	.55	.57	.197	.4800	.23	.4800	.23	..\$
480/80R46 TL	.63554	.16	.18.9	.76	.67	.415	.9350	.35	.9350	.35	..\$
RT-855 R-1W REAR											
280/85R24/4 TL	.44961	.10	.11.5	.43	.51	.93	.2680	.23	.2470	.23	..\$
380/85R24/4 TL	.44962	.12	.15	.49	.56	.162	.131	.23	.3670	.23	..\$
420/85R24/4 TL	.72945		.17.24	.52.12	.61	.205					..\$
340/85R28/4 TL	.44963	.12	.13.9	.51	.55	.147	.3860	.23	.3530	.23	..\$
380/85R28/4 TL	.44964	.12	.15	.53	.56	.181	.4540	.23	.4190	.23	..\$
420/85R28/4 TL	.44965	.15	.17.2	.56	.61	.227	.5355	.23	.4935	.23	..\$
420/85R34/4 TL	.44966	.15	.17.2	.62	.117	.258	.5840	.23	.5355	.23	..\$
460/85R34/4 TL	.44967	.16	.18.7	.65	.65	.298	.6780	.23	.6170	.23	..\$
320/85R36/4 TL	.44968	.11	.13	.57	.52	.163	.3970	.23	.3640	.23	..\$
340/85R38/4 TL	.44969	.12	.13.9	.61	.57	.198	.4540	.23	.4190	.23	..\$
420/85R38/4 TL	.44970	.15	.17.2	.66	.127	.279	.6170	.23	.5675	.23	..\$
460/85R38/4 TL	.44971	.16	.18.7	.69	.67	.325	.7165	.23	.6610	.23	..\$
320/85R24/4 TL	.57100	.11	.13	.45	.52	.117	.3305	.23	.3000	.23	..\$
340/85R24/4 TL	.57101	.12	.13.9	.47	.55	.131	.3640	.23	.3305	.23	..\$
320/85R28/4 TL	.57102	.11	.13	.50	.52	.131	.3530	.23	.3195	.23	..\$
460/85R30/4 TL	.57103	.16	.18.7	.61	.65	.283	.6395	.23	.5840	.23	..\$
380/85R34/4 TL	.57104										..\$
520/85R38/4 TL	.57105	.16	.20.3	.73	.69	.432	.8540	.23	.7825	.23	..\$
480/80R42/4 TL	.57106	.16	.18.9	.72	.68	.385	.7600	.23	.7600	.23	..\$
520/85R42/4 TL	.57107	.16	.20.3	.77	.71	.430	.9100	.23	.9100	.23	..\$
280/85R28/4 TL	.72946	.10	.11.5	.47	.51	.104	.2910	.23	.2680	.23	..\$
420/85R30/4 TL	.67627	.15	.17.2	.58	.61	.236	.5510	.23	.5070	.23	..\$
320/85R32/4 TL		.11	.13	.53	.52	.147	.3750	.23	.3415	.23	..\$
340/85R36/4 TL		.12	.13.9	.59	.55	.184	.4410	.23	.4080	.23	..\$

# RT 765

## Agricultural Tires



- Wider contact patch than the conventional 85 series tyres, having the same diameter.
- Better Traction and stability.
- Sidewall protector.
- Specially designed for Heavy duty applications.

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
240/70R16 TL		.8	.9.6	.29	.36	.48	.1985	.35	.1985	.35	..\$
260/70R16 TL	.63547	.8	.10.2	.30	.37	.50	.2265	.35	.2265	.35	..\$
280/70R16 TL		.9	.11.1	.31	.40	.55	.2465	.35	.2465	.35	..\$
280/70R18 TL	.63548	.9	.11.1	.33	.40	.62	.2600	.35	.2600	.35	..\$
280/70R20 TL	.63549	.9	.11.1	.35	.40	.64	.2755	.35	.2755	.35	..\$
300/70R20 TL		.9	.11.6	.37	.41	.75	.3085	.35	.3085	.35	..\$
320/70R20 TL		.10	.12.6	.39	.41	.86	.3415	.35	.3415	.35	..\$
360/70R20 TL		.11	.14.1	.41	.51	.114	.4080	.35	.4080	.35	..\$
380/70R20 TL		.12	.15	.43	.52	.130	.4410	.35	.4410	.35	..\$
320/70R24 TL		.10	.12.6	.43	.50	.104	.2755	.23	.2755	.23	..\$
360/70R24 TL		.11	.14.1	.45	.51	.134	.3305	.23	.3000	.23	..\$
380/70R24 TL		.12	.15	.47	.52	.139	.3640	.23	.3305	.23	..\$
420/70R24 TL	.63550	.13	.16.5	.49	.55	.174	.4190	.23	.3860	.23	..\$
480/70R24 TL		.15	.18.9	.52	.77	.220	.5200	.23	.4805	.23	..\$
360/70R28 TL		.11	.14.1	.49	.51	.150	.3640	.23	.3305	.23	..\$
380/70R28 TL		.12	.15	.50	.52	.157	.3860	.23	.3530	.23	..\$
420/70R28 TL	.63551	.13	.16.5	.53	.55	.194	.4540	.23	.4190	.23	..\$
480/70R28 TL	.68608	.15	.18.9	.56	.61	.244	.5510	.23	.5070	.23	..\$
480/70R30 TL	.67616	.15	.18.9	.58	.62	.256	.5675	.23	.5200	.23	..\$
480/70R34 TL	.67628	.15	.18.9	.62	.78	.284	.6010	.23	.5510	.23	..\$
520/70R34 TL	.68606	.16	.20.3	.65	.67	.336	.6945	.23	.6395	.23	..\$
480/70R38 TL		.15	.18.9	.66	.62	.306	.6395	.23	.5840	.23	..\$
520/70R38 TL	.68607	.16	.20.3	.69	.67	.366	.7385	.23	.6780	.23	..\$
580/70R38 TL		.18	.22.7	.72	.72	.455	.8545	.23	.7830	.23	..\$
710/70R38 TL	.63552	.23	.28.2	.77	.74	.628	.11685	.23	.11685	.23	..\$
620/70R24 TL	.67629	.20	.24.6	.76	.57	.491	.9920	.23	.9920	.23	..\$
710/70R42 TL	.67630	.23	.28.2	.81	.74		.12350	.23	.12350	.23	..\$

# AGRIMAX RT 945

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions		Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.			Max. Load	PSI	Max. Load	PSI	
380/90R46 TL	.63555	.12	.15	.73	.58	.310	.7825	.41	.7825	.41	..\$

- Specially designed Narrow Tread with Round Shoulders protect valuable crop & soil from damage.
- High speed radial tyres with tough nylon casing & rigid polyester belt.
- Best suited for all types of harvesting and cultivation jobs.

# AGRIMAX RT 955

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	5 MPH		30 MPH		PRICE
			S. Width	O.D.	NSD			Max. Load	PSI	Max. Load	PSI	
230/95R32 TL	63556											\$
270/95R32 TL	63557	.8	10.4	.52	.37	.117	.6615	.52	.4410	.52		
300/95R46 TL	63558	.10	12	.68	.35	.185	.9370	.52	.6175	.52		
230/95R48 TL	63559	.8	9.37	.65	.32	.132	.6780	.52	.4940	.52		
270/95R48 TL	63560	.8	10.4	.68	.37	.164	.8270	.52	.5510	.52		

- Specially designed Narrow Tread with Round Shoulders protect valuable crop & soil from damage.
- High speed radial tyres with tough nylon casing & rigid polyester belt.
- Best suited for all types of harvesting and cultivation jobs.

# RT 657

## Agricultural Tires



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tread Depth	Tire Wt.	25 MPH		30 MPH		PRICE
			S. Width	O.D.	NSD			Max. Load	PSI	Max. Load	PSI	
320/65R18												\$
540/65R28 TL		.16	20.9	.56	.62	.302	.7825	.35	.7165	.35		
650/65R38 TL		.20	25.4	.71	.74	.529	1.1685	.35	1.0750	.35		

- Specially designed Narrow Tread with Round Shoulders protect valuable crop & soil from damage.
- High speed radial tyres with tough nylon casing & rigid polyester belt.
- Best suited for all types of harvesting and cultivation jobs.

# PL-801

## Forklift



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	Under 15 MPH			PRICE
			S. Width	O.D.	NSD			Load Wheel	Steer Wheel	PSI	
500X8/8 TT W/ FLAP	43247	.3	5.3	.18	.16	.12	.2725	.2095	.120		\$
18X7-8/14 TT W/FLAP		.5	6.8	18.5	.17	.20	.4730	.3635	.145		
18X7-8/16 TT W/ FLAP	54697	4.33	6.8	.18	.17	.20	.4730	.3635	.145		
600-9/10 TT W/ FLAP	43248	.4	6.2	.21	.17	.20	.3780	.2910	.123		
6.00-9/12 TT W/FLAP		4.00E	6.2	21.4	.17	.20	.4155	.3195	.145		
21X8-9/14 TT W/ FLAP	45558	.6	7.9	.21	.24	.29	.5150	.4300	.131		
650-10/10 TT W/ FLAP	43249	.5	7.3	.23	.18	.24	.4300	.3305	.112		
700-12/12 TT W/ FLAP	46191	.5	7.4	.27	.18	.33	.5910	.4540	.123		
700-12/14 TT W/ FLAP	43250	.5	7.4	.27	.18	.36	.6075	.4675	.131		
23X5(-13) Tube & Flap not available		3.75P	6.1	25.2	.18	.22	.3295	.2535	.76		
7.00-15/12 TT W/ FLAP (29x8-15)	54698	.55	7.9	.29	.21	.40	.6770	.5205	.120		
7.00-15/14 TT W/ FLAP (29x8-15)	54699	.55	7.9	.29	.21	.44	.7385	.5675	.131		
7.00-15/12 TT W/ FLAP (30X8-15)		.55	8.1	.30	.21	.40	.6885	.5280	.123		
7.00-15/14 TT W/FLAP (30X8-15)		.55	8.1	.30	.21	.44	.7495	.5765	.145		
7.50-15/12 TT W/ FLAP	54700	.6	8.7	.31	.21	.50	.7595	.5840	.116		
7.50-15/14 TT W/ FLAP	54701	.6	8.7	.31	.21	.51	.8025	.6175	.134		
7.50-15/12 (32' O.D) TT W/ FLAP		5.50/6.50	8.7	32.1	.21	.54	.7595	.5840	.116		
7.50-15/14 (32' O.D) TT W/ FLAP		5.50-6.50	8.7	32.1	.21	.55	.8025	.6175	.134		
8.15-15/12 TT W/FLAP		.7	8.5	28.4	.25	.48	.7595	.5840	.120		
8.15-15/14 TT W/ FLAP	54703	.7	8.5	.28	.25	.49	.8310	.6395	.131		
8.25-15/12 TT W/ FLAP		6.0/7.0	9.3	33.6	.22	.63	.8600	.6615	.101		
8.25-15/14 TT W/ FLAP	54704	.65	9.3	.34	.22	.64	.9315	.7165	.116		
250-15/16 TT W/ FLAP	53377	.75	9.3	.29	.24	.67	.9600	.7385	.120		
250-15/20 TT W/ FLAP	54705	.75	9.3	.29	.24	.69	1.1465	.8820	.152		
300-15/18 TT W/ FLAP	53378	.8	11.6	.33	.28	.92	1.2895	.9920	.109		

- **PL-801** is designed for forklift trucks & service on material handling equipment.
- Designed with an Alternate Continuous Lug that provides increased footprint for maximum stability, handling and load distribution.
- Natural Rubber based tread compound is resistant to tears and cuts.

# POWER TRAX HD

## Widewall Forklift



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	Under 15 MPH			PRICE
			S. Width	O.D.	NSD			Load Wheel	Steer Wheel	PSI	
5.00-8/10		.3	5.7	18.9	.17	.16	.3120	.2405	.145		\$
18x7-8/16		4.33	6.8	18.5	.21	.23	.4730	.3635	.145		
6.00-9/10		.4	6.5	21.4	.20	.25	.3780	.2910	.123		
6.00-9/12		.4	6.5	21.4	.20	.25	.4155	.3195	.145		
6.50-10/10		.5	7.8	23.4	.21	.30	.4300	.3305	.112		
6.50-10/12		.5	7.8	23.4	.21	.31	.4730	.3635	.130		
23X9-10/18		6.5	9.25	23.2	.25	.48	.6965	.5360	.130		
23X9-10/20		6.5	9.25	23.2	.25	.49	.7595	.5840	.145		
7.00-12/14		.5	8.1	26.8	.23	.43	.6075	.4675	.130		
27X10-12/14		.8	10	27.2	.28	.60	.7815	.6005	.101		
27X10-12/16		.8	10	27.2	.28	.60	.8600	.6615	.116		
27X10-12/20		.8	10	27.2	.28	.65	1.0175	.7825	.130		
8.15-15/14 (28X9-15)	56407	.7	8.9	.28	.22	.56	.8310	.6395	.130		
8.25-15/14		6.5	9.8	33.3	.24	.80	.9315	.7165	.116		
250-15/16		7.5	9.4	29.3	.24	.70	.9600	.7385	.120		
250-15/18		7.5	9.4	29.3	.24	.72	1.0460	.8050	.138		
250-15/20		7.5	9.4	29.3	.24	.75	1.1465	.8820	.152		
300-15/18		.8	11.8	33.3	.29	1.04	1.2900	.9920	.109		
300-15/20		.8	11.8	33.3	.29	1.10	1.3980	1.0750	.138		
10.00-15/16 (36X11-15)		7.5	11.2	36.1	.26	1.12	1.1465	.8820	.127		
10.00-20/16		7.5	11.2	42.5	.38	1.57	1.3230	1.1025	.130		
10.00-20/18		7.5	11.2	42.5	.38	1.60	1.4110	1.1685	.145		
12.00-20/20	56409	8.5	12.6	45.3	.43	2.17	1.8125	1.5100	.145		
12.00-20/28		8.5	12.6	45.3	.43	2.19	1.8785	1.5655	.149		

- **POWER TRAX HD** is a premium tire, designed for heavy duty service on forklift trucks, material handling & mining equipment.
- The deep tread, extra thick sidewalls & tough casing provide exceptional durability and minimize the risk of punctures & accidental damages.
- Silica & natural rubber in tread compound provides greater chip & tear resistance.
- Specially designed Rim guard ensures protection against flats & wheel damages in the rim flange area.

# POWER TRAX HD SMOOTH

Widewall Forklift



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	Under 15 MPH			PRICE
			S. Width	O.D.				Load Wheel	Steer Wheel	PSI	
12.00-20/20		8.5	12.6	45.3	.43	.226	18125	15105	145	\$	

POWER TRAX HD SMOOTH PATTERN specially designed for applications in ports as well as in mining operations, with extra thick sidewalls.

# FL-252

Widewall Forklift



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	Under 15 MPH			PRICE
			S. Width	O.D.				Load Wheel	Steer Wheel	PSI	
5.00-8/8		3	5.45	18.9	.18	.14	2725	2095	120	\$	
6.00-9/10		4	6.7	21.7	.19	.21	3780	2910	123		
6.50-10/10		5	7.3	23.8	.20	.25	4300	3305	112		
7.00-12/14		5	7.5	27.1	.22	.40	6075	4675	130		
8.15-15/14		7	8.7	28.3	.22	.48	8310	6395	130		
8.25-15/14		6.5	9.4	33.7	.22	.63	9315	7165	116		

FL-252 is widewall tire designed for heavy duty forklift trucks & material handling equipments. A tough casing and thick sidewalls provides excellent durability while specially designed tread pattern provides maximum stability and load distribution.

# SKID POWER (CHEVRON)

Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	5 MPH		10 MPH		PSI	PRICE
			S. Width	O.D.				Max. Load	Max. Load				
700X15/6 TL	43244	5.5	.8	.30	.17	.39	.3175	.2510	.59		\$		

Chevron tread pattern, with nylon construction, designed for skidsteer use. Specially designed casing, for protection to increase puncture resistance.

# SKID POWER

Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	5 MPH			10 MPH			15 MPH			PSI	PRICE
			S. Width	O.D.				Max. Load	Max. Load	Max. Load	Max. Load	Max. Load	Max. Load					
10-16.5/8 TL		8.25	.10	.30.5	.19	.41	.4135	.3265	.3020	.61						\$		
12-16.5/10 TL		9.75	.12	.32.3	.22	.55	.5610	.4430	.4100	.65								
14-17.5/14 TL	43236	10.5	.14	.37	.25	.99	.8555	.6745	.6240	.80								

Natural Rubber based Compound runs cooler & provides good chipping, chunking & tear resistance. Open design provides maximum self cleaning, and adds extra traction.

# SKID POWER HD

Widewall Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			NSD	Tire Wt.	5 MPH		10 MPH		PSI	PRICE
			S. Width	O.D.				Max. Load	Max. Load				
18x8.5-10/8 TL		6	8.1	18.3	.18	.17	1585	1255	.43			\$	
23x8.50-12/6 TL		7	8.5	.23	.18	.25	1810	1430	.50				
26x12-12/8 TL		10.5	12.0	.26	.30	.47	3020	2380	.49				
26x12-12/10 TL		10.5	12.0	.26	.30	.45	3515	2780	.65				
26x12-12/12 TL	74018	10.5	12.0	.26	.30	.48	3825	3020	.75				
27x8.50-15/8 TL		7	8.6	26.6	.18	.34	2890	2280	.61				
27x10.5-15/8 TL		8.5	10.5	26.9	.18	.40	3100	2445	.61				
31x15.5-15/8 TL		13	15.7	31.1	.26	.76		3650	.45				
31x15.5-15/10 TL		13	15.7	31.1	.26	.76		4320	.61				
10-16.5/8 TL		8.25	10.5	30.5	.24	.53	4135	3260	.61				
10-16.5/10 TL	74110	8.25	10.5	30.5	.24	.54	4720	3725	.75				
12-16.5/10 TL		9.75	12.8	33.5	.27	.76	5610	4430	.65				
12-16.5/12 TL	74111	9.75	12.8	33.5	.27	.77	6095	4815	.75				
31.5x13-16.5/10 TL		9.75	13	31.3	.24	.67	5370	4245	.70				
33x15.5-16.5/12 TL		12	15.5	33	.27	.93	6935	5480	.70				
14-17.5/14 TL		10.5	13.8	36.6	.35	116	8555	6745	.80				
15-19.5/14 TL		11.75	15.8	40.8	.35	140	10055	7950	.70				

Premium tire with Extra Deep Tread & thick sidewalls providing better traction, puncture resistance and a longer life. Compounded with a superior blend of Silica and Natural Rubber to provide chip and tear resistance for extended tread life. Specially designed Rim Guard ensures greater protection against flats and wheel damage in th rim flange area.

## SKID POWER SK

## Widewall Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	5 MPH		10 MPH	PSI	PRICE
			S. Width	O.D.	NSD		Max. Load	Max. Load			
10-16.5/8 TL		8.25	10.6	30.5	19	.47	4135	3260	.61	\$	
10-16.5/10 TL		8.25	10.6	30.5	19	.48	4720	3725	.75		
12-16.5/10 TL	72123	9.75	12.3	32.5	22	.66	5610	4430	.65		
12-16.5/12 TL		9.75	12.3	32.5	22	.67	6095	4815	.75		

Newly developed widewall tire, with sidewall and rim guard protectors, meant for the value conscious yet performance oriented applications.

## SURE TRAX HD

## Widewall Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	5 MPH		10 MPH	PSI	PRICE
			S. Width	O.D.	NSD		Max. Load	Max. Load			
10-16.5/10 TL	74109	8.25	10.5	30.9	24	.59	4715	3725	.75	\$	
12-16.5/10 TL		9.75	12.8	33.7	26	.78	5610	4430	.65		
12-16.5/12 TL		9.75	12.8	33.7	26	.79	6095	4815	.75		

Special Tread compound for excellent life on paved/other hard surfaces. Specially designed to maintain the broadest possible contact surface and maximum gripping power.

## POWER TRAX HD

## Widewall Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	5 MPH		10 MPH	PSI	PRICE
			S. Width	O.D.	NSD		Max. Load	Max. Load			
NEW 10L-15/24 TT	74106	7.5	11.2	36.1		.112				\$	
NEW 10-16.5/10 TL	73646										
10-16.5/10 TL	43242	8.25	10.5	31.1	42	.76	4715	3725	.75		
12-16.5/10 TL		9.75	12.8	34.1	42	.98	5610	4430	.65		
12-16.5/12 TL	43243	9.75	12.8	34.1	42	1.00	6315	4995	.80		
12-16.5/14 TL	74112	9.75	12.8	34.1	42	1.04	6780	5360	.90		
NEW 10.00-20/16TT	74107	7.5	11.2		42.5	.157					

Deep Tread, extra thick sidewall and tough casing ensures longer life. Silica and Natural rubber based compound provides greater chip and tear resistance. Made to withstand rough concrete surface. Most suitable for scrap yards, recycling operations, mines, etc.

## JUMBO TRAX HD

## Widewall Skidsteer



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	5 MPH		10 MPH	PSI	PRICE
			S. Width	O.D.	NSD		Max. Load	Max. Load			
10-16.5/10 TL		8.25	10.5	31.3	37	.70	4715	3725	.75	\$	
12-16.5/10 TL		9.75	12.8	33.7	43	.93	5610	4430	.65		

Newly designed tire with premium depth for much higher life on paved road, tarmac and hard surface. Jumbo Trax HD has extra NSD and also has bigger and studier blocks. The specially formulated tread compound provides excellent chip & tear resistance. Extra thick side-wall with rim guard gives protection against damages.

## MINESTAR

## Forklift Mining



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	15 MPH		PSI	PRICE
			S. Width	O.D.	NSD		Max. Load	Max. Load		
8.25-15/20		6.5	9.6	33.4	24	.76	8270	149		\$

MINESTAR is a premium tire, designed for heavy duty service for underground mining equipment.

- The deep tread, wider lugs & extra tough casing provide exceptional durability and minimize the risk of punctures & accidental damages for mining operations.
- Silica & natural rubber in tread compound provides greater chip & tear resistance.

## SKID POWER H.D.

## Forklift Mining



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	15 MPH		PSI	PRICE
			S. Width	O.D.	NSD		Max. Load	Max. Load		
27x10-12/14		8	10	27.6	27	.52	6010	100		\$

SKID POWER H.D. is premium tire with extra deep tread provides better traction & puncture resistance.

- Specially designed compound provides cut/chip & tear resistance for extended tread life.
- Used for industrial & under ground mining operations.



# INDUSTRIAL RIB F-3

# Industrial Tractor Front (F3)



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	20 MPH		PSI	PRICE
			S. Width	O.D.				Max. Load	Max. Load		
11L-15/10 TL		.8	.11	.32	.16	.50	.2610	.2335	.52	..\$	
11L-15/12 TL		.8	.11	.32	.16	.50	.2845	.2555	.61	.....	
11L-16/10 TL		.8	.11	.32.7	.16	.52	.2725	.2470	.52	.....	
11L-16/12 TL	56346	.8	.11	.32.7	.16	.53	.3055	.2755	.64	.....	

- Low section height design, with highway tread pattern, provides excellent durability in industrial applications such as backhoe loader also suitable for use on agricultural implements & trailers.

# TRAC GRADER+

# Grader



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	25 MPH		PSI	PRICE
			S. Width	O.D.				Max. Load	Max. Load		
13.00-24/12 TL	43268	.8	.13.1	.50.3	.31	.145	.600	.6780	.44	..\$	
14.00-24/12 TL	43269	.8	.14.2	.53.1	.31	.165	.6780	.8050	.40	.....	
14.00-24/16 TL	43275	.8	.14.2	.53.1	.31	.169	.8050		.54	.....	

- Rugged sturdy tires for drive wheels of off-th-road equipment.
- Tough carcass and special tread compound with weather and ozone resistant properties to withstand cuts, snags and bruises in the most severe operating conditions.
- An open spaced traction pattern with self cleaning property provides traction capability, ideally suited for Graders.
- Available in "Trac Grader+" and "Super Grader" Patterns.
- Super Grader is a premium tire with heavy duty carcass and more number of lugs ensuring better life.

# SUPER GRADER

# Grader

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	25 MPH		PSI	PRICE
			S. Width	O.D.				Max. Load	Max. Load		
13.00-24/12 TL		.8	.13.1	.50.3	.31	.153	.6005		.44	..\$	
14.00-24/12 TL		.8	.14.2	.52.5	.31	.182	.6780		.40	.....	

# GR-288

# Grader



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	25 MPH		5 MPH		PRICE
			S. Width	O.D.				Max. Load	PSI	Max. Load	PSI	
115.5-25/12 TL	56401	.12	.15.1	.50	.30	.158	.5840	.33	.12350	.58	..\$	
17.5-25/12 TL	56402	.14	.17.5	.52	.32	.192	.6395	.29	.13560	.50	.....	
17.5-25/16 TL	56403	.14	.17.5	.52	.32	.196	.7385	.40	.16095	.69	.....	
20.5-25/16 TL	56404	.17	.20.5	.58	.36	.306	.8820	.33	.18190	.50	.....	
23.5-25/16 TL	56405	.19.5	.23.4	.63	.38	.420	.10470	.29	.24035	.55	.....	
23.5-25/20 TL	56406	.19.5	.23.4	.63.4	.38	.451	.12015	.36	.24035	.55	.....	



**WE ARE YOUR SUPPLIER**

**NOT YOUR COMPETITOR**

# AS-504

## All Terrain Traction



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	Load Capacity at 20 MPH					PSI	PRICE
			S. Width	O.D.	NSD		Free Rolling LLV		Drive Wheel LLV				
							A6 Load Index	Max Load (LBS)	A6 Load Index	Max Load (LBS)			
6.5/80-12/6 TT		5.0	6.4	.23	.19	.16	93	1430	.80	990	.52	\$	
7.00-12/4 TL		5.5	7.9	.27	.23	.26	88	1235	.75	850	.25		
7.00-12/6 TL	44996	5.5	7.9	.27	.23	.26	95	1520	.83	1070	.36		
11.0/65-12/8		9	10.7	.27	.26	.28	39	114	2600	101	1820	.42	
5.00-15/4 TT		4	5.7	.26	.20	.13	79	960	.67	670	.33		
5.00-15/6 TT		4	5.7	.26	.20	.13	88	1235	.75	850	.51		
7.5L-15/6 TT		6	8.3	.30	.30	.33	109	2270	.97	1610	.45		
7.5L-15/8 TT		6	8.3	.30	.31	.33	113	2535	100	1765	.54		
10.0/75-15.3/8 TL		9	10.4	.31	.29	.45	119	3000	106	2095	.45		
10.0/75-15.3/10 TL		9	10.4	.31	.29	.45	123	3415	111	2405	.57		
11.5/80-15.3/8 TL		9	11.4	.34	.29	.60	126	3750	114	2600	.39		
11.5/80-15.3/10 TL		9	11.4	.34	.29	.61	131	4300	119	3000	.49		
11.5/80-15.3/12 TL		9	11.4	.34	.29	.62	135	4805	123	3415	.59		
11.5/80-15.3/14 TT		9	11.4	.34	.29	.59	139	5360	126	3750	.70		
6.00-16/6 TT	43277	4.5	6.7	.29	.22	.20	95	1520	.83	1070	.41		
7.50-16/8 TT/TL	43278	6	8.4	.31	.27	.28	112	2470	.99	1710	.46		
15/55-17/10 TL	43256	13	15	.35	.29	.71	134	4675	122	3305	.38		
15/55-17/14 TL	58029	13	15	.35	.29	.72	141	5675	129	4080	.52		
19/45-17/14 TL		16	18.3	.34	.31	.89	144	6175	131	4300	.41		
7.50-18/8 TT		6	8.4	.33	.27	.31	114	2600	101	1820	.45		
10.5/80-18/10 TL		9	10.8	.36	.27	.64	131	4300	119	3000	.54		
12.5/80-18/12 TL		9	12.1	.39	.35	.87	142	5845	129	4080	.54		
12.5/80-18/16 TL		9	12.1	.39	.35	.87	148	6945	135	4805	.71		
7.50-20/8 TT	43281	6	8.4	.36	.27	.34	116	2755	103	1930	.46		
16.0/70-20/10 TL		14	16.5	.43	.38	136	147	6780	135	4805	.36		
16.0/70-20/14 TL	43257	14	16.5	.43	.38	139	154	8270	142	5845	.51		
15.5/80-24/10# TL		13	15.5	.50	.50	143	154	8270	142	5848	.36		
15.5/80-24/12 TL	43258	13	15.5	.50	.50	143	157	9095	145	6395	.43		
15.5/80-24/14 TL		13	15.5	.50	.50	144	160	9920	148	6945	.51		
15.5/80-24/16# TL		13	15.5	.50	.50	155	163	10750	151	7605	.58		
16.5/85-24/10 TL		13	16.3	.52	.50	171	158	9370	146	6615	.35		
16.5/85-24/12 TL		13	16.3	.52	.50	172	163	10750	151	7605	.41		
16.5/85-24/16# TL		13	16.3	.52	.50	182	168	12350	155	8545	.55		

TT = Tube Type TL = Tubless # = Made for special requirements only

# AS-507

## All Terrain Traction



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	Load Capacity at 20 MPH					PSI	PRICE
			S. Width	O.D.	NSD		Free Rolling LLV		Drive Wheel LLV				
							A6 Load Index	Max Load (LBS)	A6 Load Index	Max Load (LBS)			
185/65-15/4 TL		5.5	7.3	.25	.17	.20	89	1280	.76	880	.41	\$	

# AT-603 BACKHOE/LOADER R4

## All Terrain Traction



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	Load Capacity at 20 MPH					PSI	PRICE
			S. Width	O.D.	NSD		Free Rolling LLV		Drive Wheel LLV				
							A6 Load Index	Max Load (LBS)	A6 Load Index	Max Load (LBS)			
110.5/80-18/10 TL	43245	9	10.8	.36	.27	.64	131	4300	119	3000	.54	\$	
12.5/80-18/12 TL	72661	9	12.1	.39	.35	.87	142	5845	129	4080	.54		

# AT-621

## All Terrain Traction



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	Load Capacity at 20 MPH					PSI	PRICE
			S. Width	O.D.	NSD		Free Rolling LLV		Drive Wheel LLV				
							A6 Load Index	Max Load (LBS)	A6 Load Index	Max Load (LBS)			
12.5/80-18/12 TTT/TL		9	12.1	.38	.35	.94	142	5840	129	4080	.54	\$	
NEW 15.5/60/18/10 TL	72951	13	15.75	.37	.4	.94					.38		
NEW 17.5/65/20/10 TL	72952	14	17.72	.42	.9	129					.35		

# GRIP STAR

## All Terrain Traction



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire Wt.	Load Capacity at 20 MPH					PSI	PRICE
			S. Width	O.D.	NSD		Free Rolling LLV		Drive Wheel LLV				
							A6 Load Index	Max Load (LBS)	A6 Load Index	Max Load (LBS)			
515.5/80-24/16 TL		13	15.4	.50	.50	.163	163	10750	151	7605	.58	\$	

# MT-612

# Multi Purpose Truck

Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	Load Capacity				PRICE
			S. Width	O.D.	NSD			Single		Dual		
								Max. Load	PSI	Max. Load	PSI	
14.00-20/18		.10	.15.35	.49.8	.32	.181	.9920	.95	.8820	.95	.....\$	

- Broad lugs with enough spacing gives highest traction suitable for ON & OFF the road application.
- Extra tread width gives excellent flotation in sand & mud.

# AT-621

# Industrial Tractor Rear



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	Loaded Capacity at 5 MPH		Loaded Capacity at 25 MPH		PRICE
			S. Width	O.D.	NSD			Max. Load	PSI	Max. Load	PSI	
15.5/60-18/10 TL	.13	.15.75	.37.4	.28	.94	.5292	.38					
17.5/65-20 10 TL	.14	.17.72	.42.91	.31	.129	.7045	.35					
17.5L-24/8 TL	.15	.17.71	.49.4	.36	.163	.5360	.25					
16.9-28/12 TL	.15	.17.7	.55.5	.25	.201			.7825	.38			
16.9-30/12 TL	.15	.17.71	.57.48	.37	.229			.8050	.38			

- Pattern engineered to provide excellent traction to drive wheels in severe conditions.
- Wider lugs with optimum gap between them at centre and at shoulder has improved the puncture resistance.
- Better tread life due to usage of wear & cut resistant tread compound.

# R-4 (TR-461)

# Industrial Tractor Rear (R-1, R-3 & R-4)



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	NSD			Max. Load	PSI	Max. Load	PSI	
19.5L-24/12 TL	.17	.19.3	.51.6	.36	.246			.7605	.33			
19.5L-24/14 TL	.17	.19.3	.51.6	.36	.246			.8270	.38			
21L-24/14 TL	.18	.21.25	.54.5	.40	.297			.9095	.36			
16.9-28/14 TL	.15	.17.3	.54.7	.32	.225			.8270	.42			

Specially designed patter with wider foot print and more land area to give higher life on hard surface. Wide wall feature for protection against cuts and bruises.

# TR-459 (R-4)

# Industrial Tractor Rear (R-1, R-3 & R-4)



Tire Size	Code No.	Rim Width	Unloaded Inflated Dimensions			Tire NSD	Tire Wt.	20 MPH		25 MPH		PRICE
			S. Width	O.D.	NSD			Max. Load	PSI	Max. Load	PSI	
14.9-24/12 TL	.43280	.13	.15.4	.49	.33	.129			.6395	.42		
16.9-24/8 TL	.72124	.15	.17.3	.51.6	.35	.155			.5845	.28		
16.9-24/10 TL	.43259	.15	.17.3	.51.6	.35	.157			.6615	.32		
16.9-24/12 TL	.45003	.15	.17.3	.51.6	.35	.158			.7165	.38		
16.9-28/8 TL	.72664	.15	.17.3	.51.6	.35	.158			.7165	.38		
17.5L-24/8 TL		.15	.17.5	.50	.33	.146			.5360	.25		
17.5L-24/10 TL	.72662	.15	.17.5	.50	.33	.148			.6175	.32		
17.5L-24/12 TL	.43260	.15	.17.5	.50	.33	.149			.6945	.39		
18.4-24/12 TL	.53376	.16	.18.6	.54.1	.36	.206			.8545	.36		
19.5L-24/10 TL	.72399	.17	.19.3	.52.2	.35	.192			.6780	.27		
19.5L-24/12 TL	.56344	.17	.19.3	.52.2	.35	.195			.7605	.33		
21LX24/12 TL	.43261	.18	.21	.54.2	.36	.232			.8545	.32		
18.4-26/12 TL	.43279	.16	.18.7	.56.3	.30	.208			.8820	.36		
18.4-26/14 TL		.16	.18.6	.56.1	.36	.225			.9645	.42		
16.9X28/8 TL		.15	.17.3	.55.5	.35	.173			.6395	.27		
16.9X28/10 TL		.15	.17.3	.55.5	.35	.175			.6945	.32		
16.9X28/12 TL	.43262	.15	.17.3	.55.5	.35	.175			.7825	.38		
18.4-28/12 TL	.56345	.16	.18.6	.58.1	.37	.226			.9095	.36		

Drive wheel tires for Industrial Tractors made with a pattern having extra wide lugs with extensive overlap at the center, gives resistance to buckling, tearing and cracking. Super Compound and Tough Nylon casing gives best results on Industrial use as well as for off-the-road and construction sites.