



COOPERTIRES

ZEON RS3

Maximum Performance



UTQG 220 AA

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| 275/40ZR18 99W | 02020 | (9.5) 9.0-11.0 | 51 | 1709 | 26.64 | 11.12 | 10.0 | 778 | 9.5 | 7.5 | 30 | \$ |
| 275/35R20XL 102W | 02021 | (9.5) 9.0-11.0 | 50 | 1874 | 27.57 | 10.70 | 9.66 | 752 | 9.5 | 7.5 | 28 | |



Special Features

- The Cooper Zeon RS3 is a maximum performance, dry traction tire, developed in conjunction with RUSH Performance, to provide ultimate grip, handling and excitement.
- The Cooper Zeon RS3 is perfectly balanced to blend the needs of a track day tire with the requirements of an everyday tire.

ZEON 2XS

Premium, Ultra-High Performance



UTQG V-Rated 280 A A Others 280 AA A

FREE 45-Day Road Test!

Y/W/V-Speed Design Directional Design

Special Features

- The Cooper Zeon 2XS is a premium, (ZR) ultra-high performance summer tire.
- The V-, W- and Y-rated 2XS is designed to provide excellent cornering ability and steering response along with optimum wet and dry traction and high-speed capability.
- As a summer tire, the Cooper Zeon 2XS is not intended to be driven in snow or ice.

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|--------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL Y-RATED | | | | | | | | | | | | |
| 215/45R17 87Y | 01200 | (7.0) 7.0-8.0 | 51 | 1201 | 24.73 | 8.30 | 7.96 | 838 | 10 | 7.9 | 23 | \$ |
| 225/45R17 91Y | 01201 | (7.5) 7.0-8.5 | 51 | 1356 | 24.88 | 9.03 | 8.19 | 833 | 10 | 7.9 | 23 | |
| 235/45R17 94Y | 01202 | (8.0) 7.5-9.0 | 51 | 1477 | 25.32 | 9.30 | 8.59 | 819 | 10 | 7.9 | 25 | |
| 245/40R17 91Y | 01205 | (8.5) 8.0-9.5 | 51 | 1356 | 24.69 | 9.84 | 9.07 | 840 | 10 | 7.9 | 24 | |
| 255/40R17 94Y | 01206 | (9.0) 8.5-10.0 | 51 | 1477 | 25.00 | 10.31 | 9.39 | 829 | 10 | 7.9 | 26 | |
| 225/40R18RE 92Y | 01207 | (8.0) 7.5-9.0 | 50 | 1389 | 25.07 | 9.03 | 8.44 | 827 | 10 | 7.9 | 23 | |
| 235/40R18 91Y | 01208 | (8.5) 8.0-9.5 | 51 | 1356 | 25.37 | 9.55 | 8.75 | 817 | 10 | 7.9 | 25 | |
| 245/40R18XL 97Y | 01209 | (8.5) 8.0-9.5 | 50 | 1609 | 25.69 | 9.85 | 9.07 | 807 | 10 | 7.9 | 26 | |
| 235/35ZR19XL 91Y | 01211 | (8.5) 8.0-9.5 | 50 | 1356 | 25.37 | 9.60 | 8.75 | 817 | 10 | 7.9 | 24 | |
| 255/35ZR19XL 96Y | 01215 | (9.0) 8.5-10.0 | 50 | 1565 | 25.97 | 10.06 | 9.31 | 798 | 10 | 7.9 | 26 | |
| BLACKWALL W-RATED | | | | | | | | | | | | |
| 205/55ZR16 91W | +01224 | (6.5) 5.5-7.5 | 51 | 1356 | 24.85 | 8.49 | 7.42 | 834 | 10 | 7.9 | 22 | |
| 215/55ZR16 93W | +01225 | (7.0) 6.0-7.5 | 51 | 1433 | 25.24 | 8.90 | 7.67 | 821 | 10 | 7.9 | 23 | |
| 225/55ZR16 95W | +01226 | (7.0) 6.0-8.0 | 51 | 1521 | 25.71 | 9.02 | 7.93 | 806 | 10 | 7.9 | 26 | |
| 205/50ZR17XL 93W | 01257 | (6.5) 5.5-7.5 | 50 | 1433 | 25.08 | 8.34 | 7.35 | 827 | 10 | 7.9 | 23 | |
| 205/45ZR17XL 88W | +01258 | (7.0) 6.5-7.5 | 50 | 1235 | 24.21 | 8.12 | 7.39 | 856 | 10 | 7.9 | 21 | |
| 215/45ZR17 87W | +01233 | (7.0) 7.0-8.0 | 51 | 1201 | 24.73 | 8.30 | 7.96 | 838 | 10 | 7.9 | 23 | |
| 245/45R17 95W | 01236 | (8.0) 7.5-9.0 | 51 | 1521 | 25.62 | 9.61 | 8.91 | 809 | 10 | 7.9 | 26 | |
| 255/45R17 98W | 01237 | (8.5) 8.0-9.5 | 51 | 1653 | 26.03 | 10.12 | 9.35 | 796 | 10 | 7.9 | 29 | |
| 205/40R17RE 84W | 01238 | (7.5) 7.0-8.0 | 50 | 1102 | 23.42 | 8.49 | 7.80 | 885 | 10 | 7.9 | 19 | |
| 275/40R17 98W | 01243 | (9.5) 9.0-11.0 | 51 | 1653 | 25.64 | 11.06 | 10.02 | 809 | 10 | 7.9 | 28 | |
| 285/40ZR17 100W | 01259 | (10.0) 9.5-11.0 | 51 | 1764 | 25.95 | 11.61 | 10.50 | 799 | 10 | 7.9 | 32 | |
| 225/45R18RE 95W | 01250 | (7.5) 7.0-8.5 | 50 | 1521 | 25.89 | 9.03 | 8.19 | 801 | 10 | 7.9 | 24 | |
| 245/45R18RE 100W | 01251 | (8.0) 7.5-9.0 | 50 | 1764 | 26.62 | 9.61 | 8.91 | 779 | 10 | 7.9 | 27 | |
| 275/40ZR18 99W | 01261 | (9.5) 9.0-11.0 | 51 | 1709 | 26.64 | 11.06 | 10.04 | 778 | 10 | 7.9 | 29 | |
| 215/35ZR18RE 84W | +01247 | (7.5) 7.0-8.5 | 50 | 1102 | 23.86 | 8.56 | 7.95 | 869 | 10 | 7.9 | 21 | |
| 255/35ZR18XL 94W | 01268 | (9.0) 8.5-10.0 | 50 | 1477 | 24.96 | 10.06 | 9.31 | 831 | 10 | 7.9 | 25 | |
| 265/35ZR18 93W | +01248 | (9.5) 9.0-10.5 | 51 | 1433 | 25.28 | 10.50 | 9.71 | 820 | 10 | 7.9 | 26 | |
| 255/40ZR19XL 100W | +01260 | (9.0) 8.5-10.0 | 50 | 1764 | 27.01 | 10.31 | 9.39 | 768 | 10 | 7.9 | 28 | |
| 225/35ZR19XL 88W | +01265 | (8.0) 7.5-9.0 | 50 | 1235 | 25.18 | 9.13 | 8.35 | 823 | 10 | 7.9 | 22 | |
| 275/30ZR19XL 96W | +01256 | (9.5) 9.0-10.0 | 50 | 1565 | 25.52 | 10.84 | 10.18 | 813 | 10 | 7.9 | 27 | |
| 245/35ZR20XL 95W | 01262 | (8.5) 8.0-9.5 | 50 | 1521 | 26.76 | 9.68 | 8.91 | 775 | 10 | 7.9 | 26 | |
| 255/35ZR20XL 97W | 01267 | (9.0) 8.5-10.0 | 50 | 1609 | 26.97 | 10.06 | 9.31 | 769 | 10 | 7.9 | 27 | |
| 275/30ZR20XL 97W | +01255 | (9.5) 9.0-10.0 | 50 | 1609 | 26.52 | 10.79 | 10.18 | 782 | 10 | 7.9 | 28 | |
| 285/30ZR20XL 99W | +01253 | (10.0) 9.5-10.5 | 50 | 1709 | 26.74 | 11.26 | 10.66 | 775 | 10 | 7.9 | 29 | |

+ Discontinued - Limited Availability



ZEON SPORT A/S

Ultra-High Performance



UTQG
W-Rated 400 AA AA
V-Rated 400 A A
FREE 45-Day
Road Test!
W/V-Speed Design
Directional Design
M+S Rated

Special Features

- The Cooper Zeon Sport A/S is a premium W-speed rated, ultra-high performance all-season line designed for drivers who want year-round traction with commendable handling and high-speed capabilities.
- The Cooper Zeon Sport A/S is an excellent original equipment replacement for a wide range of vehicles including luxury touring cars, performance cars and crossovers (CUV).

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|--------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL W-RATED | | | | | | | | | | | | |
| 205/55ZR16 91W | 25501 | (6.5) 5.5-7.5 | 51 | 1356 | 24.87 | 8.49 | 7.38 | 834 | 10.0 | 7.9 | 22 | \$ |
| 215/55ZR16 93W | 25515 | (7.0) 6.0-7.5 | 51 | 1433 | 25.27 | 8.90 | 7.63 | 821 | 10.0 | 7.9 | 24 | |
| 225/55ZR16 95W | 25502 | (7.0) 6.0-8.0 | 51 | 1521 | 25.79 | 9.02 | 7.89 | 804 | 10.0 | 7.9 | 27 | |
| 225/50ZR16 92W | 25505 | (7.0) 6.0-8.0 | 51 | 1389 | 24.91 | 9.12 | 8.32 | 832 | 10.0 | 7.9 | 27 | |
| 245/50ZR16 97W | 25516 | (7.5) 7.0-8.5 | 51 | 1609 | 25.66 | 9.86 | 8.96 | 808 | 10.0 | 7.9 | 29 | |
| 215/55ZR17 94W | 25518 | (7.0) 6.0-7.5 | 51 | 1477 | 26.29 | 8.90 | 7.63 | 789 | 10.0 | 7.9 | 25 | |
| 225/55ZR17 97W | 25526 | (7.0) 6.0-8.0 | 51 | 1609 | 26.74 | 9.11 | 7.95 | 775 | 10.5 | 8.3 | 29 | |
| 235/55ZR17 99W | 25503 | (7.5) 6.5-8.5 | 51 | 1709 | 27.13 | 9.67 | 8.52 | 764 | 10.0 | 7.9 | 30 | |
| 205/50ZR17XL 93W | 25520 | (6.5) 5.5-7.5 | 50 | 1433 | 25.11 | 8.34 | 7.37 | 826 | 10.0 | 7.9 | 23 | |
| 215/50ZR17 91W | 25504 | (7.0) 6.0-7.5 | 51 | 1356 | 25.50 | 8.82 | 7.77 | 813 | 10.0 | 7.9 | 25 | |
| 225/50ZR17 94W | 25506 | (7.0) 6.0-8.0 | 51 | 1477 | 25.90 | 9.12 | 8.34 | 801 | 10.0 | 7.9 | 29 | |
| 235/50ZR17 96W | 25507 | (7.5) 6.5-8.5 | 51 | 1565 | 26.29 | 9.55 | 8.60 | 789 | 10.0 | 7.9 | 30 | |
| 205/45ZR17 84W | 25521 | (7.0) 6.5-7.5 | 51 | 1102 | 24.24 | 8.12 | 7.40 | 855 | 10.0 | 7.9 | 21 | |
| 215/45ZR17XL 91W | 25522 | (7.0) 7.0-8.0 | 50 | 1356 | 24.75 | 8.30 | 7.97 | 838 | 10.0 | 7.9 | 23 | |
| 225/45ZR17XL 94W | 25510 | (7.5) 7.0-8.5 | 50 | 1477 | 24.91 | 9.03 | 8.20 | 832 | 10.0 | 7.9 | 24 | |
| 235/45ZR17 94W | 25512 | (8.0) 7.5-9.0 | 51 | 1477 | 25.35 | 9.30 | 8.60 | 818 | 10.0 | 7.9 | 25 | |
| 245/45ZR17 95W | 25508 | (8.0) 7.5-9.0 | 51 | 1521 | 25.65 | 9.61 | 8.92 | 808 | 10.0 | 7.9 | 26 | |
| 275/40ZR17 98W | 25525 | (9.5) 9.0-11.0 | 51 | 1653 | 25.66 | 11.06 | 10.04 | 808 | 10.0 | 7.9 | 31 | |
| 235/55ZR18 100W | 25519 | (7.5) 6.5-8.5 | 51 | 1764 | 28.13 | 9.67 | 8.52 | 737 | 10.0 | 7.9 | 31 | |
| 225/45ZR18 91W | 25511 | (7.5) 7.0-8.5 | 51 | 1356 | 25.91 | 9.03 | 8.20 | 800 | 10.0 | 7.9 | 25 | |
| 245/45ZR18 96W | 25509 | (8.0) 7.5-9.0 | 51 | 1565 | 26.65 | 9.81 | 8.92 | 778 | 10.0 | 7.9 | 28 | |
| 255/45ZR18XL 103W | 25523 | (8.5) 8.0-9.5 | 50 | 1929 | 27.03 | 9.80 | 9.36 | 767 | 10.0 | 7.9 | 29 | |
| 225/40ZR18XL 92W | 25514 | (8.0) 7.5-9.0 | 50 | 1389 | 25.07 | 9.19 | 8.44 | 827 | 10.0 | 7.9 | 24 | |
| 235/40ZR18XL 95W | 25524 | (8.5) 8.0-9.5 | 50 | 1521 | 25.36 | 9.33 | 8.00 | 817 | 10.0 | 7.9 | 25 | |
| 245/40ZR18XL 97W | 25513 | (8.5) 8.0-9.5 | 50 | 1609 | 25.72 | 9.84 | 9.08 | 806 | 10.0 | 7.9 | 26 | |
| 275/40ZR18 99W | 25517 | (9.5) 9.0-11.0 | 51 | 1709 | 26.66 | 11.06 | 10.04 | 778 | 10.0 | 7.9 | 30 | |
| 245/45ZR20 99W | 25528 | (8.0) 7.5-9.0 | 51 | 1709 | 28.61 | 9.59 | 8.86 | 725 | 10.5 | 8.3 | 30 | |
| BLACKWALL V-RATED | | | | | | | | | | | | |
| 265/50R20XL 111V | 25530 | (8.5) 7.5-9.5 | 50 | 2403 | 30.42 | 10.73 | 9.44 | 682 | 10.5 | 8.3 | 37 | |



ZEON ZPT

Premium All-Season



UTQG 380 A A
FREE 45-Day
Road Test!
H-Speed Design
Directional Design
M+S Rated

Special Features

- The Cooper Zeon ZPT is a premium all-season, H-rated high performance tire targeted to the growing "tuner" market.
- The Cooper Zeon ZPT provides an ultra-high performance "look" at the more affordable H-rated price. It is especially suited for foreign and domestic compacts that have undergone tire/wheel "plus fitment" upgrades.

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| 195/50R15 82H | 01852 | (6.0) 5.5-7.0 | 44 | 1047 | 22.77 | 7.95 | 7.26 | 911 | 10.0 | 7.9 | 19 | \$ |
| 205/50R15 86H | 01853 | (6.5) 5.5-7.5 | 44 | 1168 | 23.15 | 8.34 | 7.37 | 896 | 10.0 | 7.9 | 20 | |
| 205/50R16 87H | 01857 | (6.5) 5.5-7.5 | 44 | 1201 | 24.06 | 8.34 | 7.35 | 862 | 10.0 | 7.9 | 21 | |
| 225/50R16 92H | 01859 | (7.0) 6.0-8.0 | 44 | 1389 | 24.98 | 9.12 | 8.32 | 830 | 10.0 | 7.9 | 26 | |
| 245/50R16 97H | 01861 | (7.5) 7.0-8.5 | 44 | 1609 | 25.74 | 9.86 | 8.95 | 805 | 10.0 | 7.9 | 29 | |
| 205/45R16 83H | 01860 | (7.0) 6.5-7.5 | 44 | 1074 | 23.29 | 8.12 | 7.39 | 890 | 10.0 | 7.9 | 20 | |
| 215/45R17 87H | 01863 | (7.0) 7.0-8.0 | 44 | 1201 | 24.75 | 8.30 | 7.97 | 838 | 10.0 | 7.9 | 23 | |
| 225/45R17 91H | 01864 | (7.5) 7.0-8.5 | 44 | 1356 | 24.91 | 9.03 | 8.20 | 832 | 10.0 | 7.9 | 25 | |
| 235/45R17 94H | 01865 | (8.0) 7.5-9.0 | 44 | 1477 | 25.35 | 9.30 | 8.60 | 818 | 10.0 | 7.9 | 26 | |
| 245/45R17 95H | 01866 | (8.0) 7.5-9.0 | 44 | 1521 | 25.65 | 9.61 | 8.92 | 808 | 10.0 | 7.9 | 26 | |
| 205/40R17RE 84H | 01868 | (7.5) 7.0-8.0 | 50 | 1102 | 23.45 | 8.43 | 7.81 | 884 | 10.0 | 7.9 | 20 | |
| 215/40R17 83H | 01869 | (7.5) 7.0-8.5 | 44 | 1074 | 23.77 | 8.51 | 8.12 | 872 | 10.0 | 7.9 | 20 | |
| 215/45R18 89H | 01878 | (7.0) 7.0-8.0 | 44 | 1279 | 25.67 | 8.30 | 7.99 | 801 | 10.5 | 8.3 | 23 | |
| 225/40R18 88H | 01874 | (8.0) 7.5-9.0 | 44 | 1235 | 25.07 | 9.03 | 8.44 | 827 | 10.0 | 7.9 | 24 | |
| 235/40R18 91H | 01875 | (8.5) 8.0-9.5 | 44 | 1356 | 25.40 | 9.55 | 8.76 | 816 | 10.0 | 7.9 | 26 | |
| 245/40R18RE 97H | 01876 | (8.5) 8.0-9.5 | 50 | 1609 | 25.72 | 9.84 | 9.08 | 806 | 10.0 | 7.9 | 27 | |
| 215/35R18RE 84H | 01877 | (7.5) 7.0-8.5 | 50 | 1102 | 23.88 | 8.56 | 7.96 | 868 | 10.0 | 7.9 | 21 | |



CS4 TOURING (V, H & T)

Premium Luxury Touring



UTQG
V-Rated 520 A A
H-Rated 560 A A

60,000 Mile
Treadwear Protection
Limited Warranty

FREE 45-Day
Road Test!

V/H-Speed Rated
M+S Rated

Special Features

- The CS4 Touring is Cooper's premium luxury touring tire designed for drivers who want optimum ride comfort, sporty handling, all-season traction and attractive styling in a touring tire.

UTQG
14" 620 A
Others 780 A

80,000 Mile
Treadwear Protection
Limited Warranty

FREE 45-Day
Road Test!

T-Speed Rated
M+S Rated

Special Features

- The CS4 Touring is Cooper's premium luxury touring tire designed for drivers who want optimum ride comfort, sporty handling, all-season traction and attractive styling in a touring tire.

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE |
|--------------------------|----------|--|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|
| BLACKWALL V-RATED | | | | | | | | | | | |
| 205/65R15 94V | 22506 | (6.0) 5.5-7.5 | 44 | 1477 | 25.41 | 8.37 | 6.46 | 817 | 11 | 8.7 | 22 |
| 195/55R15 85V | 22507 | (6.0) 5.5-7.0 | 44 | 1135 | 23.43 | 7.92 | 6.52 | 887 | 11 | 8.7 | 21 |
| 205/60R16 92V | 22501 | (6.0) 5.5-7.5 | 44 | 1389 | 25.65 | 8.40 | 6.55 | 809 | 11 | 8.7 | 24 |
| 215/60R16 95V | 22502 | (6.5) 6.0-7.5 | 44 | 1521 | 26.10 | 8.95 | 7.13 | 795 | 11 | 8.7 | 24 |
| 225/60R16 98V | 22503 | (6.5) 6.0-8.0 | 44 | 1653 | 26.56 | 9.15 | 7.16 | 782 | 11 | 8.7 | 27 |
| 235/60R16 100V | 22505 | (7.0) 6.5-8.5 | 44 | 1764 | 27.10 | 9.52 | 7.55 | 766 | 11 | 8.7 | 27 |
| 225/55R16 95V | 22509 | (7.0) 6.0-8.0 | 44 | 1521 | 25.77 | 9.36 | 7.59 | 806 | 11 | 8.7 | 27 |
| 225/50R16 92V | 22513 | (7.0) 6.0-8.0 | 44 | 1389 | 24.89 | 9.15 | 7.69 | 835 | 11 | 8.7 | 23 |
| 215/55R17 94V | 22508 | (7.0) 6.0-7.5 | 44 | 1477 | 26.31 | 8.90 | 7.32 | 789 | 11 | 8.7 | 27 |
| 225/55R17 97V | 22510 | (7.0) 6.0-8.0 | 44 | 1609 | 26.79 | 9.31 | 7.40 | 774 | 11 | 8.7 | 27 |
| 235/55R17 99V | 22511 | (7.5) 6.5-8.5 | 44 | 1709 | 27.15 | 9.75 | 8.01 | 765 | 11 | 8.7 | 29 |
| 225/50R17 94V | 22514 | (7.0) 6.0-8.0 | 44 | 1477 | 25.89 | 9.66 | 7.69 | 802 | 11 | 8.7 | 23 |
| 235/50R17 96V | 22515 | (7.5) 6.5-8.5 | 44 | 1565 | 26.30 | 9.91 | 8.09 | 790 | 11 | 8.7 | 23 |
| 225/60R18 100V | 22504 | (6.5) 6.0-8.0 | 44 | 1764 | 28.62 | 9.01 | 7.19 | 725 | 11 | 8.7 | 28 |
| BLACKWALL H-RATED | | | | | | | | | | | |
| 185/65R14 86H | 11407 | (5.5) 5.0-6.5 | 44 | 1168 | 23.45 | 7.64 | 5.75 | 885 | 11 | 8.7 | 19 |
| 185/60R14 82H | 11401 | (5.5) 5.0-6.5 | 44 | 1047 | 22.73 | 7.48 | 5.90 | 914 | 11 | 8.7 | 18 |
| 195/60R14 86H | 11402 | (6.0) 5.5-7.0 | 44 | 1168 | 23.20 | 7.97 | 6.29 | 894 | 11 | 8.7 | 20 |
| 185/65R15 88H | 11408 | (5.5) 5.0-6.5 | 44 | 1235 | 24.45 | 7.83 | 5.75 | 849 | 11 | 8.7 | 20 |
| 195/65R15 91H | 11409 | (6.0) 5.5-7.0 | 44 | 1356 | 24.97 | 8.05 | 6.13 | 831 | 11 | 8.7 | 25 |
| 205/65R15 94H | 11410 | (6.0) 5.5-7.5 | 44 | 1477 | 25.41 | 8.34 | 6.46 | 817 | 11 | 8.7 | 22 |
| 215/65R15 96H | 11411 | (6.5) 6.0-7.5 | 44 | 1565 | 26.04 | 8.69 | 6.76 | 780 | 11 | 8.7 | 24 |
| 195/60R15 88H | 11403 | (6.0) 5.5-7.0 | 44 | 1235 | 24.20 | 8.03 | 6.29 | 858 | 11 | 8.7 | 21 |
| 205/60R15 91H | 11404 | (6.0) 5.5-7.5 | 44 | 1356 | 24.65 | 8.29 | 6.55 | 841 | 11 | 8.7 | 20 |
| 215/60R15 94H | 11405 | (6.5) 6.0-7.5 | 44 | 1477 | 25.10 | 8.82 | 6.93 | 828 | 11 | 8.7 | 23 |
| 225/60R15 96H | 11406 | (6.5) 6.0-8.0 | 44 | 1565 | 25.56 | 8.97 | 7.16 | 813 | 11 | 8.7 | 26 |
| 205/60R16 92H | 11417 | (6.0) 5.5-7.5 | 44 | 1389 | 25.65 | 8.40 | 6.55 | 809 | 11 | 8.7 | 23 |
| 215/60R16 95H | 11418 | (6.5) 6.0-7.5 | 44 | 1521 | 26.10 | 8.95 | 7.13 | 795 | 11 | 8.7 | 25 |
| 225/60R16 98H | 11419 | (6.5) 6.0-8.0 | 44 | 1653 | 26.56 | 9.15 | 7.16 | 782 | 11 | 8.7 | 26 |
| 205/55R16 91H | 11413 | (6.5) 5.5-7.5 | 44 | 1356 | 24.86 | 8.59 | 7.17 | 836 | 11 | 8.7 | 23 |
| 215/55R16 93H | 11414 | (7.0) 6.0-7.5 | 44 | 1433 | 25.27 | 8.87 | 7.17 | 822 | 11 | 8.7 | 23 |
| 225/55R16 95H | 11415 | (7.0) 6.0-8.0 | 44 | 1521 | 25.77 | 9.29 | 7.79 | 806 | 11 | 8.7 | 27 |
| 205/50R16 87H | 11416 | (6.5) 5.5-7.5 | 44 | 1201 | 24.09 | 8.32 | 7.05 | 862 | 11 | 8.7 | 23 |
| 235/65R17 104H | 11412 | (7.0) 6.5-8.5 | 44 | 1984 | 29.09 | 10.06 | 7.36 | 715 | 11 | 8.7 | 30 |
| P255/65R18 109H | 11420 | (7.5) 7.0-9.0 | 44 | 2271 | 31.02 | 10.20 | 8.33 | 670 | 11 | 8.7 | 37 |
| P255/60R19 108H | 11421 | (7.5) 7.0-9.0 | 44 | 2205 | 31.02 | 10.20 | 8.53 | 671 | 11 | 8.7 | 36 |
| BLACKWALL T-RATED | | | | | | | | | | | |
| 185/70R14 88T | 11144 | (5.5) 4.5-6.0 | 44 | 1235 | 24.15 | 7.44 | 5.67 | 860 | 12 | 9.5 | 19 |
| 195/70R14 91T | 11145 | (6.0) 5.0-6.5 | 44 | 1356 | 24.80 | 8.05 | 6.03 | 840 | 12 | 9.5 | 21 |
| 185/65R14 86T | 11130 | (5.5) 5.0-6.5 | 44 | 1168 | 23.51 | 7.64 | 5.82 | 885 | 12 | 9.5 | 20 |
| 205/70R15 96T | 11146 | (6.0) 5.0-7.0 | 44 | 1565 | 26.28 | 8.23 | 6.27 | 791 | 12 | 9.5 | 22 |
| 215/70R15 98T | 11147 | (6.5) 5.5-7.0 | 44 | 1653 | 26.85 | 8.70 | 6.63 | 775 | 12 | 9.5 | 24 |
| 185/65R15 88T | 11131 | (5.5) 5.0-6.5 | 44 | 1235 | 24.51 | 7.83 | 5.82 | 849 | 12 | 9.5 | 21 |
| 195/65R15 91T | 11132 | (6.0) 5.5-7.0 | 44 | 1356 | 25.03 | 8.05 | 6.18 | 831 | 12 | 9.5 | 24 |
| 205/65R15 94T | 11133 | (6.0) 5.5-7.5 | 44 | 1477 | 25.47 | 8.34 | 6.43 | 817 | 12 | 9.5 | 22 |
| 215/65R15 96T | 11134 | (6.5) 6.0-7.5 | 44 | 1565 | 26.04 | 8.69 | 6.76 | 780 | 12 | 9.5 | 24 |
| 185/60R15 84T | 11120 | (5.5) 5.0-6.5 | 44 | 1102 | 23.73 | 7.44 | 5.96 | 876 | 12 | 9.5 | 20 |
| 195/60R15 88T | 11121 | (6.0) 5.5-7.0 | 44 | 1235 | 24.26 | 8.03 | 6.34 | 858 | 12 | 9.5 | 22 |
| 205/60R15 91T | 11122 | (6.0) 5.5-7.5 | 44 | 1356 | 24.71 | 8.29 | 6.59 | 841 | 12 | 9.5 | 23 |
| 215/60R15 94T | 11124 | (6.5) 6.0-7.5 | 44 | 1477 | 25.16 | 8.82 | 6.97 | 828 | 12 | 9.5 | 25 |
| 225/70R16 103T | 11150 | (6.5) 6.0-7.5 | 44 | 1929 | 28.49 | 9.60 | 6.89 | 730 | 12 | 9.5 | 27 |
| 215/65R16 98T | 11135 | (6.5) 6.0-7.5 | 44 | 1653 | 27.10 | 8.70 | 6.80 | 770 | 12 | 9.5 | 26 |
| 225/65R16 100T | 11119 | (6.5) 6.0-8.0 | 44 | 1764 | 27.50 | 9.10 | 7.07 | 757 | 12 | 9.5 | 28 |
| 235/65R16 103T | 11138 | (7.0) 6.5-8.5 | 44 | 1929 | 27.93 | 9.56 | 7.39 | 744 | 12 | 9.5 | 27 |
| 205/60R16 92T | 11123 | (6.0) 5.5-7.5 | 44 | 1389 | 25.71 | 8.40 | 6.59 | 809 | 12 | 9.5 | 25 |
| 215/60R16 95T | 11125 | (6.5) 6.0-7.5 | 44 | 1521 | 26.16 | 8.95 | 6.97 | 795 | 12 | 9.5 | 25 |
| 225/60R16 98T | 11127 | (6.5) 6.0-8.0 | 44 | 1653 | 26.62 | 9.15 | 7.19 | 782 | 12 | 9.5 | 28 |
| 235/60R16 100T | 11129 | (7.0) 6.5-8.5 | 44 | 1764 | 27.16 | 9.52 | 7.57 | 766 | 12 | 9.5 | 28 |
| 205/55R16 91T | 11140 | (6.5) 5.5-7.5 | 44 | 1356 | 24.92 | 8.59 | 7.00 | 836 | 12 | 9.5 | 24 |
| 215/65R17 99T | 11136 | (6.5) 6.0-7.5 | 44 | 1709 | 27.98 | 8.93 | 6.80 | 743 | 12 | 9.5 | 28 |
| 225/65R17 102T | 11137 | (6.5) 6.0-8.0 | 44 | 1874 | 28.40 | 8.98 | 7.00 | 732 | 12 | 9.5 | 29 |
| 215/60R17 96T | 11126 | (6.5) 6.0-7.5 | 44 | 1565 | 27.11 | 9.03 | 6.97 | 767 | 12 | 9.5 | 27 |
| 225/60R17 99T | 11128 | (6.5) 6.0-8.0 | 44 | 1709 | 27.56 | 9.14 | 7.19 | 754 | 12 | 9.5 | 29 |
| 235/60R17 102T | 11149 | (7.0) 6.5-8.5 | 44 | 1873 | 28.16 | 10.07 | 7.64 | 736 | 12 | 9.5 | 33 |
| 225/55R17 97T | 11141 | (7.0) 6.0-8.0 | 44 | 1609 | 26.85 | 9.31 | 7.61 | 774 | 12 | 9.5 | 28 |
| 235/55R17 99T | 11143 | (7.5) 6.5-8.5 | 44 | 1709 | 27.21 | 9.75 | 8.01 | 765 | 12 | 9.5 | 30 |
| 235/65R18 106T | 11139 | (7.0) 6.5-8.5 | 44 | 2094 | 29.93 | 10.06 | 7.38 | 695 | 12 | 9.5 | 32 |
| 225/55R18 98T | 11142 | (7.0) 6.0-8.0 | 44 | 1653 | 27.85 | 9.11 | 7.60 | 747 | 12 | 9.5 | 29 |
| WHITWALL T-RATED | | | | | | | | | | | |
| 225/60R16 98T | 11148 | (6.5) 6.0-8.0 | 44 | 1653 | 26.62 | 9.15 | 7.19 | 782 | 12 | 9.5 | 28 |



LIFELINE GLS (V, H & T)

All-Season Touring



UTQG
V/H-Rated 440 A A
45,000 Mile
Treadwear Protection
Limited Warranty
V/H-Speed Rated
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE |
|--------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|
| BLACKWALL V-RATED | | | | | | | | | | | |
| 205/60R16 92V | 01655 | (6.0) 5.5-7.5 | 44 | 1389 | 25.65 | 8.22 | 6.22 | 811 | 10.5 8.3 | 24 | \$ |
| 215/60R16 95V | 01656 | (6.5) 6.0-7.5 | 44 | 1521 | 26.11 | 8.82 | 6.65 | 796 | 10.5 8.3 | 27 | |
| 215/55R17 94V | 01657 | (7.0) 6.0-7.5 | 44 | 1477 | 26.25 | 8.75 | 7.04 | 792 | 10.5 8.3 | 27 | |
| 215/50R17XL 95V | 01658 | (7.0) 6.0-7.5 | 50 | 1521 | 25.46 | 8.72 | 7.04 | 817 | 10.5 8.3 | 26 | |
| 225/50R17 94V | 01659 | (7.0) 6.0-8.0 | 44 | 1477 | 25.83 | 8.99 | 7.25 | 805 | 10.5 8.3 | 27 | |
| BLACKWALL H-RATED | | | | | | | | | | | |
| 195/65R15 91H | 01683 | (6.0) 5.5-7.0 | 44 | 1356 | 24.96 | 8.09 | 5.87 | 833 | 10.5 8.3 | 22 | |
| 205/65R15 94H | 01684 | (6.0) 5.5-7.5 | 44 | 1477 | 25.40 | 8.42 | 6.03 | 819 | 10.5 8.3 | 23 | |
| 195/60R15 88H | 01680 | (6.0) 5.5-7.0 | 44 | 1235 | 24.16 | 8.10 | 5.98 | 861 | 10.5 8.3 | 21 | |
| 205/60R15 91H | 01681 | (6.0) 5.5-7.5 | 44 | 1356 | 24.64 | 8.40 | 6.22 | 844 | 10.5 8.3 | 22 | |
| 225/60R16 98H | 01682 | (6.5) 6.0-8.0 | 44 | 1653 | 26.55 | 9.11 | 6.78 | 783 | 10.5 8.3 | 25 | |
| 205/55R16 91H | 01685 | (6.5) 5.5-7.5 | 44 | 1356 | 24.85 | 8.59 | 6.67 | 837 | 10.5 8.3 | 23 | |
| 215/55R16 93H | 01686 | (7.0) 6.0-7.5 | 44 | 1433 | 25.24 | 8.92 | 7.04 | 824 | 10.5 8.3 | 24 | |
| 225/55R16 95H | 01654 | (7.0) 6.0-8.0 | 44 | 1521 | 25.76 | 8.88 | 7.08 | 807 | 10.5 8.3 | 26 | |



UTQG
T-Rated 540 A B
60,000 Mile
Treadwear Protection
Limited Warranty
T-Speed Rated
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE |
|-------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|
| BLACKWALL | | | | | | | | | | | |
| 175/70R13 82T | 01611 | (5.0) 4.5-6.0 | 44 | 1047 | 22.68 | 6.89 | 5.10 | 914 | 10.0 7.9 | 15 | \$ |
| 175/70R14 84T | 01612 | (5.0) 4.5-6.0 | 44 | 1102 | 23.68 | 6.89 | 5.10 | 876 | 10.0 7.9 | 16 | |
| 185/70R14 88T | 01613 | (5.5) 4.5-6.0 | 44 | 1235 | 24.23 | 7.40 | 5.30 | 856 | 10.0 7.9 | 17 | |
| 195/70R14 91T | 01614 | (6.0) 5.0-6.5 | 44 | 1356 | 24.78 | 7.80 | 5.60 | 837 | 10.0 7.9 | 18 | |
| 175/65R14 82T | 01603 | (5.0) 5.0-6.0 | 44 | 1047 | 22.95 | 6.85 | 5.20 | 903 | 10.0 7.9 | 16 | |
| 185/65R14 86T | 01604 | (5.5) 5.0-6.5 | 44 | 1168 | 23.40 | 7.35 | 5.55 | 886 | 10.0 7.9 | 17 | |
| 185/65R15 88T | 01605 | (5.5) 5.0-6.5 | 44 | 1235 | 24.40 | 7.35 | 5.55 | 852 | 10.0 7.9 | 18 | |
| 195/65R15 91T | 01606 | (6.0) 5.5-7.0 | 44 | 1356 | 24.90 | 7.80 | 5.85 | 832 | 10.0 7.9 | 20 | |
| 205/65R15 94T | 01607 | (6.0) 5.5-7.5 | 44 | 1477 | 25.26 | 8.16 | 6.05 | 821 | 10.5 8.3 | 21 | |
| 215/65R15 96T | 01608 | (6.5) 6.0-7.5 | 44 | 1565 | 25.81 | 8.65 | 6.50 | 803 | 10.5 8.3 | 23 | |
| 185/60R15 84T | 01690 | (5.5) 5.0-6.5 | 44 | 1102 | 23.59 | 7.18 | 5.62 | 881 | 10.0 7.9 | 17 | |
| 215/60R15 94T | 01691 | (6.5) 6.0-7.5 | 44 | 1477 | 24.94 | 8.54 | 6.57 | 834 | 10.5 8.3 | 21 | |
| 215/65R16 98T | 01609 | (6.5) 6.0-7.5 | 44 | 1653 | 26.81 | 8.65 | 6.50 | 773 | 10.5 8.3 | 25 | |
| 235/65R16 103T | 01693 | (7.0) 6.5-8.5 | 44 | 1929 | 27.79 | 9.37 | 7.10 | 748 | 10.5 8.3 | 26 | |
| 215/60R16 95T | 01601 | (6.5) 6.0-7.5 | 44 | 1521 | 25.93 | 8.55 | 6.55 | 800 | 10.5 8.3 | 24 | |
| 225/60R16 98T | 01602 | (6.5) 6.0-8.0 | 44 | 1653 | 26.50 | 8.80 | 6.80 | 782 | 10.5 8.3 | 24 | |
| 205/55R16 91T | 01610 | (6.5) 5.5-7.5 | 44 | 1356 | 24.64 | 8.30 | 7.00 | 841 | 10.0 7.9 | 23 | |
| 225/60R17 99T | 01692 | (6.5) 6.0-8.0 | 44 | 1709 | 27.38 | 8.81 | 6.78 | 759 | 10.5 8.3 | 25 | |
| WHITEWALL (.65") | | | | | | | | | | | |
| 205/70R14 95T | 01615 | (6.0) 5.0-7.0 | 44 | 1521 | 25.28 | 8.11 | 5.80 | 822 | 10.5 8.3 | 20 | |
| 215/70R14 96T | 01616 | (6.5) 5.5-7.0 | 44 | 1565 | 25.78 | 8.58 | 6.10 | 804 | 10.5 8.3 | 22 | |
| WHITEWALL (.75") | | | | | | | | | | | |
| 205/70R15 96T | 01617 | (6.0) 5.0-7.0 | 44 | 1565 | 26.18 | 8.11 | 5.80 | 792 | 10.5 8.3 | 21 | |
| 215/70R15 98T | 01618 | (6.5) 5.5-7.0 | 44 | 1653 | 26.68 | 8.58 | 6.10 | 777 | 10.5 8.3 | 22 | |



Special Features

- The Lifeline GLS is Cooper's first line all-season touring tire designed for consumers looking for touring performance in a moderately-priced tire.
- It is ideally suited as a replacement set of tires on the vehicle.
- The Lifeline GLS fits a wide range of automobiles requiring a speed rated touring tire, both foreign and domestic.

GFE

Low Resistance



UTQG 540 A B
60,000 Mile
Treadwear Protection
Limited Warranty
FREE 45-Day
Road Test!
T-Speed Rated
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE |
|------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|
| BLACKWALL | | | | | | | | | | | |
| 175/65R14 82T | 02403 | (5.0) 5.0-6.0 | 44 | 1047 | 22.95 | 6.85 | 5.20 | 903 | 10.0 7.9 | 15 | \$ |
| 185/65R14 86T | 02404 | (5.5) 5.0-6.5 | 44 | 1168 | 23.40 | 7.35 | 5.55 | 886 | 10.0 7.9 | 16 | |
| 185/65R15 88T | 02405 | (5.5) 5.0-6.5 | 44 | 1235 | 24.40 | 7.35 | 5.55 | 852 | 10.0 7.9 | 18 | |
| 195/65R15 91T | 02406 | (6.0) 5.5-7.0 | 44 | 1356 | 24.90 | 7.80 | 5.85 | 832 | 10.0 7.9 | 18 | |
| 205/65R15 94T | 02407 | (6.0) 5.5-7.5 | 44 | 1477 | 25.26 | 8.16 | 6.05 | 821 | 10.5 8.3 | 20 | |
| 215/65R16 98T | 02408 | (6.5) 6.0-7.5 | 44 | 1653 | 26.81 | 8.65 | 6.50 | 773 | 10.5 8.3 | 23 | |
| 215/60R16 95T | 02401 | (6.5) 6.0-7.5 | 44 | 1521 | 25.93 | 8.55 | 6.55 | 800 | 10.5 8.3 | 22 | |
| 225/60R16 98T | 02402 | (6.5) 6.0-8.0 | 44 | 1653 | 26.50 | 8.80 | 6.80 | 782 | 10.5 8.3 | 24 | |



Special Features

- The GFE is a low rolling resistant tire designed to provide your fuel efficient vehicle even better gas mileage.
- Size range is focused on small fuel efficient vehicles, but also includes larger, popular sizes.

COBRA RADIAL G/T

All-Season Performance



UTQG
50 Series 440 A C
Others 440 A B
50,000 Mile
Treadwear Protection
Limited Warranty
T/S-Speed Rated
M+S Rated

Special Features

- The Cobra Radial G/T is Cooper's all-season cosmetic performance tire that is targeted to buyers who prefer raised white-letter styling in an all-season tire.
- Available in a wide range of standard and low profile sizes, the Cobra Radial G/T is especially popular with drivers of older domestic "muscle cars" who still want to retain the characteristic "look" of their vehicles.

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|----------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| P185/60R14 82T | 39620 | (5.5) 5.0-6.5 | 44 | 1047 | 22.80 | 7.15 | 6.00 | 912 | 10.5 | 8.3 | 17 | \$ |
| P205/50R15 84S | 39618 | (6.5) 5.5-7.5 | 35 | 1113 | 23.15 | 8.18 | 6.85 | 898 | 10.5 | 8.3 | 20 | |
| P235/55R16 96T | 39650 | (7.5) 6.5-8.5 | 44 | 1565 | 26.15 | 9.65 | 7.95 | 793 | 10.5 | 8.3 | 24 | |
| RAISED WHITE LETTER | | | | | | | | | | | | |
| P215/70R14 96T | 39633 | (6.5) 5.5-7.0 | 44 | 1554 | 25.76 | 8.66 | 7.00 | 807 | 10.5 | 8.3 | 22 | |
| P225/70R14 98T | 39634 | (6.5) 6.0-7.5 | 44 | 1675 | 26.27 | 8.92 | 7.20 | 792 | 10.5 | 8.3 | 24 | |
| P215/60R14 91T | 39606 | (6.5) 6.0-7.5 | 44 | 1345 | 24.16 | 8.42 | 7.00 | 861 | 10.5 | 8.3 | 21 | |
| P235/60R14 96T | 39608 | (7.0) 6.5-8.5 | 44 | 1565 | 25.06 | 9.11 | 7.60 | 830 | 10.5 | 8.3 | 24 | |
| P215/70R15 97T | 39635 | (6.5) 5.5-7.0 | 44 | 1620 | 26.71 | 8.71 | 7.00 | 778 | 10.5 | 8.3 | 23 | |
| P225/70R15 100T | 39636 | (6.5) 6.0-7.5 | 44 | 1753 | 27.37 | 9.10 | 7.20 | 760 | 10.5 | 8.3 | 25 | |
| P235/70R15 102T | 39637 | (7.0) 6.0-8.0 | 44 | 1896 | 27.90 | 9.46 | 7.60 | 745 | 10.5 | 8.3 | 27 | |
| P255/70R15 108T | 39638 | (7.5) 6.5-8.5 | 44 | 2183 | 28.95 | 10.40 | 8.20 | 718 | 10.5 | 8.3 | 31 | |
| P215/65R15 95T | 39616 | (6.5) 6.0-7.5 | 44 | 1510 | 26.00 | 8.38 | 6.80 | 799 | 10.5 | 8.3 | 22 | |
| P235/60R15 98T | 39612 | (7.0) 6.5-8.5 | 44 | 1642 | 26.11 | 9.15 | 7.60 | 796 | 10.5 | 8.3 | 25 | |
| P245/60R15 100T | 39613 | (7.0) 7.0-8.5 | 44 | 1753 | 26.55 | 9.47 | 8.00 | 783 | 10.5 | 8.3 | 27 | |



TRENDSETTER SE

All-Season



UTQG 440 A B
40,000 Mile
Treadwear Protection
Limited Warranty
M+S Rated

Special Features

- The Trendsetter SE is Cooper's entry level all-season tire line targeted to the value-oriented consumer.
- The affordably priced Trendsetter SE is available in sizes that fit a wide range of older to later model automobiles – those that require the use of 75-series whitewall sizes.

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| P175/70R13 82S | 02907 | (5.0) 4.5-6.0 | 35 | 1036 | 22.68 | 6.89 | 4.90 | 914 | 10.0 | 7.9 | 14 | \$ |
| P185/70R13 85S | 02908 | (5.5) 4.5-6.0 | 35 | 1135 | 23.23 | 7.40 | 5.10 | 893 | 10.0 | 7.9 | 15 | |
| P175/70R14 84S | 02926 | (5.0) 4.5-6.0 | 35 | 1102 | 23.18 | 6.89 | 4.90 | 896 | 10.0 | 7.9 | 16 | |
| P185/70R14 87S | 02909 | (5.5) 4.5-6.0 | 35 | 1201 | 24.23 | 7.40 | 5.10 | 856 | 10.0 | 7.9 | 17 | |
| P195/70R14 90S | 02910 | (6.0) 5.0-6.5 | 35 | 1312 | 24.78 | 7.80 | 5.40 | 837 | 10.0 | 7.9 | 17 | |
| P205/70R14 93S | 02914 | (6.0) 5.0-7.0 | 35 | 1433 | 25.28 | 8.11 | 5.60 | 822 | 10.0 | 7.9 | 18 | |
| P175/65R14 81S | 02918 | (5.0) 5.0-6.0 | 35 | 1019 | 22.90 | 6.85 | 5.00 | 907 | 10.0 | 7.9 | 15 | |
| P185/65R14 85S | 02919 | (5.5) 5.0-6.5 | 35 | 1124 | 23.35 | 7.35 | 5.35 | 889 | 10.0 | 7.9 | 16 | |
| P205/70R15 95S | 02911 | (6.0) 5.0-7.0 | 35 | 1499 | 26.28 | 8.11 | 5.60 | 790 | 10.0 | 7.9 | 20 | |
| P195/65R15 89S | 02915 | (6.0) 5.5-7.0 | 35 | 1279 | 24.90 | 7.80 | 5.70 | 839 | 10.0 | 7.9 | 18 | |
| P205/65R15 92S | 02916 | (6.0) 5.5-7.5 | 35 | 1400 | 25.25 | 8.16 | 5.85 | 823 | 10.0 | 7.9 | 20 | |
| P215/65R15 95S | 02917 | (6.5) 6.0-7.5 | 35 | 1510 | 25.88 | 8.65 | 6.38 | 807 | 10.0 | 7.9 | 22 | |
| P215/60R16 94S | 02935 | (6.5) 6.0-7.5 | 35 | 1477 | 26.10 | 8.55 | 6.40 | 801 | 10.0 | 7.9 | 22 | |
| P225/60R16 97S | 02936 | (6.5) 6.0-8.0 | 35 | 1609 | 26.52 | 8.80 | 6.60 | 788 | 10.0 | 7.9 | 23 | |
| P205/55R16 89S | 02932 | (6.5) 5.5-7.5 | 35 | 1279 | 24.75 | 8.30 | 7.10 | 844 | 10.0 | 7.9 | 22 | |
| WHITEWALL (.50") | | | | | | | | | | | | |
| P155/80R13 STD | 01301 | (4.5) 4.0-5.0 | 35 | 959 | 22.75 | 6.10 | 3.90 | 911 | 9.5 | 7.5 | 13 | |
| WHITEWALL (.65") | | | | | | | | | | | | |
| P185/75R14 STD | 01305 | (5.0) 4.5-6.0 | 35 | 1290 | 24.80 | 7.20 | 4.60 | 836 | 10.0 | 7.9 | 17 | |
| P195/75R14 STD | 01306 | (5.5) 5.0-6.5 | 35 | 1400 | 25.40 | 7.60 | 4.90 | 816 | 10.0 | 7.9 | 18 | |
| P205/75R14 95 | 01307 | (5.5) 5.0-7.0 | 35 | 1532 | 25.95 | 7.95 | 5.10 | 799 | 10.5 | 8.3 | 19 | |
| P215/75R14 98S | 01308 | (6.0) 5.5-7.0 | 35 | 1664 | 26.55 | 8.40 | 5.40 | 781 | 10.5 | 8.3 | 20 | |
| P215/70R14 96S | 02904 | (6.5) 5.5-7.0 | 35 | 1554 | 25.78 | 8.58 | 5.90 | 804 | 10.0 | 7.9 | 21 | |
| WHITEWALL (.75") | | | | | | | | | | | | |
| P205/75R15 97S | 01310 | (5.5) 5.0-7.0 | 35 | 1598 | 26.98 | 8.03 | 5.10 | 769 | 10.5 | 8.3 | 20 | |
| P215/75R15 100S | 01311 | (6.0) 5.5-7.0 | 35 | 1742 | 27.55 | 8.40 | 5.40 | 753 | 10.5 | 8.3 | 22 | |
| P225/75R15 102S | 01312 | (6.0) 6.0-7.5 | 35 | 1874 | 28.05 | 8.70 | 5.60 | 739 | 10.5 | 8.3 | 24 | |
| P235/75R15 105S | 01313 | (6.5) 6.0-8.0 | 35 | 2028 | 28.65 | 9.10 | 5.90 | 724 | 11.0 | 8.7 | 25 | |
| P205/70R15 95S | 02905 | (6.0) 5.0-7.0 | 35 | 1499 | 26.28 | 8.11 | 5.60 | 790 | 10.0 | 7.9 | 20 | |
| P215/70R15 97S | 02906 | (6.5) 5.5-7.0 | 35 | 1620 | 26.78 | 8.58 | 5.90 | 774 | 10.0 | 7.9 | 22 | |
| P225/70R15 100S | 02912 | (6.5) 6.0-7.5 | 35 | 1753 | 27.28 | 8.85 | 6.15 | 760 | 10.0 | 7.9 | 24 | |





SUV SIZES
UTQG 520 A B
S-Speed Rated
SUV &
Light Truck Sizes
M+S Rated

Special Features

- The Cooper Zeon LTZ was developed as a hybrid between a sport truck tire and an all-terrain tire.
- The aggressiveness of the Cooper Zeon LTZ can tame any road surface while providing excellent ride and handling capabilities.

SUV SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|------|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| 285/60R18 XL 120S | 01401 | (8.5) 8.0-10.0 | 50 | 3086 | 31.48 | 11.43 | 9.46 | 660 | 14 | 11.1 | 49 | \$ |
| 275/60R20 XL 119S | 01403 | (8.0) 7.5-9.5 | 50 | 2998 | 33.03 | 11.06 | 9.00 | 629 | 14 | 11.1 | 53 | |
| 275/55R20 XL 117S | 01405 | (8.5) 7.5-9.5 | 50 | 2833 | 31.93 | 11.22 | 9.30 | 652 | 14 | 11.1 | 52 | |
| 285/50R20 XL 116S | 01409 | (9.0) 8.0-10.0 | 50 | 2756 | 31.29 | 11.63 | 9.73 | 664 | 14 | 11.1 | 49 | |
| 305/50R20 XL 120S | 01407 | (9.5) 8.5-11.0 | 50 | 3086 | 32.18 | 12.14 | 10.37 | 646 | 14 | 11.1 | 53 | |
| 275/45R20 XL 110S | 01411 | (9.0) 8.5-10.5 | 50 | 2337 | 29.82 | 10.87 | 9.25 | 695 | 14 | 11.1 | 45 | |
| 305/40R22 XL 114S | 01402 | (11.0) 10.0-12.0 | 50 | 2601 | 31.64 | 12.71 | 11.01 | 657 | 14 | 11.1 | 47 | |
| 305/35R24 XL 112S | 01404 | (11.0) 10.0-12.0 | 50 | 2469 | 32.48 | 12.71 | 11.13 | 640 | 14 | 11.1 | 49 | |



LIGHT TRUCK SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Space w/o Chains | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-----------------------------|----------|-------------------------------------|-----|----------------|------------------|------------------|---------------|-------------|----------------------------|---------------|------------------------|------|-------|----|
| BLACKWALL | | | | | | | | | | | | | | |
| LT305/55R20 E 121/118S | 01408 | (9.5) 8.5-11.0 | 65 | 2910 | 3195 | 33.2 | 12.44 | 10.2 | 14.5 | 626 | 16 | 12.7 | 60 | \$ |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | | |
| LT265/75R16 E 123/120R | 01430 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 31.60 | 10.63 | 7.8 | 12.2 | 659 | 16.5 | 13.1 | 47 | |
| LT265/70R17 E 121/118R | 01412 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.60 | 10.90 | 8.5 | 12.4 | 659 | 16.5 | 13.1 | 50 | |
| LT275/70R18 E 125/122S | 01420 | (8.0) 7.0-8.5 | 80 | 3305 | 3640 | 33.15 | 11.11 | 9.0 | 12.8 | 627 | 16.0 | 12.7 | 56 | |



ZEON XST^A

Premium Sport Truck



UTQG 420 A A
FREE 45-Day Road Test!
V/H-Speed Rated
Asymmetrical Design
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| V-RATED | | | | | | | | | | | | |
| 235/65R17 104V | 06020 | (7.0) 6.5-8.5 | 44 | 1984 | 29.20 | 9.65 | 7.70 | 712 | 12 | 9.5 | 34 | \$ |
| 255/55R18XL 109V | 06061 | (8.0) 7.0-9.0 | 50 | 2271 | 29.00 | 10.30 | 8.60 | 698 | 12 | 9.5 | 42 | |
| 275/45R22XL 112V | 06097 | (9.0) 8.5-10.0 | 50 | 2469 | 31.70 | 10.80 | 9.40 | 657 | 12 | 9.5 | 46 | |
| 285/45R22XL 114V | 06076 | (9.5) 9.0-11.0 | 50 | 2601 | 32.00 | 11.30 | 9.90 | 609 | 12 | 9.5 | 48 | |
| 305/45R22XL 118V | 06088 | (10.0) 9.5-11.0 | 50 | 2910 | 32.70 | 12.00 | 10.40 | 636 | 12 | 9.5 | 52 | |
| 305/40R22XL 114V | 06089 | (11.0) 10.0-12.0 | 50 | 2601 | 31.60 | 12.50 | 10.80 | 657 | 12 | 9.5 | 48 | |
| 245/35R22XL 97V | 06078 | (8.5) 8.0-9.5 | 50 | 1609 | 28.70 | 9.90 | 9.40 | 722 | 12 | 9.5 | 32 | |
| 265/35R22XL 102V | 06077 | (9.5) 9.0-10.0 | 50 | 1874 | 29.30 | 10.90 | 9.60 | 708 | 12 | 9.5 | 36 | |
| 255/30R22XL 95V | 06063 | (9.0) 8.5-9.5 | 50 | 1521 | 28.07 | 10.30 | 8.70 | 739 | 10 | 7.9 | 29 | |
| 295/35R24XL 110V | 06096 | (10.0) 10.0-12.0 | 50 | 2337 | 32.10 | 11.90 | 10.20 | 611 | 12 | 9.5 | 48 | |
| 305/35R24XL 112V | 06094 | (11.0) 10.0-12.0 | 50 | 2469 | 32.40 | 12.50 | 10.90 | 644 | 12 | 9.5 | 48 | |



Special Features

- The Cooper Zeon XST^A is a premium sport truck tire that utilizes an asymmetrical tread design to combine ride comfort with all-season traction.
- The Cooper Zeon XST^A size range provides coverage from plus applications to OE sizes.

ZEON XST

Premium All-Season Sport Truck



UTQG 420 A A
FREE 45-Day Road Test!
V-Speed Rated
Directional Design
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| 285/60R18 116V | +04058 | (8.5) 8.0-10.0 | 44 | 2756 | 31.33 | 11.73 | 9.66 | 644 | 12 | 9.5 | 45 | \$ |
| 285/55R18 113V | +04066 | (9.0) 8.0-10.0 | 44 | 2535 | 30.23 | 11.93 | 9.94 | 667 | 12 | 9.5 | 44 | |
| 285/50R20XL 116V | 04071 | (9.0) 8.0-10.0 | 50 | 2756 | 31.13 | 11.92 | 9.93 | 648 | 12 | 9.5 | 49 | |

+ Discontinued - Limited Availability



Special Features

- The Cooper Zeon XST is a premium all-season sport truck tire designed for drivers who want to upgrade their vehicles' looks and handling by replacing the original equipment wheels and tires.
- The Cooper Zeon XST size range provides "plus fitments" for a wide range of pickups, SUVs and crossovers (CUV).

DISCOVERER H/T PLUS

Light Truck Touring



UTQG 460 A B
T-Speed Rated
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| 265/60R18XL 114T | 19931 | (8.0) 7.5-9.5 | 50 | 2601 | 30.39 | 10.92 | 8.99 | 664 | 12 | 9.5 | 44 | \$ |
| 285/60R18 116T | 19930 | (8.5) 8.0-10.0 | 44 | 2756 | 31.33 | 11.73 | 9.66 | 644 | 12 | 9.5 | 44 | |
| 255/55R18XL 109T | 19934 | (8.0) 7.0-9.0 | 50 | 2271 | 28.99 | 10.36 | 8.85 | 698 | 12 | 9.5 | 41 | |
| 275/60R20XL 119T | 19932 | (8.0) 7.5-9.5 | 50 | 2998 | 32.95 | 11.00 | 9.30 | 632 | 12 | 9.5 | 48 | |
| 275/55R20XL 117T | 19935 | (8.5) 7.5-9.5 | 50 | 2833 | 31.95 | 11.00 | 9.50 | 652 | 12 | 9.5 | 47 | |
| 285/50R20XL 116T | 19937 | (9.0) 8.0-10.0 | 50 | 2756 | 31.13 | 11.92 | 9.93 | 648 | 12 | 9.5 | 47 | |
| 305/50R20XL 120T | 19936 | (9.5) 8.5-11.0 | 50 | 3086 | 32.05 | 12.44 | 10.57 | 648 | 12 | 9.5 | 52 | |
| 275/45R20XL 110T | 19939 | (9.0) 8.5-10.0 | 50 | 2337 | 29.75 | 10.75 | 9.25 | 680 | 12 | 9.5 | 41 | |



Special Features

- The Discoverer H/T Plus is an extension of Cooper's Discoverer H/T SUV / light truck touring line that features sport truck and original equipment sizing in a non-directional, T-rated platform.
- It provides an excellent replacement for the 20-inch original equipment fitments on full-size pickups and SUVs as well as "plus fitments" for drivers seeking to upgrade the looks and handling of their vehicles.

DISCOVERER CTS

Premium Luxury Touring



UTQG 700 A B
SUV Sizes
70,000 Mile Treadwear Protection Limited Warranty
FREE 45-Day Road Test!
M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-----------------------------|----------|-------------------------------------|-----|-----------|------------------|---------------|-------------|---------------|------------------------|------|-------|----|
| BLACKWALL | | | | | | | | | | | | |
| 255/65R16 109T | 04601 | (7.5) 7.0-9.0 | 44 | 2271 | 29.11 | 10.16 | 8.23 | 714 | 12.0 | 9.5 | 34 | \$ |
| 235/70R17XL 111T | 04602 | (7.0) 6.0-8.0 | 50 | 2403 | 30.01 | 9.47 | 7.43 | 692 | 13.0 | 10.3 | 36 | |
| 255/70R18 113T | 04603 | (7.5) 6.5-8.5 | 44 | 2535 | 32.13 | 10.25 | 8.08 | 647 | 13.5 | 10.7 | 40 | |
| 235/65R18 106T | 04604 | (7.0) 6.5-8.5 | 44 | 2094 | 30.09 | 9.37 | 7.58 | 690 | 12.0 | 9.5 | 34 | |
| 245/60R18 105T | 04605 | (7.0) 7.0-8.5 | 44 | 2039 | 29.68 | 9.55 | 8.00 | 700 | 12.0 | 9.5 | 32 | |
| 275/55R20XL 117T | 04606 | (8.5) 7.5-9.5 | 50 | 2833 | 31.94 | 10.95 | 9.17 | 650 | 12.0 | 9.5 | 41 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | |
| 225/75R16 104T | 04607 | (6.0) 6.0-7.5 | 44 | 1984 | 29.13 | 8.64 | 6.40 | 713 | 13.0 | 10.3 | 29 | |
| 245/75R16 111T | 04608 | (7.0) 6.5-8.0 | 44 | 2403 | 30.31 | 9.60 | 7.07 | 685 | 13.5 | 10.7 | 34 | |
| 265/75R16 116T | 04609 | (7.5) 7.0-9.0 | 44 | 2756 | 31.56 | 10.50 | 7.77 | 658 | 13.5 | 10.7 | 39 | |
| 215/70R16 100T | 04610 | (6.5) 5.5-7.0 | 44 | 1764 | 27.73 | 8.70 | 6.89 | 749 | 13.0 | 10.3 | 28 | |
| 235/70R16 106T | 04611 | (7.0) 6.0-8.0 | 44 | 2094 | 28.83 | 9.41 | 7.43 | 721 | 13.0 | 10.3 | 3 | |
| 245/70R16 107T | 04612 | (7.0) 6.5-8.0 | 44 | 2149 | 29.43 | 9.75 | 7.66 | 706 | 13.0 | 10.3 | 34 | |
| 255/70R16 111T | 04613 | (7.5) 6.5-8.5 | 44 | 2403 | 30.03 | 10.24 | 7.97 | 692 | 13.5 | 10.7 | 36 | |
| 265/70R16 112T | 04614 | (8.0) 7.0-9.0 | 44 | 2469 | 30.40 | 10.80 | 8.29 | 683 | 13.5 | 10.7 | 38 | |
| 245/70R17 110T | 04615 | (7.0) 6.5-8.0 | 44 | 2337 | 30.48 | 9.68 | 7.75 | 682 | 13.0 | 10.3 | 36 | |
| 265/70R17 115T | 04616 | (8.0) 7.0-9.0 | 44 | 2679 | 31.43 | 10.68 | 8.30 | 661 | 13.5 | 10.7 | 39 | |
| 245/65R17 107T | 04617 | (7.0) 7.0-8.5 | 44 | 2149 | 29.55 | 9.53 | 7.75 | 703 | 12.0 | 9.5 | 34 | |
| 255/65R17 110T | 04618 | (7.5) 7.0-9.0 | 44 | 2337 | 30.11 | 10.09 | 8.23 | 690 | 12.0 | 9.5 | 37 | |
| 265/65R17 112T | 04619 | (8.0) 7.5-9.5 | 44 | 2469 | 30.58 | 10.60 | 8.56 | 679 | 12.0 | 9.5 | 38 | |
| 265/70R18 116T | 04620 | (8.0) 7.0-9.0 | 44 | 2756 | 32.63 | 10.72 | 8.43 | 637 | 13.5 | 10.7 | 42 | |



Special Features

- The Discoverer CTS is a premium luxury touring tire designed to deliver higher levels of wet traction, ride comfort and appearance.
- It is especially suited for "body on frame" sport utility vehicles (SUV), crossovers (CUV) and late model light duty trucks.

SRM II RADIAL LT

Premium All-Season Light Truck



Light Truck Sizes
***M+S Rated.**

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Space w/o Chains | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|------------------------|----------|-------------------------------------|-----|----------------|------------------|------------------|---------------|-------------|----------------------------|---------------|------------------------|------|-------|----|
| BLACKWALL | | | | | | | | | | | | | | |
| LT215/85R16 E 115/112N | 64311 | (6.0) 5.5-7.0 | 80 | 2470 | 2680 | 30.26 | 8.21 | 5.93 | 9.9 | 683 | 14 | 11.1 | 39 | \$ |
| LT235/85R16 E 120/116N | 64310 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.70 | 9.21 | 6.69 | 10.8 | 656 | 14 | 11.1 | 42 | |
| LT225/75R16 E 115/112N | 64316 | (6.0) 6.0-7.0 | 80 | 2470 | 2680 | 29.18 | 8.60 | 6.60 | 10.2 | 711 | 14 | 11.1 | 39 | |
| LT245/75R16 E 120/116N | 64307 | (7.0) 6.5-7.0 | 80 | 2778 | 3042 | 30.46 | 9.35 | 6.98 | 11.3 | 680 | 14 | 11.1 | 44 | |
| LT265/75R16 E 123/120N | 64312 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 31.65 | 10.50 | 8.00 | 12.2 | 663 | 14 | 11.1 | 47 | |
| 7.50R16LT D 112/107N | 64301 | (6.0) 5.5-7.0 | 65 | 2150 | 2470 | 31.80 | 8.35 | 6.13 | 10.0 | 652 | 14 | 11.1 | 38 | |
| 8.75R16.SLT D 111/106N | 64303 | (6.75) 6.0-6.75 | 65 | 2095 | 2405 | 29.42 | 8.70 | 6.75 | 9.9 | 704 | 14 | 11.1 | 39 | |
| 9.50R16.SLT D 117/112N | 64304 | (6.75) 6.75-8.25 | 65 | 2470 | 2835 | 30.43 | 9.15 | 7.15 | 10.7 | 681 | 14 | 11.1 | 40 | |

* Four-Rib Tread Design - Not M+S Rated



Special Features

- The SRM II Radial LT is Cooper's premium all-season light truck rib tire geared toward drivers of work and commercial vehicles.
- The solid shoulder design allows the SRM II to be especially suited in applications where tire rotations are infrequent or as a companion tire used on the steer axles of vehicles that use a traction tire on the drive axle.



UTQG
H-Rated 440 A A
Other 520 A B

SUV Sizes

H-Rated 40,000 Mile
Treadwear Protection
Limited Warranty

T/S-Rated 60,000 Mile
Treadwear Protection
Limited Warranty

M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Pass. Max. Load | L.T. Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-------------------------------------|----------|-------------------------------------|-----|-----------------|----------------|------------------|---------------|-------------|---------------|------------------------|------|-------|----|
| BLACKWALL H-RATED | | | | | | | | | | | | | |
| 235/65R17 104H | 50501 | (7.0) 6.5-8.5 | 44 | 1984 | 1804 | 29.06 | 9.45 | 7.65 | 715 | 12.0 | 9.5 | 31 | \$ |
| BLACKWALL S-RATED | | | | | | | | | | | | | |
| 265/70R15 112S | 50525 | (8.0) 7.0-9.0 | 35 | 2469 | 2245 | 29.43 | 10.45 | 8.00 | 707 | 14.0 | 11.1 | 35 | |
| 225/75R16 104S | 50539 | (6.0) 6.0-7.5 | 35 | 1984 | 1804 | 29.15 | 8.65 | 6.40 | 711 | 13.0 | 10.3 | 30 | |
| 215/70R16 100S | 50545 | (6.5) 5.5-7.0 | 35 | 1764 | 1604 | 27.75 | 8.80 | 7.20 | 753 | 13.0 | 10.3 | 29 | |
| 245/70R16 107S | 50546 | (7.0) 6.5-8.0 | 35 | 2149 | 1954 | 29.40 | 9.90 | 7.70 | 705 | 13.0 | 10.3 | 33 | |
| 275/65R17 115S | 50504 | (8.0) 7.5-9.5 | 44 | 2679 | 2435 | 30.90 | 11.20 | 9.30 | 672 | 12.0 | 9.5 | 39 | |
| OUTLINE WHITE LETTER T-RATED | | | | | | | | | | | | | |
| 235/75R15XL 109T | 50502 | (6.5) 6.0-8.0 | 50 | 2271 | 2065 | 29.00 | 9.40 | 6.85 | 717 | 13.0 | 10.3 | 33 | |
| 235/70R16 106T | 50503 | (7.0) 6.0-7.5 | 44 | 2094 | 1904 | 28.85 | 9.40 | 7.40 | 719 | 12.5 | 9.9 | 33 | |
| OUTLINE WHITE LETTER S-RATED | | | | | | | | | | | | | |
| P205/75R15 97S | 50510 | (5.5) 5.0-6.5 | 35 | 1598 | 1453 | 27.05 | 8.10 | 5.70 | 764 | 13.0 | 10.3 | 24 | |
| P215/75R15 100S | 50511 | (6.0) 5.5-7.0 | 35 | 1742 | 1584 | 27.60 | 8.60 | 5.95 | 750 | 13.0 | 10.3 | 26 | |
| P225/75R15 102S | 50512 | (6.0) 6.0-7.0 | 35 | 1874 | 1704 | 28.20 | 8.95 | 6.20 | 735 | 13.0 | 10.3 | 27 | |
| P235/75R15 105S | 50513 | (6.5) 6.0-7.5 | 35 | 2028 | 1844 | 28.85 | 9.30 | 6.45 | 719 | 13.5 | 10.7 | 29 | |
| P265/75R15 112S | 50517 | (7.5) 7.0-8.5 | 35 | 2469 | 2245 | 30.50 | 10.65 | 7.60 | 680 | 14.0 | 11.1 | 37 | |
| P225/70R15 100S | 50521 | (6.5) 6.0-7.0 | 35 | 1753 | 1594 | 27.25 | 9.10 | 7.00 | 761 | 12.0 | 9.5 | 27 | |
| P235/70R15 102S | 50522 | (7.0) 6.0-7.5 | 35 | 1896 | 1724 | 27.80 | 9.65 | 7.40 | 746 | 12.0 | 9.5 | 29 | |
| 255/70R15 108S | 50530 | (7.5) 6.5-8.0 | 44 | 2205 | 2005 | 29.00 | 10.40 | 8.00 | 715 | 12.0 | 9.5 | 33 | |
| 225/75R16 104S | 50518 | (6.0) 6.0-7.5 | 35 | 1984 | 1804 | 29.15 | 8.65 | 6.40 | 711 | 13.0 | 10.3 | 31 | |
| P235/75R16 106S | 50526 | (6.5) 6.0-8.0 | 35 | 2094 | 1904 | 29.70 | 9.30 | 6.90 | 700 | 13.5 | 10.7 | 33 | |
| P245/75R16 109S | 50527 | (7.0) 6.5-7.5 | 35 | 2271 | 2065 | 30.35 | 9.60 | 7.00 | 683 | 13.5 | 10.7 | 35 | |
| P265/75R16 114S | 50529 | (7.5) 7.0-8.5 | 35 | 2601 | 2365 | 31.50 | 10.60 | 7.60 | 658 | 14.0 | 11.1 | 40 | |
| P225/70R16 101S | 50532 | (6.5) 6.0-7.0 | 35 | 1819 | 1654 | 28.30 | 9.00 | 7.00 | 733 | 13.0 | 10.3 | 30 | |
| 245/70R16 107S | 50534 | (7.0) 6.5-8.0 | 35 | 2149 | 1954 | 29.40 | 9.90 | 7.70 | 705 | 13.0 | 10.3 | 34 | |
| P255/70R16 109S | 50535 | (7.5) 6.5-8.0 | 35 | 2271 | 2065 | 29.95 | 10.30 | 8.00 | 692 | 13.5 | 10.7 | 36 | |
| 265/70R16 112S | 50536 | (8.0) 7.0-9.0 | 35 | 2469 | 2245 | 30.40 | 10.80 | 8.00 | 682 | 13.5 | 10.7 | 38 | |
| 275/70R16 114S | 50528 | (8.0) 7.0-9.0 | 44 | 2601 | 2365 | 31.20 | 11.00 | 8.92 | 669 | 13.0 | 10.3 | 40 | |
| 255/65R16 109S | 50520 | (7.5) 7.0-9.0 | 35 | 2271 | 2065 | 29.06 | 10.24 | 8.25 | 715 | 12.0 | 9.5 | 32 | |
| 245/70R17 110S | 50531 | (7.0) 6.5-8.0 | 44 | 2337 | 2125 | 30.43 | 9.96 | 8.16 | 662 | 13.0 | 10.3 | 35 | |
| P265/70R17 113S | 50538 | (8.0) 7.0-9.0 | 35 | 2535 | 2305 | 31.40 | 10.65 | 8.30 | 660 | 13.5 | 10.7 | 40 | |
| 235/65R17 104S | 50519 | (7.0) 6.5-8.5 | 35 | 1984 | 1804 | 29.06 | 9.45 | 7.65 | 715 | 12.0 | 9.5 | 31 | |
| 245/65R17 107S | 50537 | (7.0) 7.0-8.5 | 35 | 2149 | 1954 | 29.45 | 9.62 | 7.85 | 685 | 12.0 | 9.5 | 33 | |
| 275/60R17 110S | 50516 | (8.0) 7.5-9.5 | 35 | 2337 | 2125 | 29.88 | 11.00 | 9.00 | 675 | 12.0 | 9.5 | 37 | |



LIGHT TRUCK SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Rev. Per Mile | Dual Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-----------------------------|----------|-------------------------------------|-----|----------------|------------------|------------------|---------------|-------------|-------------------------|--------------------|------------------------|------|-------|----|
| BLACKWALL | | | | | | | | | | | | | | |
| LT215/85R16 E 115/112Q | 50595 | (6.0) 5.5-7.0 | 80 | 2470 | 2680 | 30.26 | 8.21 | 6.13 | 9.9 | 683 | 16 | 12.7 | 39 | \$ |
| LT235/85R16 E 120/116Q | 50597 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.65 | 9.31 | 6.77 | 10.8 | 654 | 16 | 12.7 | 43 | |
| LT225/75R16 E 115/112Q | 50506 | (6.0) 6.0-7.0 | 80 | 2470 | 2680 | 29.39 | 8.95 | 6.60 | 10.2 | 710 | 16 | 12.7 | 39 | |
| LT245/75R16 E 120/116Q | 50580 | (7.0) 6.5-7.5 | 80 | 2778 | 3042 | 30.44 | 9.57 | 7.45 | 11.3 | 680 | 16 | 12.7 | 45 | |
| LT245/70R17 E 119/116R | 50589 | (7.0) 6.5-8.0 | 80 | 2755 | 3000 | 30.60 | 9.56 | 7.45 | 11.3 | 679 | 16 | 12.7 | 46 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | | |
| LT235/75R15 C 104/101Q | 50551 | (6.5) 6.0-7.0 | 50 | 1820 | 1985 | 28.83 | 9.00 | 6.61 | 10.8 | 719 | 16 | 12.7 | 34 | |
| 31X10.50R15LT C 109Q | 50553 | (8.5) 7.0-9.0 | 50 | --- | 2270 | 30.27 | 11.06 | 8.50 | --- | 684 | 16 | 12.7 | 40 | |
| LT245/75R16 C 108/104Q | 50564 | (7.0) 6.5-7.5 | 50 | 2006 | 2205 | 30.44 | 9.57 | 7.45 | 11.3 | 680 | 16 | 12.7 | 42 | |
| LT265/75R16 C 112/109Q | 50567 | (7.5) 7.0-8.5 | 50 | 2270 | 2470 | 31.60 | 10.33 | 7.65 | 12.2 | 654 | 16 | 12.7 | 44 | |
| LT265/75R16 E 123/120Q | 50569 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 31.61 | 10.40 | 7.60 | 12.2 | 654 | 16 | 12.7 | 48 | |
| LT235/80R17 E 120/117R | 50586 | (6.5) 6.0-8.0 | 80 | 2835 | 3085 | 31.65 | 9.40 | 6.85 | 10.8 | 652 | 16 | 12.7 | 44 | |
| LT245/75R17 E 121/118S | 50554 | (7.0) 6.5-8.0 | 80 | 2910 | 3195 | 31.60 | 9.59 | 7.65 | 11.3 | 657 | 16 | 12.7 | 46 | |
| LT265/70R17 E 121/118R | 50592 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.60 | 10.65 | 8.50 | 12.4 | 656 | 16 | 12.7 | 51 | |
| LT275/65R18 E 123/120S | 50555 | (8.0) 7.5-9.5 | 80 | 3085 | 3415 | 32.09 | 10.90 | 8.80 | 12.8 | 645 | 18 | 14.3 | 54 | |



Special Features

- The Discoverer H/T is Cooper's premium touring SUV/light truck original equipment replacement tire.
- It is designed for drivers who want ride comfort, all-season traction and a premium warranty in a highway touring tire.
- The Discoverer H/T is suitable for a wide range of vehicles including SUVs, crossovers (CUV), light trucks and vans up to 1 ton.

DISCOVERER ATR

Premium All Terrain



UTQG 500 A B

SUV Sizes

**50,000 Mile
Treadwear Protection
Limited Warranty**

M+S Rated

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Pass. Max. Load | L.T. Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|---------------------|----------|--|-----|-----------------|----------------|------------------|---------------|-------------|---------------|------------------------|------|-------|----|
| OUTLINE | | | | | | | | | | | | | |
| WHITE LETTER | | | | | | | | | | | | | |
| 225/70R14 99S | 05564 | (6.5) 6.0-7.0 | 44 | 1709 | 1554 | 26.45 | 8.90 | 7.05 | 795 | 12.5 | 9.9 | 26 | \$ |
| 205/75R15 97S | 05565 | (5.5) 5.0-6.5 | 44 | 1609 | 1463 | 27.10 | 7.90 | 6.00 | 771 | 13.5 | 10.7 | 24 | |
| 215/75R15 100S | 05566 | (6.0) 5.5-7.0 | 44 | 1764 | 1604 | 27.60 | 8.40 | 6.40 | 757 | 13.5 | 10.7 | 26 | |
| 225/75R15 102S | 05567 | (6.0) 6.0-7.0 | 44 | 1874 | 1704 | 28.33 | 8.70 | 6.65 | 737 | 13.5 | 10.7 | 27 | |
| 235/75R15 105S | 05568 | (6.5) 6.0-7.5 | 44 | 2039 | 1854 | 28.90 | 9.23 | 7.00 | 723 | 14.0 | 11.1 | 30 | |
| 235/75R15XL 109S | 05569 | (6.5) 6.0-8.0 | 41 | 2271 | 2065 | 28.90 | 9.20 | 7.00 | 723 | 14.0 | 11.1 | 32 | |
| 265/75R15 112S | 05558 | (7.5) 7.0-8.5 | 44 | 2469 | 2245 | 30.69 | 10.50 | 8.00 | 681 | 14.5 | 11.5 | 37 | |
| 205/70R15 96T | 05570 | (6.0) 5.0-7.0 | 44 | 1565 | 1423 | 26.40 | 8.44 | 6.50 | 790 | 13.5 | 10.7 | 24 | |
| 225/70R15 100S | 05571 | (6.5) 6.0-7.5 | 44 | 1764 | 1604 | 27.45 | 9.00 | 7.05 | 763 | 12.5 | 9.9 | 27 | |
| 235/70R15 103S | 05572 | (7.0) 6.0-8.0 | 44 | 1929 | 1754 | 27.99 | 9.45 | 7.40 | 747 | 12.5 | 9.9 | 29 | |
| 255/70R15 108S | 05559 | (7.5) 6.5-8.5 | 44 | 2205 | 2005 | 29.05 | 10.50 | 8.05 | 715 | 14.0 | 11.1 | 34 | |
| 265/70R15 112S | 05560 | (8.0) 7.0-9.0 | 44 | 2469 | 2245 | 29.60 | 10.60 | 8.45 | 706 | 14.0 | 11.1 | 36 | |
| 225/75R16 104S | 05573 | (6.0) 6.0-7.5 | 44 | 1984 | 1804 | 29.25 | 8.71 | 6.65 | 712 | 13.5 | 10.7 | 30 | |
| 235/75R16 108S | 05574 | (6.5) 6.0-8.0 | 44 | 2205 | 2005 | 29.84 | 9.25 | 7.00 | 700 | 14.0 | 11.1 | 33 | |
| 245/75R16 111S | 05575 | (7.0) 6.5-7.5 | 44 | 2403 | 2185 | 30.52 | 9.65 | 7.40 | 685 | 14.0 | 11.1 | 34 | |
| 265/75R16 116S | 05557 | (7.5) 7.0-9.0 | 44 | 2756 | 2505 | 31.65 | 10.51 | 8.00 | 658 | 14.5 | 11.5 | 38 | |
| 215/70R16 100S | 05576 | (6.5) 5.5-7.0 | 44 | 1764 | 1604 | 27.87 | 8.70 | 6.85 | 750 | 13.5 | 10.7 | 29 | |
| 225/70R16 103S | 05577 | (6.5) 6.0-7.0 | 44 | 1929 | 1704 | 28.40 | 8.90 | 7.05 | 736 | 13.5 | 10.7 | 30 | |
| 235/70R16 106T | 05578 | (7.0) 6.0-8.0 | 44 | 2094 | 1904 | 28.99 | 9.46 | 7.43 | 720 | 13.5 | 10.7 | 33 | |
| 245/70R16 107S | 05579 | (7.0) 6.5-8.0 | 44 | 2149 | 1954 | 29.59 | 9.79 | 7.70 | 707 | 13.5 | 10.7 | 33 | |
| 255/70R16 111S | 05561 | (7.5) 6.5-8.5 | 44 | 2403 | 2185 | 30.10 | 10.24 | 8.00 | 695 | 14.0 | 11.1 | 36 | |
| 265/70R16 112T | 05555 | (8.0) 7.0-9.0 | 44 | 2469 | 2245 | 30.45 | 10.90 | 8.45 | 682 | 14.0 | 11.1 | 37 | |
| 235/70R17RE 111S | 05554 | (7.0) 6.0-8.0 | 41 | 2403 | 2185 | 29.99 | 9.46 | 7.43 | 697 | 14.0 | 11.1 | 35 | |
| 245/70R17 110S | 05580 | (7.0) 6.5-8.0 | 44 | 2337 | 2125 | 30.40 | 10.10 | 7.70 | 683 | 14.0 | 11.1 | 33 | |
| 255/70R17 112S | 05581 | (7.5) 6.5-8.5 | 44 | 2469 | 2246 | 31.10 | 10.24 | 8.00 | 671 | 14.0 | 11.1 | 38 | |
| 265/70R17 115S | 05556 | (8.0) 7.0-9.0 | 44 | 2679 | 2435 | 31.60 | 10.70 | 8.45 | 662 | 14.0 | 11.1 | 40 | |
| 235/65R17 104T | 05562 | (7.0) 6.5-8.5 | 44 | 1984 | 1804 | 29.10 | 9.54 | 7.65 | 716 | 13.5 | 10.7 | 33 | |
| 245/65R17 107S | 05551 | (7.0) 7.0-8.5 | 44 | 2149 | 1954 | 29.63 | 9.59 | 8.00 | 704 | 13.5 | 10.7 | 34 | |
| 255/65R17 110S | 05552 | (7.5) 7.0-9.0 | 44 | 2337 | 2125 | 30.05 | 9.88 | 8.45 | 695 | 13.5 | 10.7 | 36 | |
| 265/65R17 112T | 05563 | (8.0) 7.5-9.5 | 44 | 2470 | 2245 | 30.55 | 10.71 | 8.75 | 682 | 13.5 | 10.7 | 38 | |
| 235/60R17 102T | 05582 | (7.0) 6.5-8.5 | 44 | 1874 | 1705 | 28.40 | 9.54 | 7.65 | 734 | 14.0 | 11.1 | 33 | |
| 265/70R18 116S | 05550 | (8.0) 7.0-9.0 | 44 | 2756 | 2508 | 32.60 | 10.70 | 8.45 | 636 | 14.0 | 11.1 | 42 | |
| 265/65R18 114T | 05584 | (8.0) 7.5-9.5 | 44 | 2601 | 2367 | 31.50 | 10.52 | 8.86 | 658 | 13.5 | 10.7 | 41 | |
| 265/60R18 110T | 05583 | (8.0) 7.5-9.5 | 44 | 2337 | 2127 | 30.46 | 10.52 | 9.05 | 680 | 13.5 | 10.7 | 40 | |
| 275/55R20RE .117S | 05553 | (8.5) 7.5-9.5 | 50 | 2833 | 2575 | 31.92 | 11.18 | 9.40 | 654 | 13.0 | 10.3 | 45 | |



LIGHT TRUCK SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Space w/o Chains | Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE | |
|-----------------------------|----------|--|-----|----------------|------------------|------------------|---------------|-------------|----------------------------|---------------|------------------------|------|-------|----|
| BLACKWALL | | | | | | | | | | | | | | |
| LT215/85R16 E 115/112R | 05510 | (6.0) 5.5-7.0 | 80 | 2470 | 2680 | 30.30 | 8.42 | 6.00 | 9.9 | 686 | 16.5 | 13.1 | 38 | \$ |
| LT235/85R16 E 120/116R | 05502 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.78 | 9.36 | 6.70 | 10.8 | 660 | 16.5 | 13.1 | 42 | |
| LT225/75R16 E 115/112R | 05511 | (6.0) 6.0-7.0 | 80 | 2470 | 2680 | 29.39 | 8.92 | 6.90 | 10.2 | 713 | 16.5 | 13.1 | 38 | |
| LT245/75R16 E 120/116R | 05501 | (7.0) 6.5-7.5 | 80 | 2778 | 3042 | 30.37 | 9.26 | 7.40 | 11.3 | 684 | 16.5 | 13.1 | 42 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | | |
| LT235/75R15 C 104/101R | 05520 | (6.5) 6.0-7.0 | 50 | 1820 | 1985 | 28.90 | 9.15 | 7.00 | 10.8 | 723 | 16.0 | 12.7 | 35 | |
| 30X9.50R15LT C 104R | 05518 | (7.5) 6.5-8.5 | 50 | --- | 1985 | 29.30 | 9.60 | 7.30 | --- | 711 | 16.5 | 13.1 | 36 | |
| 31X10.50R15LT C 109R | 05519 | (8.5) 7.0-9.0 | 50 | --- | 2270 | 30.30 | 10.70 | 8.20 | --- | 688 | 16.5 | 13.1 | 40 | |
| LT235/85R16 E 120/116R | 05521 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.78 | 9.36 | 6.70 | 10.8 | 660 | 16.5 | 13.1 | 43 | |
| LT245/75R16 C 108/104R | 05522 | (7.0) 6.5-7.5 | 50 | 2006 | 2205 | 30.52 | 9.62 | 7.40 | 11.3 | 688 | 16.5 | 13.1 | 42 | |
| LT245/75R16 E 120/116R | 05523 | (7.0) 6.5-7.5 | 80 | 2778 | 3042 | 30.37 | 9.26 | 7.40 | 11.3 | 684 | 16.5 | 13.1 | 43 | |
| LT265/75R16 C 112/109R | 05512 | (7.5) 7.0-8.0 | 50 | 2270 | 2470 | 31.60 | 10.49 | 7.80 | 12.2 | 657 | 16.5 | 13.1 | 46 | |
| LT265/75R16 E 123/120R | 05506 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 31.60 | 10.63 | 7.80 | 12.2 | 657 | 16.5 | 13.1 | 48 | |
| LT285/75R16 D 122/119R | 05507 | (8.0) 7.5-9.0 | 65 | 3000 | 3305 | 32.60 | 11.47 | 8.80 | 13.1 | 637 | 17.0 | 13.5 | 51 | |
| LT315/75R16 D 121R | 05513 | (8.5) 8.0-10.0 | 50 | --- | 3195 | 34.5 | 12.43 | 9.80 | --- | 603 | 17.0 | 13.5 | 62 | |
| LT255/70R16 C 108/104R | 05514 | (7.5) 6.5-8.0 | 50 | 1985 | 2205 | 30.08 | 10.38 | 8.10 | 12.3 | 692 | 16.5 | 13.1 | 43 | |
| LT305/70R16 D 118/115R | 05504 | (9.0) 8.0-9.5 | 50 | 2680 | 2910 | 32.95 | 12.24 | 9.70 | 14.2 | 638 | 17.0 | 13.5 | 55 | |
| LT235/80R17 E 120/117R | 05508 | (6.5) 6.0-7.5 | 80 | 2835 | 3085 | 31.78 | 9.23 | 6.70 | 10.8 | 654 | 16.5 | 13.1 | 43 | |
| LT245/75R17 E 121/118S | 05527 | (7.0) 6.5-7.5 | 80 | 2910 | 3195 | 31.50 | 9.95 | 7.65 | 11.3 | 660 | 15.5 | 12.3 | 46 | |
| LT265/70R17 C 112/109R | 05515 | (8.0) 7.0-8.5 | 50 | 2270 | 2470 | 31.58 | 10.61 | 8.50 | 12.4 | 662 | 16.5 | 13.1 | 48 | |
| LT265/70R17 E 121/118R | 05503 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.60 | 10.90 | 8.50 | 12.4 | 659 | 16.5 | 13.1 | 50 | |
| LT275/70R17 C 114/110R | 05505 | (8.0) 7.0-8.5 | 50 | 2335 | 2600 | 32.20 | 11.10 | 8.65 | 12.8 | 647 | 16.5 | 13.1 | 49 | |
| LT285/70R17 D 121/118R | 05516 | (8.5) 7.5-9.0 | 65 | 2910 | 3195 | 32.76 | 11.69 | 9.00 | 13.4 | 636 | 17.0 | 13.5 | 52 | |
| LT315/70R17 D 121/118R | 05509 | (9.5) 8.5-10.0 | 50 | 2910 | 3195 | 34.35 | 12.65 | 9.90 | 14.8 | 606 | 17.0 | 13.5 | 61 | |
| LT275/70R18 E 125/122S | 05526 | (8.0) 7.0-8.5 | 80 | 3305 | 3640 | 33.15 | 11.11 | 9.00 | 12.8 | 627 | 15.5 | 12.3 | 54 | |
| LT275/65R18 C 113/110S | 05524 | (8.0) 7.5-9.5 | 50 | 2335 | 2535 | 32.10 | 11.05 | 8.80 | 12.8 | 647 | 16.0 | 12.7 | 50 | |
| LT275/65R18 E 123/120S | 05525 | (8.0) 7.5-9.5 | 80 | 3085 | 3415 | 32.10 | 11.07 | 8.80 | 12.8 | 647 | 15.5 | 12.3 | 52 | |





Light Truck Sizes M+S Rated

Special Features

- The Discoverer STT is Cooper's premium high void off-road light truck traction tire designed for drivers who want the utmost in off-road traction.
- It is offered in a wide range of commercial and large diameter flotation sizes and is designed for use on pickups, SUVs and off-road vehicles

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | Dual PSI | Single Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Space Chains | Dual Rev. Per Mile | Tread Depth (32nds mm) | Wt. | PRICE |
|-----------------------------|----------|-------------------------------------|----------|------------------|------------------|------------------|---------------|-------------|-------------------|--------------------|------------------------|-----|-------|
| BLACKWALL | | | | | | | | | | | | | |
| LT235/85R16 E 120/116Q | 76104 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.80 | 9.70 | 7.30 | 10.8 | 652 | 18.0 14.3 | 49 | \$ |
| LT325/80R16 D 124/121Q | 76113 | (9.0) 8.5-11.0 | 50 | 3195 | 3525 | 36.78 | 13.10 | 10.80 | 14.8 | 565 | 20.5 16.3 | 85 | |
| LT245/75R16 E 120/116Q | 76103 | (7.0) 6.5-7.0 | 80 | 2778 | 3042 | 30.70 | 9.45 | 7.60 | 11.3 | 675 | 18.0 14.3 | 47 | |
| LT245/70R17 E 119/116Q | 76102 | (7.0) 6.5-8.0 | 80 | 2755 | 3000 | 30.70 | 9.60 | 7.60 | 11.3 | 676 | 18.0 14.3 | 47 | |
| LT295/70R17 D 121/118Q | 76139 | (8.5) 7.5-10.0 | 65 | 2910 | 3195 | 33.45 | 11.80 | 9.40 | 13.7 | 623 | 20.5 16.3 | 63 | |
| 37X12.50R17LT D 124P | 76101 | (10.0) 8.5-11.0 | 50 | ----- | 3525 | 36.90 | 13.10 | 10.00 | ----- | 563 | 23.0 18.3 | 83 | |
| LT275/70R18 E 125/122Q | 76134 | (8.0) 7.0-9.0 | 80 | 3305 | 3640 | 33.35 | 11.00 | 8.80 | 12.8 | 623 | 20.5 16.3 | 60 | |
| LT325/65R18 E 127/124N | 76132 | (9.5) 9.0-12.0 | 65 | 3525 | 3860 | 34.75 | 13.50 | 10.80 | 14.8 | 598 | 23.0 18.3 | 78 | |
| LT305/60R18 E 121/118Q | 76136 | (9.0) 8.5-11.0 | 65 | 2910 | 3195 | 32.64 | 12.09 | 9.80 | 14.2 | 636 | 20.5 16.3 | 65 | |
| LT325/60R18 E 124/121N | 76133 | (9.0) 9.0-12.0 | 65 | 3195 | 3525 | 33.22 | 13.30 | 10.80 | 14.8 | 625 | 23.0 18.3 | 75 | |
| 33X12.50R20LT E 114Q | 76128 | (10.0) 8.5-11.0 | 65 | ----- | 2600 | 32.66 | 12.49 | 9.80 | ----- | 636 | 20.5 16.3 | 65 | |
| 35X12.50R20LT E 121Q | 76130 | (10.0) 8.5-11.0 | 65 | ----- | 3195 | 34.66 | 12.50 | 9.80 | ----- | 599 | 20.5 16.3 | 70 | |
| 35X13.50R20LT E 122N | 76131 | (11.0) 8.5-11.0 | 65 | ----- | 3305 | 34.65 | 13.65 | 10.50 | ----- | 599 | 21.0 16.7 | 77 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | |
| LT235/75R15 C 104/101Q | 76125 | (6.5) 6.0-7.0 | 50 | 1820 | 1985 | 29.09 | 9.45 | 7.00 | 10.8 | 718 | 18.0 14.3 | 39 | |
| 30X9.50R15LT C 104Q | 76107 | (7.5) 6.5-8.5 | 50 | ----- | 1985 | 29.70 | 9.80 | 7.80 | ----- | 708 | 20.0 15.9 | 43 | |
| 31X10.50R15LT C 109Q | 76105 | (8.5) 7.0-9.0 | 50 | ----- | 2270 | 30.75 | 10.85 | 8.30 | ----- | 681 | 20.0 15.9 | 47 | |
| 32X11.50R15LT C 113Q | 76117 | (9.0) 8.0-10.0 | 50 | ----- | 2535 | 31.76 | 11.40 | 9.00 | ----- | 657 | 20.0 15.9 | 49 | |
| 33X12.50R15LT C 108Q | 76115 | (10.0) 8.5-11.0 | 35 | ----- | 2205 | 32.76 | 12.08 | 9.70 | ----- | 637 | 20.5 16.3 | 56 | |
| 35X12.50R15LT C 113Q | 76118 | (10.0) 8.5-11.0 | 35 | ----- | 2535 | 34.76 | 12.20 | 10.00 | ----- | 600 | 20.5 16.3 | 67 | |
| LT225/75R16 E 115/112Q | 76124 | (6.0) 6.0-7.0 | 80 | 2470 | 2680 | 29.53 | 8.70 | 6.70 | 10.2 | 703 | 17.5 13.9 | 43 | |
| LT265/75R16 E 123/120Q | 76111 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 32.00 | 10.10 | 8.25 | 12.2 | 655 | 18.0 14.3 | 53 | |
| LT285/75R16 D 122/119Q | 76112 | (8.0) 7.5-9.0 | 65 | 3000 | 3305 | 33.10 | 11.30 | 8.85 | 13.7 | 646 | 18.0 14.3 | 56 | |
| LT315/75R16 D 121Q | 76126 | (8.5) 8.0-10.0 | 50 | ----- | 3195 | 34.47 | 11.92 | 9.80 | ----- | 620 | 20.0 15.9 | 67 | |
| LT255/70R16 C 108/104Q | 76122 | (7.5) 6.5-8.0 | 50 | 1985 | 2205 | 30.31 | 10.56 | 8.00 | 12.3 | 685 | 17.5 13.9 | 46 | |
| LT265/70R16 C 110/107Q | 76120 | (8.0) 7.0-8.5 | 50 | 2150 | 2335 | 30.86 | 10.94 | 8.40 | 12.4 | 673 | 18.5 14.7 | 49 | |
| LT305/70R16 D 118/115Q | 76121 | (9.0) 8.0-9.5 | 50 | 2680 | 2910 | 33.07 | 12.00 | 9.80 | 13.3 | 628 | 19.0 15.1 | 61 | |
| LT265/70R17 E 121/118Q | 76109 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.90 | 10.80 | 8.25 | 12.4 | 652 | 18.0 14.3 | 53 | |
| LT285/70R17 D 121/118Q | 76110 | (8.5) 7.5-9.5 | 65 | 2910 | 3195 | 33.00 | 11.50 | 8.85 | 13.4 | 646 | 18.0 14.3 | 57 | |
| 33X12.50R17LT D 114Q | 76116 | (10.0) 8.5-11.0 | 50 | ----- | 2600 | 32.76 | 12.54 | 9.80 | ----- | 634 | 20.5 16.3 | 63 | |
| 35X12.50R17LT D 119Q | 76119 | (10.0) 8.5-11.0 | 50 | ----- | 3000 | 34.76 | 12.67 | 9.80 | ----- | 598 | 20.5 16.3 | 68 | |
| LT275/65R18 C 113/110Q | 76108 | (8.0) 7.5-9.0 | 50 | 2335 | 2535 | 32.32 | 10.98 | 8.45 | 12.8 | 643 | 18.0 14.3 | 56 | |
| 35X12.50R18LT E 123Q | 76127 | (10.0) 8.5-11.0 | 65 | ----- | 3415 | 34.76 | 12.50 | 10.00 | ----- | 598 | 20.0 15.9 | 68 | |



COMPTON

1714 Anderson Ave.
Compton, CA 90220
Local 310-631-8200 • Fax 310-631-2503
Toll Free: 1-800-962-5222



BAKERSFIELD

7600 District Blvd., Suite B
Bakersfield, CA 93313
Local 661-831-5600 • Fax 661-831-5641
Toll Free: 1-888-414-8473

HOUSTON

3635 Willowbend Blvd.
Houston, TX 77054
Local 713-660-6600 • Fax 713-660-9633
Toll Free: 1-800-711-3919

MIAMI

9800 NW 100 Road
Medley, FL 33178
Local 305-887-8876 • Fax 305-470-9967
Toll Free: 1-888-833-3953

PORTLAND

7515 N. Leadbetter Dr.
Portland, Oregon 97203
Local 503-283-0416 • Fax 503-240-3342
Toll Free: 1-866-977-8473

UNION CITY

33375 Central Ave.
Union City, CA 94587
Local 510-489-7600 • Fax 510-489-0494
Toll Free: 1-800-447-8473

SAN ANTONIO

4530 Tejasco Dr.
San Antonio, TX 78218
Local 210-212-8866 • Fax 210-212-8815
Toll Free: 1-800-666-8840

TAMPA

9110 King Palm Drive, Suite 106
Tampa FL 33619
Local 813-626-0866 • Fax 813-626-0977
Toll Free: 1-800-483-2099

CHICAGO

3710 N River Road, Suite 400
Franklin Park, IL 60131
Local 708-450-7000 • Fax 708-450-7001
Toll Free: 1-866-220-8439

PHOENIX

601 South 65th Avenue, Suite 6
Phoenix, AZ 85043
Local 623-474-4660 • Fax 623-474-4661
Toll Free: 1-855-825-8473

DALLAS

9500 Royal Lane, Suite 160
Irving, Texas 75063
Local 972-484-6900 • Fax 972-484-7742
Toll Free: 1-888-455-2234

ORLANDO

2222 Diversified Way
Orlando, FL 32804
Local 407-218-4600 • Fax 407-218-4601
Toll Free: 1-800-903-0014

OHIO/MICHIGAN

14801 TR 212
Findlay, OH 45840
Local 419-425-6508 • Fax 419-425-6514
Toll Free: 1-877-309-1972



**Studdable
M+S Rated**

Special Features

- The Discoverer S/T is Cooper's premium all-purpose SUV/light truck traction tire that is a hybrid of three designs – all-terrain, high void and commercial traction.
- The Discoverer S/T fits a wide range of SUVs and light trucks up to 1 ton, but it is especially suitable for high-powered, high-torque light trucks where optimum wear and traction are required.

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

SUV SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Pass. Max. Load | L. T. Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Stud Size | Wt. | PRICE | |
|-------------------------------------|----------|-------------------------------------|-----|-----------------|-----------------|------------------|---------------|-------------|---------------|------------------------|-----------|-----|-------|----|
| BLACKWALL S | | | | | | | | | | | | | | |
| 275/60R20RE 119S | 73420 | (8.5) 8.0-9.5 | 50 | 2998 | 2725 | 33.05 | 12.69 | 9.10 | 629 | 15.0 | 11.9 | 13 | 51 | \$ |
| OUTLINE WHITE LETTER S-RATED | | | | | | | | | | | | | | |
| 235/75R15 105S | 73406 | (6.5) 6.0-8.0 | 35 | 2039 | 1854 | 29.00 | 9.40 | 7.40 | 717 | 15.0 | 11.9 | 13 | 32 | |
| 235/75R15RE 109S | 73405 | (6.5) 6.0-7.5 | 41 | 2271 | 2065 | 29.00 | 9.40 | 7.40 | 717 | 15.0 | 11.9 | 13 | 3 | |
| 245/75R16 111S | 73409 | (7.0) 6.5-8.0 | 35 | 2403 | 2185 | 30.40 | 9.65 | 7.60 | 683 | 15.0 | 11.9 | 13 | 35 | |
| 265/75R16 116S | 73410 | (7.5) 7.0-9.0 | 35 | 2756 | 2505 | 31.55 | 10.55 | 8.30 | 658 | 15.0 | 11.9 | 13 | 40 | |
| 235/70R16 106S | 73412 | (7.0) 6.0-8.0 | 35 | 2094 | 1904 | 28.90 | 9.50 | 7.40 | 719 | 15.0 | 11.9 | 13 | 33 | |
| 255/70R16 111S | 73413 | (7.5) 6.5-8.5 | 35 | 2403 | 2185 | 30.10 | 10.15 | 7.80 | 691 | 15.0 | 11.9 | 13 | 36 | |
| 265/70R16 112S | 73414 | (8.0) 7.0-9.0 | 44 | 2469 | 2245 | 30.63 | 10.71 | 8.40 | 684 | 15.0 | 11.9 | 13 | 38 | |
| 245/70R17 110S | 73416 | (7.0) 6.5-8.0 | 44 | 2337 | 2125 | 30.43 | 9.96 | 7.60 | 683 | 15.0 | 11.9 | 13 | 36 | |



LIGHT TRUCK SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Space w/o Chains | Rev. Per Mile | Tread Depth (32nds mm) | Stud Size | Wt. | PRICE | |
|-----------------------------|----------|-------------------------------------|-----|----------------|------------------|------------------|---------------|-------------|----------------------------|---------------|------------------------|-----------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | | | | |
| LT215/85R16 E 115/112N | 73430 | (6.0) 5.5-7.0 | 80 | 2470 | 2680 | 30.48 | 8.41 | 6.10 | 9.9 | 684 | 18 | 14.3 | 15 | 41 | \$ |
| LT235/85R16 E 120/116N | 73432 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.90 | 9.29 | 7.00 | 10.8 | 654 | 18 | 14.3 | 15 | 45 | |
| LT225/75R16 E 115/112N | 73433 | (6.0) 6.0-7.0 | 80 | 2470 | 2680 | 29.35 | 8.54 | 6.60 | 10.2 | 710 | 18 | 14.3 | 15 | 40 | |
| LT245/75R16 E 120/116N | 73434 | (7.0) 6.5-7.5 | 80 | 2778 | 3042 | 30.53 | 9.76 | 7.45 | 11.3 | 680 | 18 | 14.3 | 15 | 46 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | | | |
| LT235/75R15 C 104/101Q | 73422 | (6.5) 6.0-7.0 | 50 | 1820 | 1985 | 28.62 | 9.14 | 7.20 | 10.8 | 715 | 18 | 14.3 | 15 | 37 | |
| 30X9.50R15LT C 104Q | 73446 | (7.5) 6.5-8.5 | 50 | --- | 1985 | 29.35 | 9.63 | 7.40 | --- | 708 | 18 | 14.3 | 15 | 37 | |
| 31X10.50R15LT C 109Q | 73447 | (8.5) 7.0-9.0 | 50 | --- | 2270 | 30.47 | 10.71 | 8.20 | --- | 687 | 18 | 14.3 | 15 | 41 | |
| 33X12.50R15LT C 108Q | 73448 | (10.0) 8.5-11.0 | 35 | --- | 2205 | 32.63 | 12.36 | 9.80 | --- | 640 | 20 | 15.9 | 17 | 53 | |
| 35X12.50R15LT C 113Q | 73449 | (10.0) 8.5-11.0 | 35 | --- | 2535 | 34.88 | 12.87 | 10.20 | --- | 613 | 20 | 15.9 | 17 | 64 | |
| LT255/85R16 D 119/116N | 73440 | (7.0) 6.5-8.0 | 65 | 2755 | 3000 | 33.21 | 10.04 | 7.20 | 11.7 | 628 | 18 | 14.3 | 15 | 48 | |
| LT265/75R16 C 112/109N | 73443 | (7.5) 7.0-8.0 | 50 | 2270 | 2470 | 31.64 | 10.50 | 8.10 | 12.2 | 654 | 18 | 14.3 | 15 | 47 | |
| LT265/75R16 E 123/120N | 73444 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 31.76 | 10.59 | 8.10 | 12.2 | 654 | 18 | 14.3 | 15 | 52 | |
| LT285/75R16 D 122/119N | 73445 | (8.0) 7.5-9.0 | 65 | 3000 | 3305 | 32.80 | 11.30 | 9.20 | 13.3 | 628 | 20 | 15.9 | 17 | 56 | |
| LT315/75R16 D 121N | 73455 | (8.5) 8.0-10.0 | 50 | --- | 3195 | 34.60 | 12.87 | 10.00 | --- | 615 | 20 | 15.9 | 17 | 65 | |
| LT305/70R16 D 118/115N | 73461 | (9.0) 8.0-9.5 | 50 | 2680 | 2910 | 32.81 | 12.29 | 10.00 | 13.3 | 626 | 18 | 14.3 | 15 | 56 | |
| LT235/80R17 E 120/117Q | 73481 | (6.5) 6.0-8.0 | 80 | 2835 | 3085 | 31.85 | 9.40 | 7.00 | 10.8 | 652 | 18 | 14.3 | 15 | 47 | |
| LT245/75R17 E 121/118Q | 73468 | (7.0) 6.5-8.0 | 80 | 2910 | 3195 | 31.75 | 9.59 | 7.67 | 11.3 | 654 | 18 | 14.3 | 15 | 49 | |
| LT245/70R17 E 119/116Q | 73471 | (7.0) 6.5-8.0 | 80 | 2755 | 3000 | 30.45 | 10.07 | 7.45 | 11.3 | 679 | 18 | 14.3 | 15 | 46 | |
| LT265/70R17 C 112/109Q | 73473 | (8.0) 7.0-8.5 | 50 | 2270 | 2470 | 31.65 | 10.71 | 8.40 | 12.4 | 656 | 18 | 14.3 | 15 | 47 | |
| LT265/70R17 E 121/118Q | 73475 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.65 | 11.03 | 8.40 | 12.4 | 656 | 18 | 14.3 | 15 | 52 | |
| LT275/70R17 C 114/110Q | 73478 | (8.0) 7.0-9.0 | 50 | 2335 | 2600 | 32.20 | 11.32 | 8.80 | 12.8 | 645 | 18 | 14.3 | 15 | 50 | |
| LT285/70R17 D 121/118Q | 73480 | (8.5) 7.5-9.5 | 65 | 2910 | 3195 | 32.80 | 11.35 | 9.10 | 13.4 | 634 | 18 | 14.3 | 15 | 55 | |
| 33X12.50R17LT D 114Q | 73450 | (10.0) 8.5-11.0 | 50 | --- | 2600 | 32.63 | 12.36 | 9.80 | --- | 640 | 20 | 15.9 | 17 | 58 | |
| 35X12.50R17LT D 119Q | 73451 | (10.0) 8.5-11.0 | 50 | --- | 3000 | 34.88 | 12.87 | 10.20 | --- | 613 | 20 | 15.9 | 17 | 66 | |
| LT275/70R18 E 125/122Q | 73484 | (8.0) 7.0-9.0 | 80 | 3305 | 3640 | 33.30 | 10.95 | 8.80 | 12.8 | 624 | 18 | 14.3 | 15 | 56 | |
| LT275/65R18 E 123/120Q | 73424 | (8.0) 7.5-9.5 | 80 | 3085 | 3415 | 32.30 | 10.90 | 8.80 | 12.8 | 643 | 18 | 14.3 | 15 | 55 | |



**Studdable
M+S Rated**

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Space w/o Chains | Rev. Per Mile | Tread Depth (32nds mm) | Stud Size | Wt. | PRICE | |
|-----------------------------|----------|-------------------------------------|-----|----------------|------------------|------------------|---------------|-------------|----------------------------|---------------|------------------------|-----------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | | | | |
| LT235/85R16 E 120/116N | 52032 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.90 | 9.29 | 7.00 | 10.8 | 654 | 18 | 14.3 | 15 | 45 | \$ |
| LT245/75R16 E 120/116N | 52034 | (7.0) 6.5-7.5 | 80 | 2778 | 3042 | 30.53 | 9.76 | 7.45 | 11.3 | 680 | 18 | 14.3 | 15 | 45 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | | | |
| LT265/75R16 E 123/120N | 52044 | (7.5) 7.0-8.0 | 80 | 3085 | 3415 | 31.76 | 10.59 | 8.10 | 12.2 | 654 | 18 | 14.3 | 15 | 50 | |
| NEW LT265/70R17 E 121/118Q | 52043 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.65 | 11.03 | 8.40 | 12.4 | 656 | 18 | 14.3 | 15 | 51 | |

Special Features

- The Discoverer S/T-C is Cooper's premium all-purpose light truck traction tire that utilizes a special cut and chip resistance tread compound.
- A hybrid of three designs – all-terrain, high void and commercial traction – the Discoverer S/T-C is especially suited for off-road applications where cutting and chipping of the tread that leads to reduced mileage is of primary concern.





**SUV & Light Truck Sizes
Studdable
M+S Rated**

Special Features

- The Discoverer M+S is Cooper's premium studdable winter SUV/light truck tire designed for drivers looking for excellent traction on snow and ice.
- The Discoverer M+S line fits a wide range of SUVs and light trucks, foreign and domestic.

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

SUV SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Pass. Max. Load | L. T. Max. Load | Overall Diameter | Section Width | Tread Width | Rev. Per Mile | Tread Depth (32nds mm) | Stud Size | Wt. | PRICE | |
|-----------------------------|----------|-------------------------------------|-----|-----------------|-----------------|------------------|---------------|-------------|---------------|------------------------|-----------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | | | |
| 225/70R14 99S | 50471 | (6.5) 6.0-7.5 | 35 | 1709 | 1554 | 26.25 | 9.10 | 7.00 | 790 | 15 | 11.9 | 13 | 27 | \$ |
| 235/75R15 105S | 50444 | (6.5) 6.0-8.0 | 35 | 2039 | 1854 | 29.00 | 9.60 | 7.20 | 717 | 15 | 11.9 | 13 | 32 | |
| 235/75R15 RE 109S | 50445 | (6.5) 6.0-7.5 | 41 | 2271 | 2065 | 29.00 | 9.40 | 7.20 | 717 | 15 | 11.9 | 13 | 33 | |
| 265/75R15 112S | 50447 | (7.5) 7.0-9.0 | 35 | 2469 | 2245 | 30.60 | 10.65 | 8.10 | 679 | 15 | 11.9 | 13 | 37 | |
| 235/70R15 103S | 50475 | (7.0) 6.0-7.5 | 35 | 1929 | 1754 | 28.00 | 9.65 | 7.40 | 746 | 15 | 11.9 | 13 | 30 | |
| 265/70R15 112S | 50478 | (8.0) 7.0-9.0 | 35 | 2469 | 2245 | 29.43 | 10.45 | 8.00 | 707 | 15 | 11.9 | 13 | 35 | |
| 225/75R16 104S | 50448 | (6.0) 6.0-7.5 | 35 | 1984 | 1804 | 29.18 | 8.65 | 6.80 | 713 | 15 | 11.9 | 13 | 31 | |
| 235/75R16 108S | 50449 | (6.5) 6.0-8.0 | 35 | 2205 | 2005 | 29.85 | 9.30 | 7.00 | 697 | 15 | 11.9 | 13 | 34 | |
| 245/75R16 111S | 50450 | (7.0) 6.5-8.0 | 35 | 2403 | 2185 | 30.40 | 9.60 | 7.40 | 683 | 15 | 11.9 | 13 | 35 | |
| 265/75R16 116S | 50451 | (7.5) 7.0-9.0 | 35 | 2756 | 2505 | 31.60 | 10.60 | 8.10 | 658 | 15 | 11.9 | 13 | 39 | |
| 215/70R16 100S | 50480 | (6.5) 5.5-7.0 | 35 | 1764 | 1604 | 27.75 | 8.80 | 7.20 | 753 | 15 | 11.9 | 13 | 30 | |
| 225/70R16 103S | 50481 | (6.5) 6.0-7.5 | 35 | 1929 | 1704 | 28.30 | 9.00 | 7.00 | 733 | 15 | 11.9 | 13 | 30 | |
| 235/70R16 106S | 50482 | (7.0) 6.0-7.5 | 35 | 2094 | 1904 | 28.85 | 9.40 | 7.40 | 719 | 15 | 11.9 | 13 | 32 | |
| 245/70R16 107S | 50483 | (7.0) 6.5-8.0 | 35 | 2149 | 1954 | 29.50 | 9.85 | 7.70 | 705 | 15 | 11.9 | 13 | 34 | |
| 255/70R16 111S | 50484 | (7.5) 6.5-8.0 | 35 | 2403 | 2185 | 29.90 | 10.30 | 8.00 | 693 | 15 | 11.9 | 13 | 35 | |
| 265/70R16 112S | 50485 | (8.0) 7.0-9.0 | 35 | 2469 | 2245 | 30.40 | 10.80 | 8.00 | 682 | 15 | 11.9 | 13 | 39 | |
| 245/70R17 110S | 50486 | (7.0) 6.5-8.0 | 44 | 2337 | 2125 | 30.50 | 9.85 | 7.70 | 681 | 14 | 11.1 | 13 | 35 | |
| 265/70R17 115S | 50488 | (8.0) 7.0-9.0 | 35 | 2679 | 2435 | 31.40 | 10.65 | 8.30 | 660 | 15 | 11.9 | 13 | 40 | |
| 255/60R17 106S | 50495 | (7.5) 7.0-9.0 | 44 | 2094 | 1904 | 29.06 | 10.29 | 8.80 | 715 | 14 | 11.1 | 13 | 36 | |
| 255/65R18 RE 109S | 50498 | (8.0) 7.0-9.0 | 50 | 2271 | 2065 | 29.12 | 10.36 | 8.90 | 713 | 14 | 11.1 | 13 | 41 | |
| 275/60R20 RE 97S | 50499 | (8.5) 8.0-9.5 | 50 | 2998 | 2725 | 33.08 | 12.69 | 9.22 | 628 | 14 | 11.1 | 13 | 50 | |
| OUTLINE WHITE LETTER | | | | | | | | | | | | | | |
| 255/65R16 109S | 50490 | (7.5) 7.0-9.0 | 35 | 2271 | 2065 | 29.18 | 10.24 | 8.25 | 718 | 14 | 11.1 | 13 | 36 | |
| 235/65R17 104S | 50493 | (7.0) 6.5-8.5 | 35 | 1984 | 1804 | 29.11 | 9.45 | 7.65 | 716 | 14 | 11.1 | 13 | 33 | |
| 245/65R17 107S | 50494 | (7.0) 7.0-8.5 | 35 | 2149 | 1954 | 29.52 | 9.82 | 9.27 | 708 | 14 | 11.1 | 13 | 36 | |
| 275/60R17 110S | 50496 | (8.0) 7.5-9.5 | 35 | 2337 | 2125 | 30.10 | 11.20 | 9.02 | 699 | 14 | 11.1 | 13 | 39 | |



LIGHT TRUCK SIZES

| Tire Size | Code No. | Meas. Rim Width/ Approved Rim Width | PSI | Dual Max. Load | Single Max. Load | Overall Diameter | Section Width | Tread Width | Min. Dual Space w/o Chains | Rev. Per Mile | Tread Depth (32nds mm) | Stud Size | Wt. | PRICE | |
|------------------------|----------|-------------------------------------|-----|----------------|------------------|------------------|---------------|-------------|----------------------------|---------------|------------------------|-----------|-----|-------|----|
| BLACKWALL | | | | | | | | | | | | | | | |
| LT235/75R15 C 104/101Q | 50410 | (6.5) 6.0-7.0 | 50 | 1820 | 1985 | 28.82 | 9.00 | 7.20 | 10.8 | 715 | 17 | 13.5 | 15 | 34 | \$ |
| 31X10.50R15LT C 109Q | 50414 | (8.5) 7.0-9.0 | 50 | --- | 2270 | 30.25 | 10.50 | 8.20 | --- | 685 | 19 | 15.1 | 15 | 40 | |
| LT215/85R16 E 115/112Q | 50422 | (6.0) 5.5-7.0 | 80 | 2470 | 2680 | 30.28 | 9.10 | 5.90 | 9.9 | 684 | 17 | 13.5 | 15 | 38 | |
| LT235/85R16 E 120/116Q | 50424 | (6.5) 6.0-7.0 | 80 | 2778 | 3042 | 31.78 | 9.31 | 6.94 | 10.8 | 654 | 17 | 13.5 | 15 | 43 | |
| LT225/75R16 E 115/112Q | 50431 | (6.0) 6.0-7.0 | 80 | 2470 | 2680 | 29.30 | 8.95 | 6.70 | 10.2 | 710 | 17 | 13.5 | 15 | 39 | |
| LT245/75R16 C 108/104Q | 50434 | (7.0) 6.5-7.5 | 50 | 2006 | 2205 | 30.44 | 9.57 | 7.45 | 11.3 | 680 | 17 | 13.5 | 15 | 41 | |
| LT245/75R16 E 120/116Q | 50432 | (7.0) 6.5-7.5 | 80 | 2778 | 3042 | 30.44 | 9.57 | 7.45 | 11.3 | 680 | 18 | 14.3 | 15 | 45 | |
| LT265/75R16 C 112/109Q | 50435 | (7.5) 7.0-8.0 | 50 | 2270 | 2470 | 31.54 | 10.33 | 8.14 | 12.2 | 654 | 17 | 13.5 | 15 | 44 | |
| LT265/75R16 E 123/120Q | 50437 | (7.5) 7.0-8.5 | 80 | 3085 | 3415 | 31.54 | 10.50 | 8.14 | 12.2 | 654 | 17 | 13.5 | 15 | 49 | |
| LT235/80R17 E 120/117Q | 50419 | (6.5) 6.0-8.0 | 80 | 2835 | 3085 | 31.85 | 9.40 | 7.00 | 10.8 | 652 | 17 | 13.5 | 15 | 45 | |
| LT245/70R17 E 119/116Q | 50416 | (7.0) 6.5-8.0 | 80 | 2755 | 3000 | 30.45 | 10.07 | 7.45 | 11.3 | 679 | 17 | 13.5 | 15 | 44 | |
| LT265/70R17 E 121/118Q | 50417 | (8.0) 7.0-8.5 | 80 | 2910 | 3195 | 31.65 | 11.03 | 8.40 | 12.4 | 656 | 17 | 13.5 | 15 | 50 | |
| LT275/70R17 C 114/110Q | 50418 | (8.0) 7.0-9.0 | 50 | 2335 | 2600 | 32.20 | 11.32 | 8.80 | 12.8 | 645 | 17 | 13.5 | 15 | 48 | |
| LT275/70R18 E 125/122R | 50411 | (8.0) 7.0-9.0 | 80 | 3305 | 3640 | 33.15 | 10.95 | 9.00 | 12.8 | 626 | 17 | 13.5 | 15 | 55 | |

