



1ST 50% FREE REPLACEMENT WARRANTY

DOUBLE COIN FR605

Fuel Efficient / Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	.14		144/142	M	41.4	11.1	17	8.25	19.8	496	\$	
11R22.5	.16		148/145	M	41.4	11.1	17	8.25	19.8	496		
295/75R22.5	.14		144/141	M	40.6	11.7	17	9.0	19.5	504		
11R24.5	.14		146/143	M	43.3	10.9	17	8.25	20.8	473		
11R24.5	.16		149/146	M	43.3	10.9	17	8.25	20.8	473		
285/75R24.5	.14		144/141	M	41.5	11.0	17	8.25	19.5	492		

Ultra Premium Fuel Efficient Steer Position Tire

- Advanced tread compounds, design and internal construction provide low rolling resistance and longer mileage.
- 5-Rib tread design enhances even wear, traction in long haul steer axle positions.
- Features extensive siping & side-shoulder decoupling groove to enhance even wear, traction in long haul steer axle positions.

DOUBLE COIN FD405

Fuel Efficient / Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	.14		143/139	J	42	10.9	26	8.25	20.1	488	\$	
11R22.5	.16		148/145	J	42	10.9	26	8.25	20.1	488		
295/75R22.5	.14		144/141	J	41.2	11.7	26	9	19.4	498		
11R24.5	.14		145/141	J	43.9	10.9	26	8.25	21.1	466		
11R24.5	.16		149/145	J	43.9	10.9	26	8.25	21.1	466		
285/75R24.5	.14		144/141	J	42.1	11	26	8.25	19.8	485		

Ultra Premium Fuel Efficient Drive Position Tire

- Advanced tread compounds and internal construction provide low rolling resistance and longer mileage.
- Advanced tread compounds and internal construction provide low rolling resistance and longer mileage.
- Deep 26/32" tread with stone drilling protectors to promote long original mileage.

DOUBLE COIN FT105

Fuel Efficient / Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	.14		143/139	M	41.0	10.9	12	8.25	19.5	500	\$	
11R22.5	.16		148/145	M	41.0	10.9	12	8.25	19.5	500		
295/75R22.5	.14		144/141	M	40.2	11.7	12	9	18.9	510		
11R24.5	.14		145/141	L	42.9	10.9	12	8.25	20.8	476		
11R24.5	.16		149/145	L	42.9	10.9	12	8.25	20.8	476		
285/75R24.5	.14		144/141	J	41.1	11	12	8.25	19.3	505		

Ultra Premium Fuel Efficient Trailer Position Tire

- Advanced tread compounds and internal construction provide low rolling resistance and longer mileage.
- Extensive tread siping help fight irregular wear in free rolling positions.
- Durable casing provides long original tread life and promotes multiple retreads.

DOUBLE COIN RT606+

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	14	59813	144/142	L	41.6	11.1	22	8.25	19.8	496		\$
11R22.5	16	59814	146/143	L	41.6	11.1	22	8.25	19.8	496		
295/75R22.5	14	59815	144/141	L	40.7	11.7	22	9	19.5	496		
11R24.5	14	59816	146/143	L	43.5	10.9	22	8.3	20.8	473		
11R24.5	16	59833	149/146	L	43.5	10.9	22	8.25	20.8	473		
285/75R24.5	14	59834	144/141	L	41.5	10.6	22	8.25	19.5	492		

Premium regional steer 5-rib steel radial highway service.

DOUBLE COIN RR680

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
9R22.5	14	136/134	L	38.3	9.1	18	6.75	17.9	206			\$
11R22.5	14	144/142	L	41.4	11.1	20	8.25	19.8	499			
11R22.5	16	148/145	L	41.4	11.1	20	8.25	19.8	499			
295/75R22.5	14	144/141	M	40.6	11.7	20	9.0	19.5	504			
11R24.5	14	145/141	L	43.3	10.9	20	8.25	20.8	476			
11R24.5	16	149/145	L	43.3	10.9	20	8.25	20.8	576			
285/75R24.5	14	144/141	M	41.5	11	20	8.25	19.5	492			
295/80R22.5	16	150/148	M	41.3	11.9	18	9	19.8	191			
315/80R22.5	20	156/150	L	42.4	12.2	18	9.0	19.9	188			

Premium Regional/All-Position Steer Tire

DOUBLE COIN RT600

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
225/70R19.5	12	125/123	J	32.3	8.2	16	6.75	15.2	635			\$
245/70R19.5	16	141/140	J	33.3	9.5	16	7.5	15.8	610			
265/70R19.5	16	143/141	J	34.3	10	16	7.5	15.9	606			
9R22.5	14	136/134	L	38.3	9.1	18.3	6.75	17.9	206			
8R19.5	12	124/122	J	34.1	8.2	16	6.5	16.3	592			
10R22.5	14	141/136	M	40.2	10	18	7.5	18.9	510			
275/70R22.5	16	141/145	M	37.9	11	18	8.25	17.7	543			

Premium Low Profile Regional/All-Position Steer Tire

DOUBLE COIN RR150

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
1000R20	16	17753	148/144	L	41.1	10.7	19	7.50	19.4	497		\$
11R22.5	14	21608	143/139	M	41.2	11.3	19	8.25	19.8	496		
11R22.5	16	33265	148/145	M	41.2	11.3	19	8.25	19.8	496		
295/75R22.5	14	17402	144/141	M	40.2	11.5	20	9.00	19.1	506		
11R24.5	14	21609	145/141	L	43.1	11.3	20	8.25	20.8	473		
11R24.5	16	18875	149/145	M	43.1	11.3	20	8.25	20.8	473		
285/75R24.5	14	21610	144/141	M	41.3	11.2	20	8.25	19.5	492		

Premium all-position 5-rib steel radial highway service.

DOUBLE COIN RR300

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	14	17480	143/139	M	41.2	11.3	19	8.25	19.8	496		\$
11R22.5	16	18872	148/145	M	41.2	11.3	19	8.25	19.8	496		
295/75R22.5	14	18873	144/141	M	40.2	11.5	20	9.00	19.1	506		
11R24.5	14	18874	145/141	L	43.1	11.3	20	8.25	20.8	473		
11R24.5	16	18875	149/145	L	43.1	11.3	20	8.25	20.8	473		
285/75R24.5	14	18876	144/141	M	41.3	11.2	20	8.25	19.5	492		
295/80R22.5	16	154/150	M	41.6	12.2	19	9	20.2	493			

Ultra premium all-position steel radial highway service.

DOUBLE COIN TR100

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	14	3895	143/139	M	40.7	11.3	14	8.25	19.5	500		\$
11R22.5	16	26658	148/145	M	40.7	11.3	14	8.25	19.5	500		
295/75R22.5	14	3896	144/141	M	39.8	11.5	14	9	18.9	510		
11R24.5	14	3897	145/141	L	42.7	11.3	14	8.25	20.8	476		
11R24.5	16	26659	149/145	L	42.7	11.3	14	8.25	20.8	476		
285/75R24.5	14	3898	144/141	J	40.9	11.2	14	8.25	19.3	505		

Shallow tread all-position steel radial highway service.

DOUBLE COIN RT500

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
NEW 7.50R16	.14	26071	122/118	J	31.7	8.3	.16	6	14.6	662	\$	
NEW 8.25R15	.14		129/127	K	33.2	9.1	.16	6.5	15.4	627		
8.25R15	.18	26069	143/141	J	33.2	9.1	.16	6.5	15.4	627		
NEW 10.00R15	.16		141/139	K	36.3	10.8	.16	7.5	17	570		
10.00R15	.14	26070	148/145	J	36.3	10.8	.16	7.5	16.9	570		
8R17.5	.10	25517	117/116	L	30.9	8.2	.16	6.00	14.3	675		
10R17.5	.16	22146	143/141	J	33.9	9.8	.16	7.50	15.7	613		
215/75R17.5	.16		135/133	J	30.3	8.5	.16	6.00	14.4	692		
8R19.5	.12	8811	124/122	J	33.9	8.1	.16	6.00	16.3	592		
225/70R19.5	.12	17499	125/123	J	32.1	8.7	.16	6.75	15.2	635		
245/70R19.5	.16	8809	141/140	J	33.1	9.5	.16	7.50	15.8	610		
265/70R19.5	.16	3900	143/141	J	34.1	10.2	.16	7.50	15.9	606		
255/70R22.5	.16	3901	140/137	N	36.5	10	.16	7.50	17.4	560		
275/70R22.5	.16	3902	148/145	M	37.7	10.4	.16	8.25	17.7	543		

Premium all-position low profile steel radial highway service.

DOUBLE COIN RR400

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
9.00R20	.14	65339	141/136	L	40.2	10.1	.19	7	18.9	611	\$	
10R22.5	.14	18877	141/136	L	40.1	9.5	.19	7.5	18.9	510		

Premium 3-rib all-position steel radial highway service.

DOUBLE COIN RLB300

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
8.25R20	.14	18878	134/136	L	38.4	9.3	.21	6.50	15.5	627	\$	

All-position 4-rib steel radial highway service

DOUBLE COIN RR200L

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
NEW 315/80R22.5	.18	65333	156/152	M	42.5	12	.19	9	19.5	485	\$	
315/80R22.5	.20	3884	157/154	K	42.1	12.0	.18	9.00	19.9	485		

Premium all-position steel radial highway service with decoupling groove.

DOUBLE COIN RLB400

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	.14	3906	143/139	J	41.9	11.3	.30	8.25	20.1	488	\$	
11R22.5	.16	3907	148/145	J	41.9	11.3	.30	8.25	20.1	488		
295/75R22.5	.14	3909	144/141	J	40.8	11.5	.30	9.00	19.4	498		
11R24.5	.14	3908	145/141	J	43.7	11.3	.30	8.25	21.1	466		
11R24.5	.16	8813	149/145	J	43.7	11.3	.30	8.25	21.1	466		
285/75R24.5	.14	3910	144/141	J	41.9	11.2	.30	8.25	19.8	485		

Premium closed shoulder on highway steel radial drive position.

DOUBLE COIN RLB450

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	.14	60504	143/137	M	41.9	12.9	.26	8.7	19.8	493	\$	
11R22.5	.16	60535	148/145	M	41.9	12.9	.26	8.7	19.8	493		
11R24.5	.14	60546	143/139	M	41.7	10.9	.26	8.25	19.8	471		
11R24.5	.16	60548	148/145	M	41.7	10.9	.26	8.25	19.8	471		
295/75R22.5	.14	60537	144/141	M	40.8	11.7	.26	8.7	19.4	495		
285/75R24.5	.14	60549	144/141	M	41.9	11	.26	8.25	19.8	485		
315/80R22.5	.20	60540	156/150	L	43.2	12.5	.29	9		480		

Premium open shoulder heavy-duty on highway service.

DOUBLE COIN RLB1

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
NEW 9.00R20	16	16738	144/139	J	40.6	10.1	26	7.5	19.1	505		\$
1000R20	16	16737	148/144	J	41.3	10.7	22	7.50	19.4	497		
100R22.5	14	41116										
NEW 1100R20	16	19176	149/145	J	43.1	11.2	29	.8	20.2	476		
11R22.5	14	3889	143/139	M	41.5	11.3	26	8.25	19.8	493		
11R24.5	14	3891	145/141	L	43.4	11.3	26	8.25	21.0	471		
11R24.5	16	3892	149/145	L	43.4	11.3	26	8.25	21.0	471		
295/75R22.5	14	16980	144/141	M	40.1	11.7	26	9.00	19.4	498		
285/75R24.5	14	16979	144/141	L	41.5	11.1	26	8.25	19.8	485		

Premium on highway steel radial drive position.

DOUBLE COIN RLB200+

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
315/80R22.5/18	18	71211	156/152	L	42.8	12.2	26	.9	20.2	478		\$
12.00R24	18		158/155	J	48.4	12.3	24	8.5	22.7	423		
12R22.5	16		152/148	J	43.1	11.7	26	.9	20.5	480		

Premium on/off highway drive position tire.

DOUBLE COIN RR99

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
1000R20	16	41122	148/144	L	41.2	10.7	20	7.5	19.4	497		\$
1100R20	16	41123	149/145	L	42.8	11.3	20	.8	20.1	478		
11R22.5	16	59855	148/145	L	41.3	10.9	18	8.25	19.5	496		
315/80R22.5	20	59856	157/154	K	42.4	12.2	18	.9	19.9	483		
11R24.5	16	59869	149/146	L	43.4	10.9	21	8.25	21	484		
12R22.5	16	41125	152/148	L	42.7	11.8	21	.9	20.1	516		
315/80R22.5	22		160/157	J	42.4	12.2	20	.9	19.9	483		

Heavy duty all position on/off hwy.

DOUBLE COIN RR900

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
385/65R22.5	18	3894	160	K	42.1	15.0	20	11.75	20.1	486		\$

Premium wide-base all-position steel radial mixed service.

DOUBLE COIN RLB900+

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
385/65R22.5	18	59850	160/158	K	42.2	14.8	22	11.75	20.1	483		\$
425/65R22.5	20	59851	165	K	44.6	16.3	22	13	21.2	458		
445/65R22.5	20	59854	168	J	45.3	17.9	22	14	20.9	457		

Premium wide base all position steel radial mixed service.

DOUBLE COIN RLB490

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
225/70R19.5	12	59835	125/123	J	32.6	8.8	19	6.75	15.8	635		\$
245/70R19.5	16	59838	135/133	J	33.5	9.6	19	7.5	15.2	617		
255/70R22.5	16	59846	140/137	J	37	10	22	7.5	17	597		
265/70R19.5	16	59839	143/141	J	34.6	10	22	7.5	16.4	615		
275/70R22.5	16	59849	148/145	J	38.1	11	22	8.25	17.7	543		

Premium regional traction drive.

DOUBLE COIN RLB800

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
1000R20	.16	16740	148/144	G	41.7	10.7	.29	7.50	19.7	489	\$	
11R22.5	.16	16741	148/145	G	41.8	11.3	.29	8.25	20.0	491		
11R24.5	.16	16742	149/145	G	43.6	11.3	.29	8.25	21.0	468		

Premium non-siped on/off highway steel radial traction.

DOUBLE COIN RLB600

Medium Truck Radial



Tire Size	Ply Rating	Code #	Load Index (S/D)	Speed Symbol	Overall Diameter	Section Width	Tread Depth	Rim Width	Loaded Radius	Revs per Mile	PRICE	F.E.T.
11R22.5	.16	23461	148/145	G	42.8	11.3	.33	8.25	20.6	478	\$	
11R24.5	.16	20168	149/145	G	44.8	11.3	.33	8.25	21.6	455		

Deep tread mining and logging steel radial on/off road service.

Quality Assurance Program

50% Free replacement warranty - Casing warranty through life of second retread - Free labor for replacement tire

Limited Warranty – China Manufacturers Alliance (CMA) hereby warrants that every new Double Coin radial truck tire is free from defects in workmanship and material for the life of the original tread of a new tire less 2/32" and the life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining, at which point the tire is considered to be fully worn out.

50% Free Replacement Warranty – If a defect in workmanship and warranty is found in any Double Coin radial truck tire within the first 50% of tread wear (calculated by subtracting one-half (1/2) the difference between the original new tire tread depth), CMA will refund the cost of a replacement Double Coin radial truck tire plus the cost of mounting and balancing as follows:

A) The defective Double Coin tire must be replaced with a comparable new Double Coin tire by an authorized Double Coin dealer. Proof of replacement is required.

B) Costs of mounting and balancing will be refunded up to a maximum of \$16.00 per tire. Written proof of these costs will be required.

C) Applicable taxes on the new tire shall be borne by the owner.

D) 50% free replacement applies to new first quality tires only. Blems, retreads and road hazard tires are specifically excluded.

General Warranty – If a defect in workmanship and materials is found in any Double Coin radial truck tire after the first 50% of tread wear of the original usable tread has worn out, a credit will be given toward the purchase of a comparable new Double Coin tire in proportion of the original usable tread remaining on such defective tire to the original usable tread of the new tire. Applicable taxes on the new tire and costs of mounting and balancing service will be borne by the owner. Adjustment on out-of-balance or out-of-round tires is allowed only during the first 2/32" of the original tread.

DOUBLE COIN RADIAL OTR

Medium Truck Radial



REM-2



REM-3



REM-6



REM-8

Tire Size	Code	Load Symbol	Overall Diameter	Section Width	Tread Depth	Rim	Speed (mph)	Single Max Load	Load (lb/psi)	Load Index	Tire Weight	PRICE
REM-2												
17.5R25	.37038		52.8	17.6	.22	14.00/1.5	.31	9075	.24	157	.319	\$
							6	15260	.31	176		
NEW 17.5R25	.72079		53	18	.34	14.00/1.5	.30	11990	.76		.338	
REM-2												
20.5R25	.37055		52.8	20.7	.31	17.00/2.	.31	12320	.24	168	.484	
							6	20900	.31	186		
20.5R25	.41215		58	21	.39	17.00/2.0	.31	12300	.51	168	.488	
							6	20900	.65	186		
23.5R25	.40911		64	24	.45	19.50/2.5	.31	20400	.65	185	.721	
							6	32000	.83	201		
29.5R25	.44579		73	29	.50	25.00/3.5	.31	30900	.65	200		
							6	49400	.83	216		
REM-3												
12R16.5	.37036		33	12	.29	9.75	.22	5676	.65	141	.42.1	
REM-6												
NEW 6.50R10	.73450		23	7	.28	.5		3960	.145		.39	
7.00R12	.39562		26	8	.35	5.00S	.22	4939	.145	136	.26.8	
8.25R25	.40311	153A5	33	9.4	.32	6.5	.13	8050	.145	49		
								Steer position				
								10470	.145			
								Steer position				
2.50R15	.37039	153A5	29	9.9	.33	.7	.22				.37	
6.00R9	.121A5		21.3	6.4	.31	4.00E	.22	3197	.145	121	.16.9	
7.00R12	.39562	136A5	26.4	7.5	.35	5.00S	.22	4939	.145	136	.26.8	
7.00R15		143A5	29	7.7	.35	5.5	.22	6009	.145	143	.31.5	
315/70R15		165A5	32.9	12.3	.45	.8	.22	11356	.145	165		
12.00R20		176A5	44.7	12.6	.52	8.5	.22	15656	.145	176	.114.7	
REM-8												
14.00R24		170E										
14.00R25		170E	53.5	15.4	.31.5							
16.00R25		177E	58.8	17	.32.8							
16.00R25		177F	58.8	17	.32.8							
20.5R25		179E	58.7	21.3	.39.1							

Premium non-siped on/off highway steel radial traction.