

FALKEN TIRE

FALKEN AZENIS PT722 A/S

Race Bread UHP Radial



**Limited Treadwear
Warranty**

**440 AA UTQG -
40,000**

**600 AA UTQG -
60,000**

- Newly developed wide steel belts that are stronger than normal cord, offer better wear and performance.
- Long lateral groove reduces hydroplaning and provides excellent driving stability in wet conditions.
- Unique rib groove inhibits irregular wear by enhancing rigidity of the tread.
- Deep tread depth improves mileage and increases longevity.
- Jointless nylon cap ply & layer increase durability at speed and in wet conditions.
- High density casing ply improves wear resistance.
- Rotation wear indicators regularly inform drivers of proper rotation timing.

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
UTQG 440 AA												
215/55R16	28222662	7.0	6.0 - 7.5	25.2	8.81	837	7.3	11.0	24.9	51	1764	\$
205/50R17	28222770	6.5	5.5 - 7.5	25.2	8.35	832	7.2	10.5	22.9	50	1609	
215/50R17	28222771	7.0	6.0 - 7.5	25.6	8.81	821	7.6	11.0	24.9	51	1609	
215/45R17	28222792	7.0	7.0 - 8.0	24.6	8.42	842	7.7	11.0	22.9	50	1521	
235/50R18	28222825	7.5	6.5 - 8.5	27.4	9.59	769	8.3	11.0	28.4	50	1819	
225/45ZR18	28223824	7.5	7.0 - 8.5	26.0	8.93	800	8.1	10.5	24.0	51	1356	
225/40ZR18	28223892	8.0	7.5 - 9.0	25.0	9.10	832	8.1	10.5	24.6	51	1477	
235/40R18	28222893	8.5	8.0 - 9.5	25.4	9.54	818	8.5	11.0	25.7	50	1356	
255/40R18	28222844	9.0	8.5 - 10.0	26.0	10.23	800	9.1	11.0	28.4	51	1609	
265/35R18	28222806	9.5	9.0 - 10.0	25.3	10.62	821	9.5	11.0	27.5	50	1609	
275/35ZR18	28223807	9.5	9.0 - 11.0	25.6	10.69	811	9.8	10.5	28.4	50	1609	
245/45ZR19	28223904	8.0	7.5 - 9.0	27.7	9.54	753	8.7	10.5	30.1	51	1764	
245/40ZR19	28223974	8.5	8.0 - 9.5	26.7	9.73	776	8.7	10.5	28.8	51	1477	
275/40ZR19	28223903	9.5	9.0 - 11.0	27.7	10.81	753	9.7	10.5	31.2	50	1433	
245/35ZR19	28223984	8.5	8.0 - 9.5	25.8	9.64	803	8.8	10.5	26.4	51	1764	
275/30ZR19	28223977	9.5	9.0 - 10.0	25.6	10.59	808	9.8	10.5	29.0	50	1521	
245/45ZR20	28223023	8.0	7.5 - 9.0	28.7	9.50	723	8.7	10.5	31.2	51	1389	
245/40ZR20	28223002	8.5	8.0 - 9.5	27.7	9.69	747	8.7	10.5	30.6	51	1521	
255/35ZR20	28223004	9.0	8.5 - 10.0	27.2	10.08	762	9.2	10.5	28.8	50	1609	
275/35ZR20	28223005	9.5	9.0 - 11.0	27.7	10.64	747	9.8	10.5	31.0	50	1874	
235/30ZR20	28223007	8.5	8.5 - 8.5	25.7	9.33	803	8.7	10.5	25.3	51	1477	
255/30ZR20	28223014	9.0	8.5 - 9.5	26.2	10.06	788	9.5	10.5	27.5	51	1609	
275/30ZR20	28223006	9.5	9.0 - 10.0	26.7	10.53	776	9.8	10.5	29.5	50	1433	
UTQG 600 AA												
205/55R16	28222483	6.5	5.5 - 7.5	24.9	8.28	851	7.0	10.5	22.4	51	1477	
225/55R16	28222670	7.0	6.0 - 8.0	25.7	8.94	823	7.6	11.0	25.5	51	1521	
225/50R16	28222672	7.0	6.0 - 8.0	24.9	9.14	845	7.9	11.0	23.8	51	1477	
215/55R17	28222727	7.0	6.0 - 7.5	26.3	8.78	800	7.3	10.5	24.0	51	1709	
225/55R17	28222762	7.0	6.0 - 8.0	26.7	9.03	788	7.6	11.0	26.6	51	1565	
235/55R17	28222725	7.5	6.5 - 8.5	27.1	9.43	778	8.0	11.0	29.0	50	1609	
225/50R17	28222772	7.0	6.0 - 8.0	25.9	9.12	808	7.9	11.0	23.8	50	1433	
235/50R17	28222773	7.5	6.5 - 8.5	26.3	9.62	800	8.3	11.0	27.9	51	1477	
245/50R17	28222776	7.5	7.0 - 8.5	26.7	9.83	788	8.5	11.0	28.2	51	1709	
225/45R17	28222795	7.5	7.0 - 8.5	25.0	9.00	834	8.1	11.0	22.2	51	1709	
235/45R17	28222794	8.0	7.5 - 9.0	25.4	9.43	821	8.5	11.0	24.9	50	1356	
245/45R17	28222784	8.0	7.5 - 9.0	25.7	9.59	813	8.7	11.0	27.7	51	1521	
255/45R17	28222786	8.5	8.0 - 9.5	26.0	10.14	803	9.1	11.0	29.0	51	1653	
245/40R17	28222785	8.5	8.0 - 9.5	24.6	9.71	842	8.7	11.0	25.1	51	1764	
225/60R18	28222826	6.5	6.0 - 8.0	28.6	8.67	740	7.3	11.0	27.5	51	1819	
225/50R18	28222805	7.0	6.0 - 8.0	27.0	9.01	776	7.9	11.0	26.0	51	1565	
245/50R18	28222820	7.5	7.0 - 8.5	27.8	9.78	758	8.5	11.0	30.8	51	1609	
235/45R18	28222895	8.0	7.5 - 9.0	26.4	9.39	790	8.5	11.0	25.1	50	1433	
245/45R18	28222865	8.0	7.5 - 9.0	26.7	9.57	783	8.7	11.0	27.9	51	1764	
255/45R18	28222866	8.5	8.0 - 9.5	26.9	10.07	774	9.1	11.0	29.2	51	1609	
245/40R18	28222894	8.5	8.0 - 9.5	25.7	9.66	808	8.7	11.0	25.5	51	1356	



UTQG 300 AA A

Maximum Performance

- 5 Linear responsive ribs and 3-dimensional rounded blocks, enhances precise handling response.
- New silica compound and multi-angled grooves, improves grip in wet weather without compromising wear resistance.
- Phase-shifted random pitch variation nearly eliminates tread noise.
- Dual tread compound provides excellent handling critical for large diameter applications.
- High stiffness wide steel belts, means greater tread rigidity for outstanding grip and high-seed durability.
- High tension carcass & high turn-up, increases handling response and high speed stability.
- Reinforced steel bead filler, stiffens the sidewall and enables quick handling and response.

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Section Width	Overall Diameter	RPM	Tread Width	Tread Depth	Shipping Weight*	Max PSI (Cold)	Max Load (lbs)	PRICE	
225/60R16 98W	40695	6.5	6.0 - 8.0	8.9	26.6	785	7.4	10/32	25.1	51	1653	\$	
235/60R16 100W	40696	7.0	6.5 - 8.5	9.4	27.1	773	7.7	10/32	27.0	51	1764		
205/55R16 91W	40692	6.5	5.5 - 7.5	8.4	24.9	838	7.2	10/32	23.8	51	1356		
215/55R16 93W	40693	7.0	6.0 - 7.5	8.9	25.3	818	7.6	10/32	24.9	51	1433		
225/55R16 95W	40694	7.0	6.0 - 8.0	9.2	25.7	805	7.9	10/32	25.7	51	1521		
205/50R16 87W	40690	6.5	5.5 - 7.5	8.4	24.1	863	7.2	10/32	22.4	51	1201		
225/50R16 92W	40691	7	6.0 - 8.0	9.2	24.9	834	8.1	10/32	24.6	51	1389		
225/45R16 89Y	40689	7.5	7.0 - 8.5	8.8	24.0	870	8.1	10/32	23.0	51	1279		
215/40R16 86Y	40688	.XL	7.5	7.0 - 8.5	8.6	914	7.2	10/32	20.5	50	1168		
205/50R17 93Y	40712	.XL	6.5	5.5 - 7.5	8.2	829	7.2	10/32	22.9	50	1433		
215/45R17 87Y	40707		7.0	7.0 - 8.0	8.4	843	7.6	10/32	23.2	51	1201		
225/45R17 94Y	40708	.XL	7.5	7.0 - 8.5	8.9	832	8.1	10/32	24.5	50	1477		
235/45R17 94Y	40709		8.0	7.5 - 9.0	9.3	819	8.5	10/32	25.1	51	1477		
245/45R17 95Y	40710		8.0	7.5 - 9.0	9.6	807	8.3	10/32	26.0	51	1521		
255/45R17 98Y	40711		8.5	8.0 - 9.5	10.0	799	9.5	10/32	27.7	51	1653		
205/40R17 84Z	40700	.XL	7.5	7.0 - 8.0	8.4	884	7.2	10/32	20.3	50	1102		
215/40R17 87Z	40701	.XL	7.5	7.0 - 8.5	8.4	874	7.2	10/32	21.0	50	1201		
235/40R17 90Y	40702		8.5	8.0 - 9.5	9.4	851	8.2	10/32	24.8	51	1323		
245/40R17 95Y	40703	.XL	8.5	8.0 - 9.5	9.8	842	8.8	10/32	26.0	50	1521		
255/40R17 94Y	40704		9.0	8.5 - 10.0	10.3	831	9.1	10/32	26.7	51	1477		
265/40R17 96Y	40705		9.5	9.0 - 10.5	10.7	821	9.3	10/32	28.6	51	1565		
275/40R17 98Y	40706		9.5	9.0 - 11.0	10.9	815	9.7	10/32	29.9	51	1653		
215/35R17 83Z	40697	.XL	7.5	7.0 - 8.5	8.4	22.9	907	7.3	10/32	19.6	50	1074	
225/35R17 86Y	40698	.XL	8.0	7.5 - 9.0	9.0	23.2	903	8.1	10/32	18.9	50	1168	
245/35R17 87Y	40699		8.5	8.0 - 9.5	9.6	23.8	872	8.8	10/32	24.0	51	1201	
225/45R18 95Y	40726	.XL	7.5	7.0 - 8.5	8.9	26.0	799	8.1	10/32	25.3	50	1521	
245/45R18 100Y	40727	.XL	8.0	7.5 - 9.0	9.6	26.7	777	8.5	10/32	28.6	50	1764	
255/45R18 103Y	40728	.XL	8.5	8.0 - 9.5	10.1	27.1	766	8.9	10/32	28.6	50	1929	
215/40R18 89Y	40721	.XL	7.5	7.0 - 8.5	8.6	24.8	836	7.2	10/32	22.5	50	1279	
225/40R18 92Y	40722	.XL	8.0	7.5 - 9.0	9.1	25.0	830	8.1	10/32	25.0	50	1389	
235/40R18 95Y	40723	.XL	8.5	8.0 - 9.5	9.6	25.3	821	8.5	10/32	26.2	50	1521	
245/40R18 97Y	40724	.XL	8.5	8.0 - 9.5	9.5	25.7	807	8.3	10/32	26.4	50	1609	
255/40R18 99Y	68469		9	8.5-10.0	10.2	26	800	8.9	10/32	26.4	50	1709	
275/40R18 99Y	40725		9.5	9.0 - 11.0	10.8	26.6	781	9.8	10/32	30.1	51	1709	
215/35R18 84Z	40714	.XL	7.5	7.0 - 8.5	8.5	23.9	870	7.7	10/32	21.6	50	1102	
225/35R18 87Y	40715	.XL	8.0	7.5 - 9.0	9.0	24.2	858	8.1	10/32	23.6	50	1201	
245/35R18 88Y	40716		8.5	8.0 - 9.5	9.6	24.8	838	8.8	10/32	25.5	51	1235	
255/35R18 94Y	40717	.XL	9.0	8.5 - 10.0	10.1	25.0	832	9.1	10/32	25.8	50	1477	
265/35R18 97Y	40718	.XL	9.5	9.0 - 10.5	10.6	25.3	821	9.6	10/32	27.1	50	1609	
275/35R18 95Y	40719		9.5	9.0 - 11.0	10.9	25.6	809	10.0	10/32	29.0	51	1521	
285/35R18 97Y	40720		10.0	9.5 - 11.0	11.2	25.9	802	9.7	10/32	31.3	51	1609	
295/30R18 94Y	40713		10.5	10.0 - 11.0	11.9	25.0	833	10.9	10/32	28.7	51	1447	
245/45R19 98Y	40741		8.0	7.5 - 9.0	9.6	27.7	750	8.5	10/32	29.7	51	1653	
225/40ZR19 93Y	68472		8	7.5-9.0	9	26.2	790	8.1	10/32	25.1	50	1433	
245/40R19 98Y	40738	.XL	8.5	8.0 - 9.5	9.8	26.7	777	8.5	10/32	28.3	50	1653	
255/40R19 100Y	40739	.XL	9.0	8.5 - 10.0	10.2	27.1	766	8.9	10/32	28.4	50	1764	
275/40R19 101Y	40740		9.5	9.0 - 11.0	10.8	27.7	750	9.6	10/32	31.2	51	1819	
215/35R19 85Z	40732	.XL	7.5	7.0 - 8.5	8.5	25.0	831	7.7	10/32	23.0	50	1135	
225/35R19 88Y	40733	.XL	8.0	7.5 - 9.0	9.0	25.2	823	8.1	10/32	23.7	50	1235	
235/35R19 91Y	40734	.XL	8.5	8.0 - 9.5	9.6	25.5	815	8.7	10/32	26.3	50	1356	
245/35R19 93Y	40735	.XL	8.5	8.0 - 9.5	9.7	25.8	805	9.1	10/32	27.3	50	1433	
255/35ZR19 96Y	68470		9	8.5-10.0	10	26.1	793	8.9	10/32	25.7	50	1565	
275/35R19 96Y	40736		9.5	9.0 - 11.0	10.7	26.6	782	9.9	10/32	30.6	51	1565	
285/35R19 99Y	40737		10.0	9.5 - 11.0	11.3	26.9	774	9.8	10/32	30.2	51	1709	
265/30R19 93Y	40730	.XL	9.5	9.0 - 10.0	10.4	25.4	819	9.3	10/32	26.5	50	1433	
275/30R19 96Y	40731	.XL	9.5	9.0 - 10.0	10.5	25.6	811	9.6	10/32	27.9	50	1565	
315/25R19 94Y	40729		11.5	11.0 - 12.0	12.8	25.2	823	11.7	10/32	30.2	51	1477	
245/45R20 99W	61613		8	7.5-9.0	9.6	28.7	723	8.5	10/32	29.5	51	1709	
255/45R20 105Y	40680	.XL	8.5	8.0 - 9.5	10.0	29.0	712	9.1	10/32	31.9	50	2039	
245/40R20 99Y	40679	.XL	8.5	8.0 - 9.5	9.8	27.7	750	8.5	10/32	28.2	50	1709	
225/35R20 90Y	61612		8.0	7.5-9.0	9.0	26.2	788	8.1	10/32	23.5	50	1323	
245/35R20 95Y	40676	.XL	8.5	8.0 - 9.5	9.6	26.7	777	8.8	10/32	27.7	50	1521	
255/35R20 97Y	40677	.XL	9.0	8.5 - 10.0	10.2	27.0	768	8.8	10/32	28.1	50	1609	
275/35R20 102Y	40678	.XL	9.5	9.0 - 11.0	10.9	27.6	750	10.0	10/32	31.0	50	1874	
225/30R20 85Y	40744	.XL	8.0	8.0	8.9	25.3	821	8.0	10/32	24.9	50	1135	
235/30R20 88Y	40745	.XL	8.5	8.5	9.5	25.6	811	8.7	10/32	26.3	50	1235	
245/30R20 90Y	40746	.XL	8.5	8.0 - 9.0	9.8	25.8	805	8.9	10/32	26.3	50	1323	
255/30R20 92Y	40747	.XL	9.0	8.5 - 9.5	10.2	26.0	798	9.3	10/32	28.5	50	1389	
275/30R20 97Y	40748	.XL	9.5	9.0 - 10.0	10.5	26.6	781	9.6	10/32	28.5	50	1609	
285/30R20 99Y	40749	.XL	10.0	9.5 - 10.5	11.4	26.7	778	10.4	10/32	30.2	50	1709	
285/25R20 93Y	40742	.XL	10.5	10.5	11.3	25.6	811	10.3	10/32	29.1	50	1433	
305/25R20 97Y	40743	.XL	11.0	10.5 - 11.5	12.3	26.0	798	11.3	10/32	30.9	50	1609	
255/35R21 98Y	40683	.XL	9.0	8.5 - 10.0	10.2	28.0	741	8.8	10/32	29.1	50	1653	
255/30R21 93Y	40682	.XL	9.0	8.5 - 9.5	10.2	27.0	769	9.0	10/32	30.0	50	1433	
295/25R21 96Y	40681	.XL	10.5	10.0 - 11.0	11.9	26.8	775	10.9	10/32	31.7	50	1565	
255/35R22 99W	65298		9	8.5-10	9.9	29.2	707	8.8	10/32	31.5	50	1709	
285/35ZR22 106W	68627		10	9.5-11.0	11.2	30	690	10.3	10/32	35	50	2094	
245/30R22 92Y	40686	.XL	8.5	8.0 - 9.0	9.8	27.8	747	8.8	10/32	28.7	50	1389	
255/30R22 95Y	40687	.XL	9.0	8.5 - 9.5	10.2	28.0	738	9.3	10/32	28.5	50	1521	
265/30R22 97Y	57519		9.5	9.0-10.0	10.6	25.4	808	9.9	10/32	31.8	50	1609	
285/25R22 95Y	40684	.XL	10.5	10.5	11.3	27.6	752	10.2	10/32	33.2	50	1521	
295/25R22 97Y	40685	.XL	10.5	10.0 - 11.0	11.9	27.8	748	10.9	10/32	34.0	50	1609	
235/30R22 90Y RF	65297		8.5	8.5	9.5	27.6	747	8.7	10/32	27.1	50	1323	
NEW 275/25R24 96W RF	71821		10.0	10.0	10.9	29.6			10	33.2	50	1565	
NEW 255/30R24 97W RF	71822		9.0	8.5-9.5	10.0	30.2	681		10	32.6	50	1609	
NEW 275/30R24 101W RF	71823		9.5		9.6	30.6			10	34.1	50	1819	

FALKEN AZENIS SPORT RT-615K

Race Bred UHP Radial



UTQG 200 A A

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
195/60R14 86H	.71735	.6.0	5.5 - 7.0	23.2	.7.9	.900	.6.6	.8	18.5	.51	1168	\$
205/50R15 89W *RD	.71736	.6.5	5.5 - 7.5	23.2	.8.2	.895	.7.6	.8	21.2	.50	1279	
225/50R16 92W	.71737	.7.0	6.0 - 8.0	24.9	.9.1	.881	.8.2	.8	24.6	.51	1389	
215/45R16 86W	.71738	.7.0	7.0 - 8.0	23.6	.8.7	.768	.8.0	.8	21.6	.51	1168	
205/40R16 83W *RD	.71739	.7.5	7.0 - 8.0	22.5	.8.5	.911	.7.2	.8	18.3	.50	1074	
215/45R17 87W	.71740	.7.0	7.0 - 8.0	24.6	.8.3	.871	.8.0	.8	22.9	.51	1201	
225/45R17 94W *RD	.71741	.7.5	7.0 - 8.5	25.0	.8.9	.822	.8.3	.8	24.9	.50	1477	
205/40R17 84W *RD	.71743	.7.5	7.0 - 8.0	23.4	.8.5	.875	.7.2	.8	19.3	.50	1102	
215/40R17 87W *RD	.71744	.7.5	7.0 - 8.5	23.9	.8.7	.861	.7.4	.8	20.4	.50	1202	
235/40R17 90W	.71745	.8.5	8.0 - 9.5	24.4	.9.4	.836	.8.7	.8	23.8	.51	1323	
255/40R17 94W	.71746	.9.0	8.5 - 10.0	25.0	.10.3	.825	.9.4	.8	26.5	.51	1477	
275/40R17 98W	.71747	.9.5	9.0 - 11.0	25.6	.10.8	.806	.10.0	.8	28.3	.51	1653	
225/40R18 92W *RD	.71748	.8.0	7.5 - 9.0	25.1	.9.3	.818	.8.3	.8	24.0	.50	1389	
235/40R18 95W *RD	.71749	.8.5	8.0 - 9.5	25.5	.9.6	.806	.8.7	.8	24.3	.50	1521	
245/40R18 97W *RD	.71750	.8.5	8.0 - 9.5	25.6	.9.8	.803	.9.1	.8	26.5	.50	1609	
255/40R18 95W	.71751	.9.0	8.5 - 10.0	25.9	.10.3	.794	.9.4	.8	27.8	.51	1521	
295/40R18 103W	.71752	.10.5	10.0 - 11.5	27.2	.11.8	.763	.10.9	.8	32.8	.51	1929	
265/35R18 97W *RD	.71753	.9.5	9.0 - 10.5	25.4	.10.7	.852	.10.0	.8	28.2	.50	1609	
275/35R18 95W	.71754	.9.5	9.0 - 11.0	25.6	.10.8	.803	.10.0	.8	26.9	.51	1521	
315/30R18 98W	.71755	.11.0	10.5 - 11.5	25.5	.12.6	.813	.11.7	.8	31.9	.51	1653	

*RD = REINFORCED

FALKEN ZE-912 CUV

Ultra-High Performance Radial



Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
235/65R17 108V XL	.73398			29.1	.10			10/32	31.5	.50	2205	\$
255/60R17 106H	.72671			29	.10.1			10/32	34.3	.51	2094	
P255/65R18 109H	.73397			.31	.10			10/32	37.4	.51	2271	
235/60R18 107V XL	.72672			29.1	.9.4			10/32	33	.50	2149	
245/60R18 105H	.72669			29.6	.9.6			10/32	34.1	.51	2039	
265/60R18 110V	.73396			30.5	.11			10/32	36.7	.51	2337	
255/60R18 112V XL	.72670			.30	.10.2			10/32	35.9	.50	2469	
235/55R18 100V	.72667			28.2	.9.6			10/32	30.4	.51	1764	
255/55R18 109V XL	.72668			.29	.10.4			10/32	34.8	.50	2271	
P255/60R19 108H	.73399											
245/55R19 103H	.73194	.7.5		29.8	.10			10/32	.51	.51	1929	
235/55R19 105W XL	.73193	.7.5		29.2	.9.7			10/32	.33	.50	2039	
P245/50R20 102V	.73195	.7.5		29.7	.9.7			10/32	.33	.51	1874	

COMPTON

1714 Anderson Ave.
Compton, CA 90220
Local 310-631-8200 • Fax 310-631-2503
Toll Free: 1-800-962-5222



BAKERSFIELD

7600 District Blvd., Suite B
Bakersfield, CA 93313
Local 661-831-5600 • Fax 661-831-5641
Toll Free: 1-888-414-8473

HOUSTON

3635 Willowbend Blvd.
Houston, TX 77054
Local 713-660-6600 • Fax 713-660-9633
Toll Free: 1-800-711-3919

MIAMI

9800 NW 100 Road
Medley, FL 33178
Local 305-887-8876 • Fax 305-470-9967
Toll Free: 1-888-833-3953

PORTLAND

7515 N. Leadbetter Dr.
Portland, Oregon 97203
Local 503-283-0416 • Fax 503-240-3342
Toll Free: 1-866-977-8473

UNION CITY

33375 Central Ave.
Union City, CA 94587
Local 510-489-7600 • Fax 510-489-0494
Toll Free: 1-800-447-8473

SAN ANTONIO

4530 Tejasco Dr.
San Antonio, TX 78218
Local 210-212-8866 • Fax 210-212-8815
Toll Free: 1-800-666-8840

TAMPA

9110 King Palm Drive, Suite 106
Tampa FL 33619
Local 813-626-0866 • Fax 813-626-0977
Toll Free: 1-800-483-2099

CHICAGO

3710 N River Road, Suite 400
Franklin Park, IL 60131
Local 708-450-7000 • Fax 708-450-7001
Toll Free: 1-866-220-8439

PHOENIX

601 South 65th Avenue, Suite 6
Phoenix, AZ 85043
Local 623-474-4660 • Fax 623-474-4661
Toll Free: 1-855-825-8473

DALLAS

9500 Royal Lane, Suite 160
Irving, Texas 75063
Local 972-484-6900 • Fax 972-484-7742
Toll Free: 1-888-455-2234

ORLANDO

2222 Diversified Way
Orlando, FL 32804
Local 407-218-4600 • Fax 407-218-4601
Toll Free: 1-800-903-0014

OHIO/MICHIGAN

14801 TR 212
Findlay, OH 45840
Local 419-425-6508 • Fax 419-425-6514
Toll Free: 1-877-309-1972



FALKEN

91

FALKEN ZE-912

Ultra-High Performance Radial



Mileage Warranty
60/65 -
65,000 UTQG 480 A A
UHP -
40,000 UTQG 360 AA A

Hybrid-Asymmetric Pattern Design
 Provides authentic High-Performance grip and genuine Touring confidence. Optimized interior an exterior pattern designs ensure that dry performance, stability, and all-season grip are available whenever and wherever you need it.

Infinite Sype Sequence
 Incorporates heavy full-depth sypes throughout the entire tread platform. Countless biting edges dramatically increase traction in winter months while improving overall grip when nature is at its worst. Come rain, shine, sleet, or snow the ZE-912 will deliver you in confidence.

R.W.I. (Rotation Wear Indicators)
 Provide the driver with visual cues to help maximize tire life and overall value. Consistent rotations and inflation pressure management are paramount when safety and confidence are top of mind.

Quad High-Volume Circumferential Grooves
 Deliver increased hydroplane resistance for maximum wet stability. Standing water and highway speeds are no match for the ZE-912.

High Angle Variable Cross Grooves
 Increase tread stability while effectively evacuating water away from contact area. The ZE-912 embodies the essence of performance during each of the four seasons.

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
360-AA-A												
195/55R15 85V	54377	6.0	5.5 - 7	23.4	8.0	902	6.9	10/32	20.4	51.0	1135	.. \$
205/55R15 88V	54380	6.5	5.5 - 7.5	23.9	8.5	883	7.2	10/32	21.7	51.0	1235	
195/50R15 82H	54375	6.0	5.5 - 7	22.7	7.9	925	6.9	10/32	19.2	51.0	1047	
205/50R15 86H	54376	6.5	5.5 - 7.5	23.1	8.4	911	7.2	10/32	20.4	51.0	1168	
225/50R15 91V	54381	7.0	6 - 8	23.9	9.0	880	7.9	10/32	21.8	51.0	1356	
195/55R16 87V	54392	6.0	5.5 - 7	24.5	7.9	860	6.9	10/32	20.4	51.0	1201	
205/55R16 91V	54359	6.5	5.5 - 7.5	25.0	8.4	842	7.2	10/32	22.8	51.0	1356	
215/55R16 97V	54388	7.0	6 - 7.5	25.4	10.9	834	7.6	10/32	25.7	50.0	1609	
225/55R16 95V	54387	7.0	6 - 8	25.7	9.3	821	7.9	10/32	26.1	51.0	1521	
195/50R16 84V	54391	6.0	5.5 - 7	23.8	7.7	883	6.9	10/32	20.2	51.0	1102	
205/50R16 87V	54382	6.5	5.5 - 7.5	24.1	8.4	874	7.2	10/32	21.6	51.0	1201	
215/50R16 90V	54393	7.0	6 - 7.5	24.6	8.8	856	7.6	10/32	22.7	51.0	1323	
225/50R16 92H	54385	7.0	6 - 8	25.0	9.1	842	7.9	10/32	24.9	51.0	1389	
225/50R16 96V	54386	7.0	6 - 8	25.0	9.1	842	7.9	10/32	25.0	50.0	1565	
245/50R16 97H	54406	7.5	7 - 8.5	25.6	9.8	823	8.5	10/32	26.9	51.0	1609	
245/50R16 97W	54407	7.5	7 - 8.5	25.6	9.8	823	8.5	10/32	24.4	51.0	1609	
205/45R16 87V	54390	7.0	6.5 - 7.5	23.3	8.0	892	7.3	10/32	20.1	50.0	1201	
205/40R16 83H	54389	7.5	7 - 8	22.4	8.4	928	7.3	10/32	18.4	50.0	1074	
215/55R17 94W	54414	7.0	6 - 7.5	26.3	8.9	800	7.6	10/32	24.8	51.0	1477	
225/55R17 101W	54372	7.0	6 - 8	27.0	9.1	781	7.9	10/32	28.0	50.0	1819	
235/55R17 99W	54410	7.5	6.5 - 8.5	27.1	9.5	778	8.3	10/32	29.2	51.0	1709	
205/50R17 93W	54413	6.5	5.5 - 7.5	25.1	8.3	837	7.2	10/32	22.8	50.0	1433	
215/50R17 91V	54362	7.0	6 - 7.5	25.7	8.7	818	7.6	10/32	23.2	51.0	1356	
225/50R17 94V	54365	7.0	6 - 8	26.1	8.9	805	7.9	10/32	24.9	51.0	1477	
235/50R17 96W	54415	7.5	6.5 - 8.5	26.3	9.4	803	8.3	10/32	26.1	51.0	1565	
205/45R17 88W	54373	7.0	6.5 - 7.5	24.6	8.1	848	7.3	10/32	22.1	50.0	1102	
215/45R17 91W	54363	7.0	7 - 8	24.8	8.3	837	7.7	10/32	23.4	50.0	1356	
225/45R17 94W	54364	7.5	7 - 8.5	25.2	8.8	829	8.1	10/32	24.8	50.0	1477	
235/45R17 94W	54367	8.0	7.5 - 9	25.6	9.4	818	8.5	10/32	24.0	51.0	1477	
245/45R17 95W	54366	8.0	7.5 - 9	25.9	9.4	805	8.7	10/32	25.9	51.0	1521	
205/40R17 84W	54360	7.5	7 - 8	23.6	8.3	880	7.3	10/32	22.0	50.0	1102	
215/40R17 87W	54370	7.5	7 - 8.5	24.1	8.5	862	7.7	10/32	22.3	50.0	1201	
245/40R17 91W	54418	8.5	8 - 9.5	24.8	9.7	840	8.7	10/32	23.7	51.0	1356	
255/40R17 94W	54420	9.0	8.5 - 10	25.0	10.2	840	9.1	10/32	25.3	51.0	1477	
NEW 215/55R18 95H	68489	7.0	6.0-7.5	27.5	8.7	767	7.6	10/32	27.1	51	1521	
NEW 225/55R18 98H	68491	7.0	6.0-8.0	27.9	9	755	7.9	10/32	29.7	51	1653	
235/50R18 101W	54419	7.5	6.5 - 8.5	27.4	9.5	769	8.3	10/32	28.7	50.0	1819	
NEW 225/50ZR18 95W	68490	7.0	6.0-8.0	27.1	9	776	7.9	10/32	27.3	51	1521	
225/45R18 91W	54374	7.5	7 - 8.5	26.3	8.7	790	8.1	10/32	24.1	51.0	1356	
NEW 235/45ZR18 94W	68493	8	7.5-9.0	26.6	9.2	783	8.5	10/32	27.7	51	1477	
245/45R18 100W	54416	8.0	7.5 - 9	26.8	9.5	778	8.7	10/32	28.8	50.0	1764	
215/40R18 89W	54409	7.5	7 - 8.5	24.8	8.5	834	7.7	10/32	21.7	50.0	1279	
225/40R18 92W	54361	8.0	7.5 - 9	25.2	8.9	823	8.1	10/32	24.9	50.0	1389	
235/40R18 95W	54369	8.5	8 - 9.5	25.5	9.5	816	8.5	10/32	26.8	50.0	1521	
245/40R18 97W	54368	8.5	8 - 9.5	25.9	9.6	803	8.7	10/32	27.5	50.0	1609	
215/35R18 84W	54371	7.5	7 - 8.5	24.0	8.5	860	7.7	10/32	22.7	50.0	1102	
NEW 235/35ZR18 90W	68492	8.5	8.0-9.5	24.6	9.5	842	8.5	10/32	24.6	50	1019	
265/35R18 97W	54417	9.5	9 - 10.5	25.3	10.5	821	9.5	10/32	28.0	50.0	1609	
480-AA-A												
185/65R14 86H	54395	5.5	5 - 6.5	23.4	7.5	905	6.1	10/32	17.9	51.0	1168	
195/65R14 89H	54397	6.0	5.5 - 7	24.1	8.0	883	6.4	10/32	19.6	51.0	1279	
185/60R14 82H	54396	5.5	5 - 6.5	22.7	7.4	931	6.1	10/32	17.4	51.0	1047	
195/60R14 86H	54394	6.0	5.5 - 7	23.3	7.9	908	6.4	10/32	18.4	51.0	1168	
NEW 175/65R15 84H	68486	5	5.0-6.0	24.2	6.8	874	5.7	10/32	18.5	51	1102	
185/65R15 88H	54378	5.5	5 - 6.5	24.5	7.3	865	6.1	10/32	18.4	51.0	1235	
195/65R15 91H	54358	6.0	5.5 - 7	25.0	8.0	848	6.4	10/32	20.5	51.0	1356	
205/65R15 94H	54398	6.0	5.5 - 7.5	25.4	8.3	834	6.7	10/32	22.1	51.0	1477	
205/65R15 94V	54399	6.0	5.5 - 7.5	25.4	8.3	834	6.7	10/32	22.2	51.0	1477	
215/65R15 96H	54401	6.5	6 - 7.5	26.0	8.8	816	7.0	10/32	23.4	51.0	1565	
185/60R15 84H	54379	5.5	5 - 6.5	23.9	7.2	883	6.1	10/32	17.5	51.0	1102	
195/60R15 88H	54356	6.0	5.5 - 7	24.3	7.9	871	6.4	10/32	20.0	51.0	1235	
205/60R15 91H	54357	6.0	5.5 - 7.5	24.7	8.1	856	6.7	10/32	20.2	51.0	1356	
215/60R15 94H	54400	6.5	6 - 7.5	25.2	8.7	842	7.0	10/32	22.1	51.0	1477	
225/60R15 96H	54402	6.5	6 - 8	25.7	8.8	826	7.3	10/32	24.0	51.0	1565	
205/65R16 95V	54408	6.0	5.5-7.5	26.5	8.2	800	6.7	10/32	24.0	51.0	1521	
NEW 215/65R16 98H	59691	6.5	6.0-8.0	27.0	8.7	786	7.0	10/32	26.8	51.0	1653	
NEW 225/65R16 100H	68487	6.5	6.0-8.0	27.4	9	774	7.3	10/32	29.3	51	1764	
NEW 235/65R16 103H	61608	7.0	6.5-8.5	27.0	9.4	783	7.6	10/32	29.1	51.0	1764	
205/60R16 92H	54383	6.0	5.5 - 7.5	25.6	8.2	823	6.7	10/32	23.4	51.0	1389	
205/60R16 92V	54384	6.0	5.5 - 7.5	25.6	8.2	823	6.7	10/32	23.4	51.0	1389	
215/60R16 99H	54404	6.5	6 - 7.5	26.2	9.0	808	7.0	10/32	25.0	50.0	1709	
225/60R16 98H	54403	6.5	6 - 8	26.5	9.0	798	7.3	10/32	26.2	51.0	1653	
235/60R16 100W	54405	7.0	6.5 - 8.5	27.0	9.4	783	7.6	10/32	29.1	51.0	1764	
NEW 215/60R17 96H	61609	6.5	6.0-7.5	27.2	8.6	776	7.0	10/32	26.6	51.0	1565	
NEW 225/60R17 99H	59692	6.5	6.0-8.0	27.7	8.8	764	7.3	10/32	29.5	51.0	1709	
NEW 235/60R17 102H	61610	7.0	6.5-8.5	28.1	9.4	753	7.6	10/32	29.5	51.0	1874	
215/65R17 98H	54411	6.5	6 - 7.5	28.0	8.7	755	7.0	10/32	25.2	51.0	1653	
NEW 225/65R17 102H	68488	6.5	6.0-8.0	28.5	9	745	7.3	10/32	29.9	51	1874	
NEW 215/45R18 93W	59693	7	7.0-8.0	25.7	8.3	808	7.7	10/32	25.7	50	1433	
225/60R18 99H	54412	6.5	6 - 8	28.7	8.8	736	7.3	10/32	29.1	51.0	1709	
NEW 235/65R18 106H	61611	7	6.5-8.5	30.1	9.4	705	7.6	10/32	29.7	51	2094	

SINCERA TOURING SN211

Ultra-High Performance Radial



NEW

UTQG 720 A B

**80,000 Mile
Tread Life Warranty**

Four Optimized Circumferential Grooves

Maximize hydroplane resistance by channeling water away from the contact patch in wet weather conditions.

Stylish Serrated Sidewall Design And Square Shoulder Profile

Compliments the overall look of coupes, sedans and wagons giving them a premium and sport inspired appearance during cornering.

Variable Sipe Depth Design

Helps reduce tread block squirm and promote long lasting wear uniformity.

Treadwear Indicators

Allow easy monitoring of tire wear and assists in prompting scheduled tire rotations.

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
P225/60R18 99T	70835	6.5	6.0-8.0	28.7	8.8	736	7.3	12	29.3	44	1709	\$
P225/55R18 97T	70836	7.0	6.0-8.0	27.8	9.1	758	7.9	12	29.5	44	1609	
P215/60R17 95T	70837	6.5	6.0-7.5	27.2	8.4	774	7.0	12	27.3	44	1521	
P215/65R17 98T	70838	6.5	6.5-7.5	28.0	8.6	755	7.0	12	28.6	44	1653	
P225/55R17 91T	70839	7.0	6.0-8.0	26.8	9.1	788	7.9	12	28.2	44	1521	
P225/60R17 98T	70840	6.5	6.0-8.0	27.7	8.9	764	7.3	12	29.0	44	1653	
P235/50R17 95T	70841	7.5	6.5-8.5	26.4	9.5	800	8.3	12	27.5	44	1521	
P235/55R17 98T	70842	7.5	6.5-8.5	27.1	9.7	781	8.3	12	29.3	44	1653	
P235/60R17 100T	70843	7.0	6.5-8.5	28.1	9.4	751	7.6	12	31.5	44	1764	
P215/65R16 98T	70844	6.5	6.0-7.5	27.0	8.7	783	7.0	12	26.2	44	1653	
P205/55R16 89T	70845	6.5	6.0-8.0	24.8	8.4	851	7.2	12	23.1	44	1279	
P205/60R16 91T	70846	6.0	5.5-7.5	25.7	8.2	821	6.7	12	22.7	44	1356	
P205/65R16 94T	70847	6.0	5.5-7.5	26.5	8.3	800	6.7	12	24.0	44	1477	
P215/55R16 91T	70848	7.0	6.0-7.5	25.1	9.0	840	7.6	12	24.0	44	1356	
P215/60R16 94T	70849	6.5	6.0-7.5	26.1	8.7	811	7.0	12	24.4	44	1477	
P215/70R16 99T	70850	6.5	5.5-7.0	27.9	8.7	755	6.9	12	28.2	44	1709	
P225/55R16 94T	70851	7.0	6.0-8.0	25.6	9.2	823	7.9	12	26.2	44	1477	
P225/60R16 97T	70852	6.5	6.0-8.0	26.6	8.9	795	7.3	12	26.2	44	1609	
P225/70R16 101T	70853	6.5	6.0-7.5	28.4	9.1	740	7.1	12	29.9	44	1819	
P235/60R16 99T	70854	7.0	6.5-8.5	27.0	9.4	783	7.6	12	29.3	44	1709	
P235/65R16 101T	70855	7.0	6.5-8.5	28.0	9.6	760	7.6	12	29.3	44	1819	
P185/60R15 84T	70856	5.5	5.0-6.5	23.7	7.5	889	6.1	12	19.4	44	1102	
P185/65R15 86T	70857	5.5	5.0-6.5	24.5	7.5	865	6.1	12	19.4	44	1168	
P195/60R15 87T	70858	6.0	5.5-7.0	24.1	8.0	874	6.4	12	20.0	44	1190	
P195/65R15 89T	70859	6.0	5.5-7.0	24.9	8.0	848	6.4	12	21.1	44	1279	
P205/60R15 90T	70860	6.0	5.5-7.5	24.6	8.2	860	6.7	12	22.2	44	1301	
P205/65R15 92T	70861	6.0	5.5-7.5	25.5	8.3	832	6.7	12	22.7	44	1400	
P205/70R15 95T	70862	6.0	5.0-7.0	26.4	8.3	798	6.7	12	24.9	44	1499	
P215/60R15 93T	70863	6.5	6.0-7.5	25.1	8.6	845	7.0	12	23.3	44	1411	
P215/65R15 95T	70864	6.5	6.0-7.5	25.9	8.8	818	6.8	12	24.0	44	1510	
P215/70R15 97T	70865	6.5	5.5-7.0	27.1	8.9	778	7.0	12	26.4	44	1620	
P225/60R15 96T	70866	6.5	6.0-8.0	25.5	9.0	834	7.3	12	24.4	44	1521	
P175/65R14 81T	70867	7.0	6.0-8.0	22.9	7.0	921	5.7	12	17.6	44	1019	
P185/60R14 82T	70868	5.5	5.0-6.5	22.8	7.4	931	6.1	12	17.8	44	1047	
P185/65R14 85T	70869	5.5	5.0-6.5	23.5	7.4	905	5.7	12	18.0	44	1124	
P185/70R14 87T	70870	5.5	4.5-6.0	24.2	7.6	868	6.0	12	19.1	44	1201	
P195/60R14 85T	70871	6.0	5.5-7.0	23.0	7.9	918	6.4	12	19.4	44	1135	
P195/65R14 88T	70872	6.0	5.5-7.0	23.9	8.1	889	6.4	12	20.2	44	1235	
P195/70R14 90T	70873	6.0	5.0-6.5	24.8	8.0	848	6.5	12	20.9	44	1312	
P205/70R14 93T	70874	6.0	5.0-7.0	25.4	8.4	832	6.7	12	24.2	44	1433	

FALKEN ZIEX ZE-502

Performance Light Truck/SUV Radial



- M + S rated, directional tread design and five circumferential grooves.
- Infinite pitch shoulder design for flat, even tread wear, notice reduced tire noise, and a smooth, comfortable ride.
- Improved rim protection ridge that helps shield custom wheels.
- Twin high mass center ribs have been incorporated providing continuous rubber-to-road contact for incredible levels of dry traction.

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
UTQG 300 A A												
195/55R15 84V	20395	6	5.5-7.0	23.5	7.8	895	7	10	19.1	44	1102	\$
205/55R15 87V	20396	6.5	5.5-7.5	23.9	8.5	883	7.6	10	20.2	44	1201	
205/50R16 87V	20406	6.5	5.5-7.5	24.2	8.2	871	7.6	10	20.9	44	1201	
205/55R16 89V	20402	6.5	5.5-7.5	25	8.4	842	7.6	10	21.1	44	1279	
215/55R16 93V	20403	7	6.0-7.5	25.4	8.9	832	8	10	23.3	44	1433	
225/55R16 94V	20404	7	6.0-8.0	25.7	9.4	821	8.3	10	24.2	44	1477	
235/55R16 96V	20405	7.5	6.5-8.5	26.2	9.7	805	8.7	10	26.4	44	1565	
205/40ZR17 80	20425	7.5	7.0-8.0	23.6	8.5	880	7.5	10	19.8	44	992	
205/45ZR17 84	20416	7	6.5-7.5	24.2	8.1	856	7.5	10	19.8	44	1102	
205/50ZR17 93W RD	68188	6.5	5.5-7.5	25.2	8.2	840	7.2	10	24.2	50	1433	
215/40ZR17 83	20427	7.5	7.0-8.5	23.9	5.1	868	8	10	21.3	44	1074	
215/45ZR17 87	20418	7	7.0-8.0	24.8	8.6	840	8	10	21.3	44	1201	
225/45ZR17 94W RD	68187	7.5	7.0-8.5	25	8.7	832	7.9	11	24.2	50	1477	
215/50R17 91V	20415	7	6.0-7.5	25.4	8.7	826	8	10	22	44	1356	
215/55R17 94V	68190	7	6.0-7.5	26.4	8.8	800	7.3	10	24.2	51	1477	
225/50R17 94V	68189	7	6.0-8.0	25.9	9	811	7.6	11	24.2	51	1477	
225/55R17 97V	68191	7	6.0-8.0	26.8	9.1	788	7.8	11	28.6	51	1609	
235/45ZR17 94	20420	8	7.5-9.0	25.3	9.4	823	8.6	10	23.5	44	1433	
245/45ZR17 95	20422	8	7.5-9.0	25.7	9.6	811	9.1	10	25.3	44	1521	
P275/40ZR17 98	20429	9.5	9.0-10.5	25.7	11	813	10.2	11	28.2	44	1433	
215/35ZR18 80	20430	7.5	7.0-8.5	23.9	8.7	868	7.6	10	19.4	50	1102	
225/40ZR18 92W RD	68193	8	7.5-9.0	25.3	9	821	7.9	11	24.2	50	1389	
P235/55R18 99V	68196	7.5	6.5-8.5	28.2	9.6	747	8.1	11	30.8	51	1709	
245/40ZR18 97W RD	68194	8.5	8.0-9.5	25.9	9.2	803	8.5	11	26.4	50	1609	
245/45ZR18 100W RD	68195	8	7.5-9.0	26.7	9.4	778	8.4	11	28.6	50	1764	
UTQG 340 A A												
195/50R15 82H	20397	6	5.5-7.0	22.8	7.8	921	7	10	17.6	44	1047	
205/50R15 86H	20399	6.5	5.5-7.5	23.2	8.4	908	7.6	10	18.5	44	1168	
225/50R16 92H	20407	7	6.0-8.0	25	8.9	842	8.3	10	22.9	44	1389	
P245/50R16 96H	20409	7.5	7.0-8.5	25.7	10	823	9.1	10	26.4	44	1576	
205/40R16 83H	20414	7.5	7.0-8.0	22.4	8.4	928	7.5	10	18.5	50	1074	
235/55R17 99H	68192	7.5	6.5-8.5	27.2	9.6	774	8.1	11	28.6	51	1709	
P225/60R18 99H	68197	6.5	6.0-8.0	28.6	8.8	740	7.3	11	28.6	51	1709	

FALKEN ZIEX S/TZ 01 Performance Light Truck/SUV Radial



UTQG 420 AA
50,000 Limited
Treadwear Warranty

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
285/60R17 114H	.20462	8.5	8.0 - 10.0	30.5	11.5	726	9.0	12/32	42.5	51	2601	..\$
225/50R17 94H	..20463	7.0	6.0 - 8.0	25.9	8.9	813	7.8	11/32	26.9	51	1477
255/50R17 101H	..20464	8.0	7.0 - 9.0	27.2	10.2	807	8.7	11/32	32.2	51	1819
275/50R17 106H	..20465	8.5	7.5 - 9.5	28	10.8	755	9.4	11/32	36.0	51	2094
235/55R17 103W *RD	.45433	7.5	6.5-8.5	27.2	9.6	763	8.2	11/32	28.2	50	1929
265/60R18 110H	..20466	8.0	7.5 - 9.5	30.7	10.6	717	8.4	11/32	39.8	51	2337
235/50R18 101W *RD	.45434	7.5	6.5-8.5	27.3	9.6	761	8.2	11/32	28.4	50	1819
295/40R20 106W	..37021	10.5	10.0 - 11.5	29.3	11.9	710	11.9	11/32	36.9	51	2094
295/30R22 103W *RD	..37022	10.5	10.0 - 11.0	29.1	11.7	715	11.7	11/32	35.7	50	1929

*RD = REINFORCED

FALKEN ZIEX S/TZ 04 Performance Light Truck/SUV Radial



UTQG 460 AB
50,000 Limited
Treadwear Warranty

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
OUTLINED WHITE LETTER												
LT235/80R17/10 117R	.69164											..\$
LT235/75R15/6	..33103	6.5	6.0 - 7.0	29.3	9.3	712	7.3	16/32	36.2	50	1985
P235/75R16 106T	.69161	6.5	6.0-8.0	29.8	9.1	709	6.8	13/32	37.6	44	2094
P255/70R15 108S	..33107	7.5	6.5-8.5	29.3	10.3	751	7.4	12/32	35.1	51	2183
P265/70R15 110S	..33109	8	7.0 - 9.0	29.8	10.6	743	7.7	12/32	37	51	2337
LT30X9.50R15/6	..33105	7.5	6.5 - 8.5	29.3	9.7	720	7.3	16/32	36.2	50	1985
LT31X10.50R15/6	..33106	8.5	7.0 - 9.0	30.3	10.8	687	8.1	16/32	40.3	50	2270
P245/75R16 109S	..33110	7	6.5 - 8.0	30.6	9.7	720	7.7	13/32	35.3	51	2271
P265/75R16 114S	..37023	7.5	7.0 - 9.0	31.7	10.8	661	8.1	16/32	41.2	44	2601
LT285/75R16/8	..33104	8	7.5 - 9.0	33.1	10.7	644	8.7	17/32	51.8	65	3305
P235/70R16 104S	..37024	7.0	6.0 - 8.0	29.1	9.4	724	6.9	12/32	33.1	44	1984
P245/70R16 106S	..33112	7	6.5 - 8.0	29.6	9.7	745	7.2	12/32	34	51	2094
P255/70R16 109S	..33113	7.5	6.5 - 8.5	30.2	10.3	733	7.4	12/32	35.7	51	2271
P265/70R16 111S	..33114	8	7.0 - 9.0	30.7	10.6	716	7.7	12/32	37.5	51	2403
P275/70R16 114H	..33115	8	7.0 - 9.0	31.2	11	700	7.8	13/32	41	51	2601
LT275/70R18/10 122S	.69170										
255/70R17 112T	..69167	7.5	6.5-8.5	31.1	10	679	7.4	12/32	40.3	44	2469
P265/70R17 113T	..33118	8	7.0 - 9.0	31.8	10.8	675	7.7	12/32	40.6	51	2535
P275/60R17 110S	..37025	8.0	7.5 - 9.5	30.0	11.1	733	8.7	13/32	40.6	44	2337
P255/70R18 112S	..69168	7.5	6.5-8.5	32.1	10.1	658	7.4	Dec-32	41.8	44	2469
275/65R18 116H	..69169	8.7	7.5-9.5	32.1	10.9	664	8.1	13/32	45.1	51	2756
OUTLINED BLACK LETTER												
P215/70R16 99S	..33111	6.5	5.5 - 7.0	28	8.5	765	6.3	12/32	26.7	51	1709
P255/65R16 106S	..33116	7.5	7.0 - 9.0	29.3	9.8	750	7.4	12/32	32.2	51	2094
P235/60R16 99H	..33117	7	6.5 - 8.5	27.1	9.4	770	7.2	12/32	27.1	51	1709
BLACKWALL												
P235/75R17 108S	..69163	6.5	6.0-8.0	30.9	9.3	684	6.8	13/32	38.5	44	2205
P235/70R17 108S *RD	.69162	7	6.0-8.0	30	9.3	702	6.9	12/32	36.3	41	2205
P265/70R18 114S	..68483	8	7.0-9.0	32.7	10.6	645	7.7	10/32	44	44	2601
P245/70R17 108S	..69166	7	6.5-8.0	30.6	9.6	690	7.1	12/32	37.8	44	2205
245/65R17 107T	..68474	7	7.0-8.5	29.5	9.6	720	7.2	10/32	37	44	2149
P265/65R17 110T	..68481	8	7.5-9.5	30.5	10.6	697	7.8	10/32	39.2	44	2337
P255/65R17 108S	..68478	7.5	7.0-9.0	30.1	10.1	708	7.5	12/32	38.5	44	2205
P265/65R18 112S	..68482	8	7.5-9.5	31.6	10.6	674	7.8	10/32	42	44	2469
P275/60R18 113H	..68810	8	7.5	31.2	10.7	682	8.2	13/32	39.8	51	2535
285/60R18 116H	..23910	8.5	8.0 - 10.0	31.5	11.5	686	9	14/32	47.1	51	2756
255/55R18 109H *RD	.29154	8	7.0 - 9.0	29	10.1	730	8.7	14/32	37.5	50	2271
P275/60R20 114H	..68484	8	7.5-9.5	33	10.7	641	8.2	10/32	44.4	51	2601
275/55R20 117H *RD	..23911	8.5	7.5 - 9.5	32	11	662	9.4	14/32	46.1	50	2833
265/50R20 111H *RD	..23912	8.5	7.5 - 9.5	30.6	10.6	691	9	14/32	41.4	50	2469
285/50R20 112H	..68485	9	8.0-10.0	31.3	11.1	664	9	14	42	51	2469
295/50R20 118H *RD	..23914	9.5	8.0 - 10.5	31.7	11.9	666	10.1	14/32	47.0	50	2679
305/50R20 120H *RD	..29009	9.5	8.5 - 11.0	32	12.1	658	10.5	14/32	49.6	50	3086
P275/45R20 106H	..29010	9	8.5 - 10.0	29.7	10.7	701	9.2	14/32	39.6	51	2094
P295/45R20 114H *RD	..23915	10	9.5 - 11.0	30.4	11.6	686	9.8	14/32	42.2	50	2601
265/40R22 106H *RD	..37026	9.5	9.0 - 10.5	30.3	10.6	685	9.5	14/32	38.9	50	2094
265/35R22 102H *RD	..39566	9.5	9.0 - 10.5	29.3	10.6	710	9.6	14/32	37.3	50	1874
285/45R22 114H *RD	..39761	10	9.0 - 10.5	32	11	650	10	14/32	44	50	2601
285/40R22 115H *RD	..37027	10	9.5 - 11.0	31.0	11.1	670	10.3	14/32	43.2	50	2679
P305/45R22 118H *RD	..23916	10	9.5 - 11.5	32.7	12	635	10.2	14/32	52.4	50	2910
305/40R22 114H *RD	..39678	11	10.0 - 12.0	31.6	12.1	658	10.9	14/32	46.5	50	2601
285/35R23 106H *RD	..37028	10	9.5 - 11.0	30.8	11.0	674	10.3	14/32	41.6	50	2094
P305/40R23 115H *RD	..29198	10.5	10.0 - 12.0	32.8	12	634	11	14/32	51.3	50	2679
305/35R23 111H *RD	..40519	11	10.0 - 12.0	31.3	12.5	661	11.0	14/32	45.8	50	2403
305/25R23 100H *RD	..40518	11	10.5 - 11.5	29.1	12.4	707	11.6	14/32	41.3	50	1764
275/45R22 112H *RD	..69171	9	8.5-10.5	31.8	10.7	659	8.9	14/32	43.1	50	2469
305/45R24 120H *RD	..44546	10	9.5 - 11.5	37.8	11.7	598	10.2	14/32	51.8	50	3086
295/40R24 114H *RD	..40752	10.5	10.0 - 11.5	33.3	11.8	623	10.6	14/32	48.1	50	2601
295/35R24 110H *RD	..40750	10.5	10.0 - 11.5	32.2	11.6	642	10.6	14/32	45.0	50	2337
305/35R24 112H *RD	..40751	11	10.0 - 12.0	32.4	12.2	639	11.0	14/32	47.9	50	2469
305/30R26 109H *RD	..55197	11	10.5 - 11.5	33.3	12.0	619	11.6	14/32	48.1	50	2271

*RD=REINFORCED

FALKEN LANDAIR H/T Performance Light Truck/SUV Radial



50,000 Limited Treadwear Warranty

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	Tread RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
OUTLINED WHITE LETTER												
30X9.50R15/6	20473	7.5	6.5 - 8.5	28.9	9.8	706	6.8	13/32	34.6	50	1985	\$
31X10.50R15/6	20474	8.5	7.0 - 9.0	30.1	11	684	7.4	13/32	38.7	50	2270	
NEW LT235/75R15 6PLY	20472	6.5	6.0-7.0	28.9	9.4	728	6.8	14/32	32.4	50	1985	
LT235/75R15/6	20472	6.5	6.0 - 7.0	28.9	9.4	728	6.8	12024	32.4	50	1985	
LT245/75R16/10	20477	7	6.5 - 7.5	30.5	9.8	687	7.1	14/32	43.2	80	3042	
LT265/75R16/6	20478	7.5	7.0 - 8.0	31.7	10.5	683	7.6	13/32	40.6	50	2470	
OUTLINED BLACK LETTER												
LT215/85R16/8	20475	6	5.5 - 7.0	30.3	8.7	683	6.2	13/32	35.2	65	2335	
LT235/85R16/10	20476	6.5	6.0 - 7.0	31.7	9.3	655	6.9	14/32	43.4	80	3042	

FALKEN LANDAIR AP Performance Light Truck/SUV Radial



Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	Tread RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
RAISED OUTLINED WHITE LETTER												
205/75R14 95S	20489	5.5	5.0-7.5	26.0	8.0	797	5.9	13/32	22.5	35	1532	\$
LT215/75R15 6PLY	20479	6.0	5.5-7.0	27.7	8.5	750	6.2	13/32	30.2	50	1765	
215/75R15 100S	20491	6.0	5.5-7.0	27.7	8.4	769	6.2	13/32	28.9	35	1765	
225/75R15 102S	20492	6.0	6.0-8.0	28.3	8.7	752	6.5	13/32	28.3	35	1874	
235/75R15 105S	20493	6.5	6.0-8.5	28.9	9.3	736	6.8	14/32	33.1	35	2028	
235/75R15XL 108S	20494	6.5	6.0-8.5	28.9	9.3	736	6.8	14/32	35.7	41	2183	
LT235/75R15 6PLY	20480	6.5	6.0-7.0	28.9	9.3	722	6.8	14/32	35.0	50	1985	
30X9.50R15 6PLY	20481	7.5	6.5-8.5	28.9	9.7	733	6.8	14/32	35.0	50	1990	
31X10.50R15 6PLY	20482	8.5	7.0-9.0	30.1	11.0	692	7.4	14/32	41.1	50	2250	
LT225/75R16 8PLY	20485	6.0	6.0-7.0	29.3	8.7	730	6.5	16/32	36.2	65	2335	
LT245/75R16 6PLY	20486	7.0	6.5-7.0	30.6	9.7	699	7.1	16/32	41.5	50	2205	
LT245/75R16 10PLY	20487	7.0	6.5-7.0	30.6	9.7	698	7.1	16/32	43.8	80	3042	
LT265/75R16 8 PLY	20488	7.5	7.0-8.0	31.7	10.5	672	7.6	17/32	45.0	65	3000	
OUTLINED BLACK LETTER												
LT215/85R16 8PLY	20483	6.0	5.5-7.0	30.5	8.5	680	5.9	16/32	36.2	65	2335	
LT235/85R16 10PLY	20484	6.5	6.0-7.0	31.8	9.4	672	6.9	17/32	46.1	80	3042	

FALKEN HIGH COUNTRY A/T Performance Light Truck/SUV Radial



**UTQG 500 A B
UTQG 500 A A**

50,000 Limited Treadwear Warranty

**ALL-SEASON,
ALL-TERRAIN
TOUGHNESS**

- Four large circumferential grooves channel water out from under the contact patch in wet weather.
- Phase-shifted, random pitch block design for a smooth quiet ride.

Tire Size	Code #	Measuring UTQG	Approved Rim Width	Overall Diameter	Section Width	Tread RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE	
OUTLINED WHITE LETTER													
P215/75R15 100S	68438	500 A B	6.0	5.5 - 7.0	27.7	8.3	764	6.6	13	29.7	44	1742	\$
P225/75R15 102S	68439	500 A B	6.0	6.0 - 7.5	28.3	8.8	747	6.9	13	30.6	44	1874	
P235/75R15 105S	68440	500 A B	6.5	6.0 - 8.0	28.8	9.2	736	7.3	13	35.4	44	2028	
P265/75R15 112S	68441	500 A B	7.5	7.0 - 9.0	31.0	10.4	686	8.3	13	44.0	44	2469	
P245/75R16 109S	68443	500 A B	7.0	6.5 - 8.0	30.5	9.6	695	7.7	13	37.4	44	2271	
P265/75R16 114S	68444	500 A B	7.5	7.0 - 9.0	31.6	10.4	671	8.3	13	42.2	44	2601	
P235/70R15 102S	68445	500 A B	7.0	6.0 - 8.0	27.9	9.4	757	7.3	13	30.6	44	1896	
P225/70R16 101T	68448	500 A B	6.5	6.0 - 7.5	28.4	9.1	742	6.9	13	31.0	44	1819	
P235/70R16 104T	68449	500 A B	7.0	6.0 - 8.0	28.9	9.6	730	7.3	13	32.3	44	1984	
P245/70R16 106T	68450	500 A B	7.0	6.5 - 8.0	29.5	9.9	717	7.7	13	33.4	44	2094	
P255/70R16 109T	68451	500 A B	7.5	6.5 - 8.5	30.2	10.3	701	8.0	13	36.1	44	2271	
P265/70R16 111T	68452	500 A B	8.0	7.0 - 9.0	30.5	11.0	695	8.3	13	37.0	44	2403	
P265/70R17 113S	68454	500 A B	8.0	7.0 - 9.0	31.7	10.6	668	8.3	13	40.0	44	2535	
BLACKWALL													
P225/75R16 104S	68442	500 A B	6.0	6.0 - 7.5	29.3	8.9	721	6.9	13	33.2	44	1984	
P265/70R15 110S	68446	500 A B	8.0	7.0 - 9.0	29.7	10.7	715	8.3	13	36.5	44	2337	
P215/70R16 99S	68447	500 A B	6.5	5.5 - 7.0	27.8	8.7	758	6.6	13	28.2	44	1709	
P275/70R16 114T	68453	500 A B	8.0	7.0 - 9.0	31.1	10.8	681	8.6	14	38.5	44	2601	
OUTLINED WHITE LETTER													
235/65R17 104H	68456	500 A A	7.0	6.5 - 8.5	28.9	9.3	733	7.3	13	36.3	51	1984	
BLACKWALL													
255/65R16 109H	68455	500 A B	7.5	7.0 - 9.0	29.5	9.8	724	7.7	13	37.2	51	2271	
285/60R18 120H *	68457	500 A B	8.5	8.0 - 10.0	31.6	11.3	673	8.9	13	43.3	50	3086	
305/50R20 120H *	68458	500 A B	9.5	8.5 - 11.0	32.0	12.3	661	10.2	14	48.4	50	3086	
* REINFORCED													
OUTLINED WHITE LETTER													
LT30X9.5R15/6 104S	68425		7.5	6.5 - 8.5	29.5	9.7	715	7.4	16	36.3	50	1985	
LT31X10.5R15/6 109S	68426		8.5	7.0 - 9.0	30.5	10.9	693	8.3	17	42.5	50	2270	
LT235/75R15/6 104/101S	68429		6.5	6.0 - 7.0	28.8	9.1	751	7.2	16	34.8	50	1985	
LT245/75R16/6 108/104S	68431		7.0	6.5 - 8.0	30.5	9.7	709	7.6	16	39.4	50	2205	
LT245/75R16/10 120/116Q	68432		7.0	7.0 - 8.0	30.5	9.7	710	7.6	16	50.6	80	3042	
LT265/75R16/6 112/109S	68433		7.5	7.0 - 8.0	31.6	10.5	686	8.3	17	48.6	50	2470	
LT265/75R16/10 123/120Q	68434		7.5	7.0 - 8.0	31.7	10.5	684	8.3	17	54.6	80	3415	
LT285/75R16/8 122/119Q	68435		8.0	7.5 - 9.0	32.5	11.0	668	8.7	17	51.7	65	3305	
LT265/70R17/10 121/118S	68436		8.0	7.0 - 8.5	31.7	10.7	681	8.3	17	55.7	80	3195	
LT285/70R17/8 121/118S	68437		8.5	7.5 - 9.0	32.9	11.4	658	8.9	17	61.4	65	3195	
BLACKWALL													
LT215/85R16/10 115/112Q	68427		6.0	5.5 - 7.0	30.4	8.5	710	6.0	16	38.5	80	2680	
LT235/85R16/10 120/116Q	68428		6.5	6.0 - 7.5	31.7	9.3	683	6.7	16	49.5	80	3042	
LT225/75R16/10 115/112Q	68430		6.0	6.0 - 7.0	29.4	8.4	733	6.9	16	39.8	80	2680	

FALKEN WILDPEAK A/T Performance Light Truck/SUV Radial



UTQG 560 A B

*Metric Sizes Only

Four Wide Aggressive Multi Angled Grooves

Allows for maximum water, mud and snow evacuation while aggressive biting block edges provide unparalleled terrain traction.

Variable Block Shoulder Design

Reduces tire noise while maintaining an aggressive look.

Open Shoulder Grooves

Effectively disperses water and debris in all weather conditions for both on and off road performance.

Long Sweeping Sipes

Provides a multitude of biting edges for additional traction and ride comfort.

Tire Size	Code #	Measuring Rim Width	Approved Rim Width	Overall Diameter	Section Width	Tread RPM	Tread Width	Tread Depth	Shipping Weight	Max PSI (Cold)	Max Load (lbs)	PRICE
OUTLINED WHITE LETTER												
30X9.50R15 104S	.71708	7.5	6.0 - 8.5	29.6	9.7	714	7.5	16	38.5	50	1985	\$
31X10.50R15 109S	.71709	8.5	7.0 - 9.0	30.5	10.7	693	8.3	17	42.7	50	2270	
32X11.50R15 113S	.71710	9.0	8.0 - 10.0	31.5	11.6	671	9.1	17	46.6	50	2535	
LT245/70R16/8 113/110Q	.71714	7.0	6.0 - 7.0	29.6	9.7	703	7.7	16	46.8	65	2235	
LT245/75R16/10 120/116Q	.71716	7.0	6.5 - 8.0	30.6	9.7	683	7.6	16	53.5	80	3042	
LT265/70R16/8 117/114Q	.71718	8.0	7.0 - 8.5	30.8	10.5	679	8.3	17	51.9	65	2835	
LT265/70R17/10 121/118S	.71719	8.0	7.0 - 8.5	30.8	10.5	679	8.3	17	51.9	80	2835	
LT265/75R16/10 123/120Q	.71720	7.5	7.0 - 8.0	31.7	10.6	659	8.3	17	56.4	80	3415	
LT275/65R18/10 123/120Q	.71721	8.0	7.5 - 9.0	32.2	10.8	627	8.7	17	60.5	80	3415	
LT285/65R18/8 121/118S	.71722	8.5	8.0 - 10.0	32.6	11.2	643	9.1	17	60.6	65	3195	
LT285/75R16/8 122/119Q	.71724	8.0	7.0 - 9.0	32.9	11.1	636	8.9	17	62.0	65	3305	
245/65R17 107S *	.71727	7.0	7.0 - 8.5	29.6	9.5	718	7.8	13	37.2	44	2149	
255/65R17 110S *	.71729	7.5	7.0 - 9.0	30.2	10.1	706	8.1	13	39.5	44	2337	
255/70R17 112S *	.71730	7.5	6.5 - 8.5	31.1	10.0	679	8.0	13	40.9	44	2469	
265/70R18 116S *	.71732	8.0	7.0 - 9.0	32.6	10.8	648	8.3	13	51.1	44	2756	
OUTLINED BLACK LETTER												
33x12.50R15 108S	.71711	10.0	8.5 - 11.0	32.6	12.8	651	9.9	18	54.3	35	2205	
33X12.50R17/8 114S	.71712	10.0	8.5 - 11.0	32.5	12.5	648	10.1	17	62.7	50	2600	
LT225/75R16/8 110/107Q	.71713	6.0	6.0 - 7.0	29.4	8.7	709	7.0	15	38.6	65	2335	
LT245/70R17/10 119/116Q	.71715	7.0	6.0 - 8.0	30.7	9.5	678	7.7	16	52.8	80	3000	
LT245/75R17/10 121/118Q	.71717	7.0	6.0 - 7.5	31.5	9.7	662	7.6	16	54.1	80	3195	
LT285/70R17/8 121/118S	.71723	8.5	7.0 - 9.5	32.8	11.3	637	9.0	17	60.9	65	3195	
LT305/65R17/10 121/118S	.71725	9.0	8.5 - 11.0	32.6	12.1	643	9.7	17	63.6	65	3195	
LT305/70R16/10 124/121S	.71726	9.0	8.0 - 9.5	32.8	12.1	637	9.6	18	67.2	65	3525	
255/65R16 109S * BLK	.71728	7.5	7.0 - 9.0	29.1	10.2	733	8.1	13	38.1	44	2271	
265/65R17 112S * BLK	.71731	8.0	7.5 - 9.5	30.6	10.6	696	8.4	13	41.3	44	2469	
275/60R20 115S * BLK	.71733	8.0	7.5 - 9.5	33.1	10.9	640	8.8	13	46.1	44	2679	
285/50R20 116T * BLK	.71734	9.0	8.0 - 10.0	31.3	11.3	674	9.3	13	45.8	50	2756	

NO WARRANTY AVAILABLE

NEW 35X12.50R15LT	.74550	10	8.5 - 11.0	31.1	12.9	618	9.3	18	71.5	35	2535	
NEW 37X12.50R17LT	.74551	10	8.5 - 11.0	31.1	13	579	9.3	18	80.96	50	3525	
NEW 37X13.50R18LT	.74552	11	8.5 - 11.0	31.1	14.4	579	10.6	18	87.12	50	3525	
NEW 37X13.50R22LT	.74553	11	8.5 - 11.0	31.1	13.9	570	11.4	16	87.78	65	3415	
NEW 37X13.50R24LT	.74554	11	8.5 - 11.0	31.1	13.5	567	11.9	17	88.66	65	3085	
NEW LT325/50R22	.74555	10	9.0 - 12.0	32	13	598	11.2	17	79.2	65	3305	
NEW LT305/55R20	.74556	9.5	8.5 - 11.0	31.1	12.3	628	10.1	16	68.2	65	3195	
NEW LT325/60R18	.74557	9.5	9.0 - 12.0	32	12.8	630	10.6	17	77	65	3525	
NEW LT355/60R20	.74558	10	10.0 - 12.0	32	14.2	572	11.6	17	92.84	50	3640	
NEW LT305/65R18	.74559	9	8.5 - 11.0	31.1	12.3	627	9.7	16	72.16	65	3525	
NEW LT325/65R18	.74560	9.5	9.0 - 12.0	32	13	606	10.3	16	80.08	65	3860	
NEW LT315/70R17	.74565	9.5	8.0 - 11.0	31.1	12.5	610	9.6	17	78.1	50	3195	
NEW LT325/70R17	.74561	9.5	8.5 - 11.0	31.1	13.1	601	9.9	17	82.28	50	3195	
NEW LT315/75R16	.74562	9.5	8.0 - 11.0	31.1	12.7	608	9.5	16	76.56	50	3195	
NEW LT325/80R16	.74563	9	8.5 - 11.0	31.1	13.1	578	9.2	17	80.3	50	3525	
NEW LT295/70R17	.74564	8.5	7.5 - 10.0	30	11.8	630	9	16	74.14	85	3195	

visit us at:



OPEN 24 HRS / 7 DAYS A WEEK