

FUZION™

ZRi

High Performance



UTQG 320 A A

Tire Size	Code #	Design Rim Width	Optional Rim Width	Section Width	Overall Diameter	Tread Width	Tread Depth (32nds)	Static Loaded Radius	Weight	PRICE
205/55R15 88W	.68257	.65	5.5-7.5	.83	23.9	.66	.10	.11	.22	..\$
195/50R15 82W	.68258	.6	5.5-7.0	.78	22.7	.63	.10	.10.5	.19	
205/50R15 86W	.68259	.65	5.5-7.5	.83	23.1	.66	.10	.10.6	.21	
225/60R16 98W	.68260	.65	6.0-8.0	.89	26.6	.73	.10	.12.1	.28	
205/55R16 91W	.68261	.65	5.5-7.5	.83	24.9	.66	.10	.11.5	.23	
225/55R16 95W	.68262	.7	6.0-8.0	.91	25.7	.72	.10	.11.8	.26	
205/50R16 87W	.68263	.65	5.5-7.5	.83	24.1	.66	.10	.11.1	.24	
225/50R16 92W	.68264	.7	6.0-8.0	.91	24.9	.72	.10	.11.5	.24	
245/50R16 97W	.68265	.75	7.0-8.5	.99	25.7	.79	.10	.11.8	.28	
205/45R16 83W	.68266	.7	6.5-7.5	.82	23.2	.71	.10	.10.8	.21	
245/45R16 94W	.68267	.8	7.5-9.0	.96	24.6	.86	.10	.11.3	.26	
215/50R17 XL 95W	.68268	.7	6.0-7.5	.88	25.5	.69	.10	.11.8	.25	
255/50R17 101W	.68269	.8	7.0-9.0	1.04	27.1	.82	.10	.12.4	.31	
215/45R17 87W	.68270	.7	7.0-8.0	.85	24.6	.75	.10	.11.4	.23	
225/45R17 91W	.68271	.75	7.0-8.5	.89	25	.79	.10	.11.6	.24	
235/45R17 94W	.68272	.8	7.5-9.0	.94	25.4	.81	.10	.11.8	.25	
245/45R17 95W	.68273	.8	7.5-9.0	.96	25.7	.86	.10	.11.9	.28	
255/45R17 98W	.68289	.85	8.0-9.5	1.01	26.1	.89	.10	.12	.29	
205/40R17 XL 84W	.68274	.75	7.0-8.0	.84	23.5	.7	.10	.11	.20	
215/40R17 83W	.68275	.75	7.0-8.5	.87	23.8	.74	.10	.11.1	.21	
235/40R17 90W	.68276	.85	8.0-9.5	.96	24.4	.8	.10	.11.4	.24	
245/40R17 91W	.68277	.85	8.0-9.5	.98	24.7	.85	.10	.11.5	.25	
255/40R17 94W	.68278	.9	8.5-10.0	1.03	25	.88	.10	.11.6	.27	
275/40R17 98W	.68290	.95	9.0-11.0	.11	25.7	.95	.10	.11.9	.29	
285/60R18 116H	.68279	.85	8.0-10.0	.11.5	31.5	.92	.10	.14.2	.43	
225/40R18 88W	.68280	.8	7.5-9.0	.91	25.1	.78	.10	.11.8	.24	
235/40R18 91W	.68281	.85	8.0-9.5	.96	25.4	.8	.10	.11.9	.25	
245/40R18 93W	.68282	.85	8.0-9.5	.98	25.7	.85	.10	.12	.27	
215/35R18 84W	.68283	.75	7.0-8.5	.86	23.9	.69	.10	.11.3	.21	
265/35R18 93W	.68284	.95	9.0-10.5	1.07	25.3	.91	.10	.11.8	.27	
225/35R19 88W	.68285	.8	7.5-9.0	.91	25.2	.78	.10	.11.9	.23	
235/35R19 91W	.68286	.85	8.0-9.5	.96	25.5	.8	.10	.12	.25	
245/35R19 93W	.68287	.85	8.0-9.5	.98	25.8	.85	.10	.12.1	.27	
275/30R19 96W	.68288	.95	9.0-10.0	.11	25.6	.95	.10	.12.1	.28	
275/55R20 111H	.68291	.85	7.5-9.5	1.12	31.9	.9	.10	.14.6	.45	
265/50R20 106V	.68293	.85	7.5-9.5	1.06	30.5	.85	.11	.14	.39	
275/45R20 106V	.68292	.9	8.5-10.0	1.08	29.8	.86	.10	.13.8	.38	
255/35R20 93W	.68594	.9	8.5-10.0	1.03	27	.88	.10	.12.7	.29	

- **COCS** - A comprehensive Tire Design Method. This method improves handling in wet or dry conditions and reduces irregular treadwear by combining the ideal tread design, casing shape, materials, and construction.
- **O BEAD** - Rounder is better - Rounder overall tire shape provides better balance for wet or dry handling.
- **L.L. Carbon** - Longer is stronger - L.L. Carbon utilizes a special form of molecular re-engineered carbon black, a key factor in improving tire wear while enhancing wet performance. As a reinforcing agent, silica improves both flexibility and grip.
- **Rim Guard** - The raised rubber ridge acts like a bumper to protect wheels from curb damage.
- **Directional Tread Pattern** design contributes to both wet and dry performance as well as enhancing other tire characteristics such as resistance to hydroplaning.

VRi

High Performance



UTQG 400 A A

40,000 MILE TREADWEAR LIMITED WARRANTY

Tire Size	Code #	Design Rim Width	Optional Rim Width	Section Width	Overall Diameter	Tread Width	Tread Depth (32nds)	Static Loaded Radius	Weight	PRICE
195/55R15 85V	.68295	.6	5.5-7.0	.77	24.6	.67	.11	.11.3	.21	..\$
215/60R16 95V	.68298	.65	6.0-7.5	.85	26.1	.75	.11	.11.9	.26	
205/55R16 91V	.68297	.65	5.5-7.5	.81	24.9	.66	.11	.11.5	.24	
205/50R16 87V	.68296	.65	5.5-7.5	.81	24.1	.66	.11	.11.1	.21	
225/50R16 92V	.68299	.7	6.0-8.0	.89	24.9	.72	.11	.11.2	.26	
215/55R17 94V	.68300	.7	6.0-7.5	.89	26.3	.75	.11	.12.1	.27	
225/55R17 97V	.68301	.7	6.0-8.0	.92	26.8	.78	.11	.12.3	.29	
215/50R17 95V	.68302	.65	5.5-7.5	.89	25.5	.74	.10	.11.8	.27	

- **COCS** - A comprehensive Tire Design Method. This method improves handling in wet or dry conditions and reduces irregular treadwear by combining the ideal tread design, casing shape, materials, and construction.
- **O BEAD** - Rounder is better- Rounder overall tire shape provides better balance for wet or dry handling.
- **L.L. Carbon** - Longer is stronger- L.L. Carbon utilizes a special form of molecular re-engineered carbon black, a key factor in improving tire wear while enhancing wet performance. As a reinforcing agent, silica improves both flexibility and grip.
- **Rim Guard** - The raised rubber ridge acts like a bumper to protect wheels from curb damage.
- **Directional Tread Pattern** design contributes to both wet and dry performance as well as enhancing other tire characteristics such as resistance to hydroplaning.



UTQG 400 A A

40,000 MILE TREADWEAR LIMITED WARRANTY

Tire Size	Code #	Design Rim Width	Optional Rim Width	Section Width	Overall Diameter	Tread Width	Tread Depth (32nds)	Static Loaded Radius	Weight	PRICE
185/60R14 82H	68307	5.5	5.5-6.5	7.4	22.8	6.4	11	10.4	.18	..\$
195/60R14 86H	68308	6	5.5-7.0	7.9	23.2	6.8	11	10.6	.20	..
185/65R15 88H	68303	5.5	5.0-6.5	7.4	24.5	6.4	11	11.2	.22	..
195/65R15 91H	68304	6	5.5-7.0	7.9	25	6.8	11	11.4	.23	..
205/65R15 94H	68305	6	5.5-7.5	8.2	25.5	7.1	11	11.6	.24	..
215/65R15 96H	68306	6.5	6.0-7.5	8.7	26	7.5	11	11.8	.26	..
195/60R15 88H	68309	6	5.5-7.0	7.9	24.2	6.8	11	11.1	.22	..
205/60R15 91H	68310	6	5.5-7.5	8.2	24.7	7.1	11	11.3	.24	..
215/60R15 94H	68311	6.5	6.0-7.5	8.7	25.2	7.5	11	11.5	.25	..
225/60R15 96H	68312	6.5	6.0-8.0	9	25.6	7.8	11	11.6	.26	..
205/60R16 92H	68313	6	5.5-7.5	8.2	25.7	7.1	11	11.8	.25	..
215/60R16 95H	68314	6.5	6.0-7.5	8.7	26.1	7.5	11	11.9	.26	..
225/60R16 98H	68315	6.5	6.0-8.0	9	26.6	7.8	11	12.1	.28	..
205/55R16 91H	68316	6.5	5.5-7.5	8.4	24.9	7.1	11	11.5	.24	..
215/55R16 93H	68317	7	6.0-7.5	8.9	25.3	7.5	11	11.6	.25	..
225/55R16 95H	68318	7	6.0-8.0	9.2	25.8	7.8	11	11.8	.28	..
205/50R16 87H	68319	6.5	5.5-7.5	8.4	24.1	7.1	11	10.6	.22	..
225/50R16 92H	68320	7	6.0-8.0	9.2	24.9	7.8	11	11.5	.25	..
215/50R17 91H	68321	7	6.0-7.5	8.9	25.5	7.4	11	11.8	.25	..
215/45R17 87H	68322	7	7.0-8.0	8.4	24.6	7.5	11	11.4	.23	..
225/45R17 91H	68323	7.5	7.0-8.5	8.9	25	7.8	11	11.6	.24	..
235/45R17 94H	68324	8	7.5-9.0	9.3	25.4	8.1	11	11.8	.25	..
245/45R17 95H	68325	8	7.5-9.0	9.6	25.7	8.5	11	11.9	.25	..
205/40R17 XL 84H	68326	7.5	7.0-8.5	8.3	23.5	7	11	11	.20	..

- **COCS** - A comprehensive Tire Design Method. This method improves handling in wet or dry conditions and reduces irregular treadwear by combining the ideal tread design, casing shape, materials, and construction.
- **O BEAD** - Rounder is better - Rounder overall tire shape provides better balance for wet or dry handling.
- **L.L. Carbon** - Longer is stronger - L.L Carbon utilizes a special form of molecular re-engineered carbon black, a key factor in improving tire wear while enhancing wet performance. As a reinforcing agent, silica improves both flexibility and grip.
- **Rim Guard** - The raised rubber ridge acts like a bumper to protect wheels from curb damage.
- **Asymetric Tread Pattern** design contributes to both wet and dry performance as well as enhancing other tire characteristics such as resistance to hydroplaning.
- **5 Noise Reduction** - Arranges tread block elements to produce noise-canceling sound waves, significantly reducing the noise of the tire moving on the road surface.



UTQG 400 A B

Tire Size	Code #	Design Rim Width	Optional Rim Width	Section Width	Overall Diameter	Tread Width	Tread Depth (32nds)	Static Loaded Radius	Weight	PRICE
225/70R16 101T	68327	6.5	6.0-7.5	9	28.4	6.9	10	12.4	.29	..\$
235/70R16 104T	68328	7	6.0-8.0	9.3	29	7.2	11	12.7	.31	..
245/70R16 106S	68329	7	6.5-8.0	9.8	29.5	7.5	13	13.2	.34	..
255/70R16 109S	68330	7.5	6.5-8.5	10.2	30.1	7.8	13	13	.38	..
265/70R16 111S	68331	8	7.0-9.0	10.6	30.6	8.1	14	13.6	.39	..
265/70R17 113S	68332	8	7.0-9.0	10.7	31.7	8.1	14	14.1	.41	..
235/65R17 103T	68333	7	6.5-8.5	9.8	29.1	7.2	10	13	.30	..
245/65R17 105S	68334	7	7.0-8.5	9.6	29.5	7.5	13	13.4	.34	..
265/65R17 110T	68335	8	7.5-9.5	10.7	30.6	8.1	11	13.8	.37	..
275/65R18 114T	68336	8	7.5-9.5	11	32.1	8.4	11	14.8	.41	..
285/60R18 120S RE	68337	8.5	8.0-10.0	11.6	31.5	9	14	14.2	.44	..
275/60R20 114S	68338	8	7.5-9.5	11	33	9.2	11	14.7	.46	..
275/55R20 111S	68339	8.5	7.5-9.5	11.2	31.9	9.3	11	14.3	.44	..
LT315/75R16 121R/8	68341	8.5	8.0-10.0	12.3	34.6	9.6	17	15.9	.59	..
LT315/70R17 121/118R/8	68344	9.5	8.5-10.0	12.7	34.5	9.6	17	15.9	.59	..
LT325/65R18 127/124R/10	68342	9.5	9.0-12.0	13	34.6	10.2	17	16.1	.66	..
LT325/60R18 124/121R/10	68343	9.5	9.0-12.0	13	33.4	10.9	17	15.4	.65	..

- **COCS** - A comprehensive Tire Design Method. This method improves handling in wet or dry conditions and reduces irregular treadwear by combining the ideal tread design, casing shape, materials, and construction.
- **O BEAD** - Rounder is better- Rounder overall tire shape provides better balance for wet or dry handling.
- **L.L. Carbon** - Longer is stronger- L.L Carbon utilizes a special form of molecular re-engineered carbon black, a key factor in improving tire wear while enhancing wet performance. As a reinforcing agent, silica improves both flexibility and grip.
- **Rim Guard** - The raised rubber ridge acts like a bumper to protect wheels from curb damage.
- Reversible tribal tattoo and flame graphic sidewall.
- Unique 3D "Half Pipe" tread elements.